## G-Sicherungseinsätze

No. 520.100

Fuse-links

super quick-acting

### 5 x 20 mm

FF Werknorm







#### Aufbau:

100 mA-1,25 A Glasrohr, durchsichtig

1,6-12,5 A Keramikrohr

Kontaktkappen:

Messing, vernickelt

Lötbarkeit: gemäß EN 60068-2-20 Verpackungsmöglichkeiten: 100 St. = 10 x 10er Faltschachteln

1000 St. = Industrieverpackung (lose geschüttet

in Faltkarton)

Als Baugruppe mit 2 Aufsteckkappen in beliebiger Form und Länge, fertig montiert

#### Construction:

100 mA-1,25 A Glasstube, transparent

1,6-12,5 A ceramic-tube

Contact caps: Brass, nickel plated

Solderability: by EN 60068-2-20

Packing options:

100 pcs. = 10 boxes of 10 pieces

1000 pcs. = Industrial box (loose in carton) As assembly with two pigtails in various forms

and lengths, finally mounted

### Bemessungswerte / Ratings

Art No.	Strom Current	Spannung Voltage	Ausschaltvermögen Breaking capacity	Spannungsfall Voltage drop max [mV]	Schmelzintegral Melting integral [A <sup>2</sup> s]		
520.107	100 mA	250 V	35 A	3000	0,0020		
520.108	125 mA	250 V	35 A	0,0031			
520.109	160 mA	250 V	35 A	3000	0,0051		
520.110	200 mA	250 V	35 A	35 A 2000			
520.111	250 mA	250 V	35 A	2000	0,0312		
520.112	315 mA	250 V	35 A	2000	0,0674		
520.113	400 mA	250 V	35 A	1500	0,0960		
520114	500 mA	250 V	35 A	1500	0,1700		
520.115	630 mA	250 V	35 A	500	0,1600		
520.116	800 mA	250 V	35 A	500	0,3200		
520.117	1 A	250 V	35 A	250	0,5400		
520.118	1,25 A	250 V	35 A	250	1,2500		
520.119	1,6 A	250 V	1500 A	1000	0,2600		
520.120	2 A	250 V	1500 A	700	1,9200		
520.121	2,5 A	250 V	1500 A	700	2,7500		
520.122	3,15 A	250 V	1500 A	600	3,7700		
520.123	4 A	250 V	1500 A	600	6,4000		
520.124	5 A	250 V	1500 A	500	12,0000		
520.125	6,3 A	250 V	1500 A	500	18,0000		
520.126	8 A	250 V	1500 A	400	31,0000		
520.127	10 A	250 V	1500 A	400	50,0000		
520.128	12,5 A	250 V	1500 A	300	62,5000		

#### Schmelzzeit-Grenzwert / Pre-arcing time limits

Bemessungstrom	1,0 I <sub>rat</sub>	1,5 I <sub>rat</sub>	2000	75 I <sub>rat</sub>	10000	I <sub>rat</sub>	10 I <sub>rat</sub>
Rated current	min.	max.	min.	max.	min.	max.	max.
100 mA - 12,5 A	1 h	30 min.	2 ms	100ms	1 ms	50ms	5 ms

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cartridge Fuses category:

Click to view products by Eska manufacturer:

Other Similar products are found below:

MBO-20 MDA-V-1/100 12C10X38GI AGA-V-2-1/2 AGC-V-3-12-R AGY-50 MSL-3 MSL-4 MSL-5 BK1/C436-2A BK1-GMA-1-6-R BK1-GMA-200-R BK1GMA-6-R BK1/GMC-100-R BK1/GMC-1.5-R BK1-GMC-2-5-R BK1GMD-4-R BK1S500-250-R BK1S500-32-R BK1-S500-4-R BK1S500-5-R BK1-S505-1-R BK1-S506-2-R BK1-S506-3-15-R BK1/S506-63-R BK/ABC-5RX BK/AGW-B-4 BK/AVX-1/4 BK/C515S-250-R BK/MBO-20 BK/MBO-8 BK/MDM-3/4 BK-MDQ-4 BK/S505-V-2.5A BK/TDC120-15 BK/TDC120-20 BK/TDC122-45 BP/MDL-7 1C10X38AM S505-V-500MA SEF-1697-1-002 AGA-V-7-1/2 AGC-15WX AGC-2-1-2-R 20.0M6.3X32F 20C8X32GI GMC-50-R 361.250 MBO-8 TDC121-30