G-Sicherungseinsätze

No. 525.600

Fuse-links quick-acting

5 x 25 mm

Werknorm

flink







Aufbau:

32 mA - 1,25 A: Glasrohr, durchsichtig 1,6 A - 10 A: Glasrohr, mit Löschmittel

Kontaktkappen: Messing, vernickelt

Lötbarkeit: gemäß EN 60068-2-20

Verpackungsmöglichkeiten:

100 St. = 10 x 10er Faltschachteln

1000 St. = Industrieverpackung (lose geschüttet

in Faltkarton)

Als Baugruppe mit 2 Aufsteckkappen in beliebiger

Form und Länge, fertig montiert

Construction:

32 mA-1,25 A: Glasstube, transparent 1,6 -10 A:Glasstube, with extinguishing agent

Contact caps:

Brass, nickel plated Solderability: by EN 60068-2-20

Packing options:

100 pcs. = 10 boxes of 10 pieces

1000 pcs. = Industrial box (loose in carton)

As assembly with two pigtails in various forms and

lengths, finally mounted

Bemessungswerte / Ratings

Q							
Art No.	Strom Current	Spannung Voltage	Ausschaltvermögen Breaking capacity	Spannungsfall Voltage drop max [mV]	Schmelzintegral Melting integral [A ² s]		
525.602	32 mA	250 V	50 A				
525.603	40 mA	250 V	50 A		auf Anfrage /		
525.604	50 mA	250 V	50 A		on request		
525.605	63 mA	250 V	50 A				
525.606	80 mA	250 V	50 A				
525.607	100 mA	250 V	50 A		0,00390		
525.608	125 mA	250 V	50 A		0,0084		
525.609	160 mA	250 V	50 A		0,0154		
525.610	200 mA	250 V	50 A	auf Anfrage /	0,0292		
525.611	250 mA	250 V	50 A	on request	0,0650		
525.612	315 mA	250 V	50 A		0,16		
525.613	400 mA	250 V	50 A		0,26		
525.614	500 mA	250 V	50 A		0,25		
525.615	630 mA	250 V	50 A		0,47		
525.616	800 mA	250 V	50 A		Auf Anfrage		
525.617	1 A	250 V	50 A		1,16		
525.618	1,25 A	250 V	50 A		2,03		
525.619	1,6 A	250 V	80 A		1,28		
525.620	2 A	250 V	80 A		5,76		
525.621	2,5 A	250 V	80 A		8,13		
525.622	3,15 A	250 V	80 A		13,30		
525.623	4 A	250 V	80 A		21,12		
525.624	5 A	250 V	80 A		42,25		
525.625	6,3 A	250 V	80 A		103,59		
525.626	8 A	250 V	80 A		126,72		
525.627	10 A	250 V	100 A		208,00		

Schmelzzeit-Grenzwert / Pre-arcing time limits

Bemessungstrom	1,5 I _{rat}	2,1 I _{rat}	4 I _{rat}	10 I _{rat}
Rated current	min.	min. max.	min. max.	max.
80 mA – 10 A	1 h	30 min	300 ms	20 ms

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cartridge Fuses category:

Click to view products by Eska manufacturer:

Other Similar products are found below:

MBO-20 MDA-V-1/100 12C10X38GI AGA-V-2-1/2 AGC-V-3-12-R AGY-50 MSL-3 MSL-4 MSL-5 BK1/C436-2A BK1-GMA-1-6-R BK1-GMA-200-R BK1GMA-6-R BK1/GMC-100-R BK1/GMC-1.5-R BK1-GMC-2-5-R BK1GMD-4-R BK1S500-250-R BK1S500-32-R BK1-S500-4-R BK1S500-5-R BK1-S505-1-R BK1-S506-2-R BK1-S506-3-15-R BK1/S506-63-R BK/ABC-5RX BK/AGW-B-4 BK/AVX-1/4 BK/C515S-250-R BK/MBO-20 BK/MBO-8 BK/MDM-3/4 BK-MDQ-4 BK/S505-V-2.5A BK/TDC120-15 BK/TDC120-20 BK/TDC122-45 BP/MDL-7 1C10X38AM S505-V-500MA SEF-1697-1-002 AGA-V-7-1/2 AGC-15WX AGC-2-1-2-R 20.0M6.3X32F 20C8X32GI GMC-50-R 361.250 MBO-8 TDC121-30