# DC/YTLY 2 × 0.5mm<sup>2</sup> braid 1-5028/polyester

MULTI-WIRE STRANDED LOW VOLTAGE BRAIDED CABLE

#### **INDEX:**

OP-YTLY1-5028

### **APPLICATION:**

Designed for telecommunication devices, components, electronic devices, control systems, data processing devices, LED lighting, furniture industry, and interior installations.

#### **CONSTRUCTION:**

Conductors are made of copper stranded wires, double insulated by PVC, polyurethane braid. Braided cables are characterized by high elasticity, resistance to stretching and are extremely durable. A polyester braid protects the cable against mechanical damage, extending the life of the cable and increasing the safety.



22

#### MARKING SYSTEM: OP-YTLY1-5028



number of braid color 5028

number of the braid pattern 1

--- cable type, round shape **YTLY** 

series of cables with a polyester braid OP

### **SPECIFICATION:**

| Parameter                                  | Value              |
|--|--------------------|
| Working temperature range [°C]             | -15 70             |
| Rated voltage [V]                          | 150 V              |
| Insulation withstand test, 50 Hz [VAC]     | 2000               |
| Rated current [A]                          | 5                  |
| Isolation material                         | PVC class TI2      |
| Coating                                    | PVC class TM2      |
| Core cross-section area [mm <sup>2</sup> ] | 2 × 0.5            |
| Diameter with insulation [mm]              | 1.5                |
| Colors of the wires insulation             | White/red          |
| Core material                              | Cuprum             |
| Cable outer diameter [mm]                  | Ø 4.40             |
| Coating color                              | White              |
| Braid material                             | Polyester          |
| Braid color                                | light brown / 5028 |
| Braid thermal resistance                   | Melting at 170°C   |
| LVD 2014/35/UE                             | Compliant          |
| ROHS 2015/863                              | Compliant          |
| Packaging                                  | Reel               |
| Cable length on a reel [m]                 | 50                 |

The cable cannot be used for high-current installation outside devices

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for AC Power Leads category:

Click to view products by Espe manufacturer:

Other Similar products are found below :

62500-1774 130000023 312033-01 YP-61+YC12 P28818-M2 YP21A+YC13 FTP-629Y603 1702002600 1700001947 J2014004L001-CC SHELF IL13-EU1-H05-3100-300-S P28976-M45 BB-3271V86 HFE/C19UO MWOC-PCA-3-3-2 P29844-M5 P29844-M10 3-100-354 S002020062 S007220307 P28818-M6 1019123 387005324 387005325 5990300000 VL-0136-14-200 387007040 387006821 387006827 387006823 387006932 387006822 AC06C13EU 1036702 AC06C05UK P28984-M2 50365 W-97023 W-01528 W-01529 W-01530 W-01531 W-97020 W-97022 W-97021 W-97025 W-97057 W-97288 W-97292 W-97370