



NOTE: Threaded parts must accept 2A GO gage.  
Per current fastener industry practice,  
if form, fit, and function are achieved,  
parts may accept 2A NO GO.

FOR CUSTOMER APPROVAL ONLY				REV	BY	DATE	COMMENT	DIMENSIONS ARE IN INCHES		DRAWN	VRR	 INNOVATIVE COMPONENTS
NAME:	0	T-M	11/20/00				RELEASE DATE	FRACTIONAL ±	APPROVED	LQR		
	1	VRR	06/03/14				Changed to SolidWorks format	TWO PLACE DECIMAL ± 0.03	DATE	06/03/2014		1.38" Fluted Knob 10-24 x 1" Steel, Zinc
TITLE:								THREE PLACE DECIMAL ± 0.010	COMMENTS			
								UNLESS OTHERWISE NOTED	MIN. TORQUE N/A in.-lbs.			KN041000F2---21
DATE:	<b>PROPRIETARY AND CONFIDENTIAL</b> THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INNOVATIVE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INNOVATIVE COMPONENTS IS PROHIBITED.							KNOB MATERIAL	INSERT	Steel		
								KNOB FINISH	Textured			SCALE 1:1
SIGNATURE:								INSERT PART NUMBER	MS041250RS---21	FINISH	Zinc	

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Knobs & Dials](#) category:*

*Click to view products by [ESSENTRA](#) manufacturer:*

Other Similar products are found below :

[790-1030](#) [790-1202](#) [790-2226](#) [8519](#) [8529](#) [8547](#) [85-559](#) [8573](#) [11K5015-EMNB](#) [11K5019-ECNB](#) [11K5020-KLAB](#) [11K5048-KMNB](#)  
[11K5014-EMNB](#) [11K5015-EMNG](#) [11K5019-EMNB](#) [MS91528-2N2B](#) [1770](#) [P400S-08-D6-N](#) [K6510](#) [KNP700A1/4](#) [3045B](#) [AR22PY-122B](#)  
[PKJ50B18](#) [277A](#) [348003](#) [42000B38](#) [420114B14](#) [5006](#) [56008-001](#) [KS700B14](#) [411](#) [420037B14](#) [WA-101C-P](#) [WA-102B](#) [WA-103](#) [WA-109B](#)  
[WA-1450-P](#) [WA-1550](#) [WA-1600-P](#) [WA-2300](#) [WA-4100](#) [WA-4108-P](#) [0166736-006](#) [0195316-052](#) [0703006-003](#) [0744386-211](#) [52-928.20](#)  
[52-928.9](#) [8517](#) [8545](#)