					Ø5.80 [.228 in]					
					15.: [.622	- 80 : in]				
2. G 3. V	ALL DIMEN GENERAL T /OLTAGE"	SIONS IN MM [INCH] DLERANCE: X.X=±0.4 X.XX=±0.25 L2V DC TEMP.: -20°C TO +60°C				¢	E◆SWI	GREEN LED PARAMETERS SYMBOL TYP. UNITS AVE CURRENT IA 19 mA EMISION WAVELENGTH λP 525 nm LUMINOUS INTESTITY IF 700 mcd		
В	20381	UPDATE AND CONVERT	01/05/12	BMA	TITLE 50-004-19M					
	PCR NO	DESCRIPTION	DATE	BY	SCALE	DATE	DR	DWG	REV	
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED						1/5/2012	BMA	F050419	B	

SHEET 1 OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Fixings category:

Click to view products by E-Switch manufacturer:

Other Similar products are found below :

 893102000
 00-5150
 LZZ1A
 0098.9234
 61-9451.0
 M2PA-5011
 630155
 635401
 6PA113
 6PA147-E6
 6PA148-E6
 6PA32
 6PA9
 700106

 700109
 700303A56
 700C1GRY
 700C2GRN
 704-6001
 704.965.2
 704.965.6
 704.966.0
 7089-3
 710082-B11
 71M1048

 757200264
 764300000
 MHU35
 MHU37
 807039-1
 825.003.011
 825.053.011
 825.055.011
 826.000.071
 827.020.011

 827.400.021
 835.900.023
 MML52C10C
 MML52E10C
 MML92HGH
 MML93K
 84211M02CNNS
 84212M02CNNS
 84217A8.0LNOS

 842.500.011
 843187-000
 843487-000
 843487-000
 843487-000
 843487-000