

SERIES 500 A SWITCHES

SLIDE SWITCHES - SUB-MINIATURE

APPLICATIONS/MARKETS

Computer servers/peripherals

.200 5.08

.400

10.16

198

2.49

.122

Consumer electronics
Instrumentation

▶ Test & measurement



NAVIGATION

PUSHBUTTON SWITCHES

TOGGLE

FEATURES & BENEFITS Panel, SMT & PC board mountable

Sub-miniature

ROCKER

SLIDE

SNAP-ACTION SWITCHES

DIP

KEYLOCK



ROTARY SWITCHES



CAP




2 Comm. 1 ∳ 3● .120

.100 2.54

SPECIFICATIONS	
Contact Rating:	3 A @ 120 VAC cURus 1 A @ 250 VAC cURus
Life Expectancy:	30,000 make-and-break cycles at full load
Contact Resistance:	10 m Ω max. typical @ 2-4 VDC 100mA for both silver and gold plated contacts
Insulation Resistance:	1,000MΩ min.
Dielectric Strength:	1,000 V rms at sea level
Operating Temperature:	-30°C to 85°C

MATERIALS	
Case:	Diallyl phthalate (DAP)
Housing:	Stainless steel
Slide Handle:	Nylon
Contact & Terminals:	Gold or Silver plated copper alloy



10.94

EPEXY SEAL

020 0.51

.320 8.13

.130

3.30




2

() = Momentary



P.C. MOUNTING OPTIONS



info@e-switch.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Slide Switches category:

Click to view products by E-Switch manufacturer:

Other Similar products are found below :

6-1437581-1 M43R MHS123K15D MHS133K MHSS1104A MMD GH49S010001 MSS12A EPS1PC1 1825074-1 1825160-3 1825167-2 1825289-7 K232CB 25139NLDB 25449NAH SLB1240R45 1825078-1 1825080-4 1825269-1 1825270-2 STS141RA04 T2215BEN506 GH46P000001 GH46W000001 GH49P010001 25339NA M42A TG36P000000 TG36P000050 AYZ0202AG 47227LFE 49331L 50208L L203091MS02Q 4-1437581-7 X2225CR-437W 49329L 1101M1S3ZB8E2 1-1437581-1 MSS2225G04 TG39W000000 1825075-1 MSS42G TG36WS80065 T105S1CWZBE SLB124145 SLB1280R5 SLB1340R45 25136NLDB