


RECOMMENDED P.C.B. LAYOUT

LED SPECIFICATION	SYMBOL	RED L.E.D.		GREEN L.E.D.		UNITS
		MAX.	MIN.	TYP.	MAX.	
POWER DISSIPATION	P _d	80	--		100	mW
FORWARD VOLTAGE	V _F	2.8	1.9	2.2	2.8	V
REVERSE VOLTAGE	V _R	5			5	V
EMISSION WAVELENGTH	λ _p			695		nm
AVE. FORWARD CURRENT	I _{AF}	30	--		30	mA
LUMINOUS INTENSITY	I _v		0.7	22		mcd



CIRCUIT: SPDT
CONTACT CONFIGURATION

- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NO. FOR REF. ONLY
 4. RATING: 12mA @24V
 5. FIXED CONTACT/MOVING CONTACT:
COPPER ALLOY W/GOLD PLATE
 6. CONTACT BOUNCE: <5m SEC.
 7. CONTACT RESISTANCE: <50milli-ohms



B	21713	Description was 5511M12	12/16/14	r-c
A	12128	RELEASED FOR PRODUCTION	5/8/02	CJB
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		SCALE		DATE		DR		DWG		REV	
5511M12KREDGRN		1.5:1		5/8/02		CJB		XR0166P		B	

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pushbutton Switches](#) category:

Click to view products by [E-Switch](#) manufacturer:

Other Similar products are found below :

[8940K2012](#) [LW1L-M1C10V-A](#) [LW1L-M1C70-A](#) [LW2L-A1C20M-GD](#) [LW2L-M1C20M-A](#) [60324L](#) [M22-D-R-GB0/K11](#) [M7E-HRN2](#)
[67021K512](#) [67081K512X](#) [701PB580](#) [7190K101](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [MML21EA2ADK](#) [MML21KA3ABK](#)
[MML23KA3AC05K-001](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#) [861K11911T01A07](#)
[861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [8646ABUL](#) [9001KXRK](#) [907AYY100](#) [PMHD155A1](#) [95-313.000](#)
[9533CD4+U574+U4922](#) [95-414.000](#) [99-450.837](#) [99-453.837](#) [PV3H2B0NN-341](#) [1203MRA](#) [A22NZBGANGA](#) [A22NZBMMNGA](#)
[A22NZBNANGA](#) [A22NZMPATRA](#) [A2PMA1X03EC56](#) [A3A-5123-02](#) [A3A-7140](#) [A3A-7310](#) [A3A-7340](#) [A3U-TMW-A2C-5M](#) [A595](#)