




## SHEET 1 OF 1













## NOTE:

- 1. ALL DIMENSIONS IN MM [INCH]
- 2. GENERAL TOLERANCE: X.X=±0.4 X.XX=±0.25
- 3. TERMINAL NUMBERS FOR REF ONLY
- ▲4. CONTACT MATERIAL: SILVER
- 5. RATING: 1A @ 250 VAC
  - 3A @ 120 VAC OR 28 VDC MAX.
- 6. ELECTRIC LIFE: 50,000 MAKE-AND-BREAK CYCLES
  AT FULL LOAD
- 7. INSULATION RESISTANCE: 1,000 MEGA-OHM MIN.
- 8. ACUATION FORCE:  $300 \pm 100$ gf
- $\blacktriangle$ 9. TRAVEL: 1.0 ± 0.2mm
- 10. CONTACT RESISTANCE: 20 mOHM MAX.
  - TYPICAL @ 2-4 VDC
- 11. DIELECTRIC STRENGTH: 1,000 V RMS @ SEA LEVEL.
- 12. OPERATING TEMP.: -30°C to 85°C
- 13. ▲ DENOTES CRITICAL PARAMETER.
- 14. 2002/95/EC (ROHS) COMPLIANT.





F	20052	DRAWING UPDATE / CLEAN-UP	7/7/11	BGL
Е	17847	Dim 6.70 was 5.00	11/8/07	rc
D	16420	CLEANED UP DWG.	9/11/06	ВО
С	16040	REVISED AND REDRAWN	5/19/06	CT
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

_	
<b>₹</b>	E+SWITCH
•	

TLE 700DP7B10M1QE

SCALE 2:1 DATE 5/19/2006 CT DWG T721003 REV F

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by E-Switch manufacturer:

Other Similar products are found below:

8940K2012 LW1L-M1C10V-A LW1L-M1C70-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M22-D-R-GB0/K11 M7E-HRN2 67021K512 67081K512X 701PB580 7190K101 7199K101 810K12910 810KSV30B MML21EA2ADK MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8442K3 8450K1 860K11911T01A 861901 861K11911T01A07 861K13810T00A14 861K13911 8646AB6X718UL 8646ABUL 9001KXRK 907AYY100 PMHD155A1 95-313.000 9533CD4+U574+U4922 95-414.000 99-450.837 99-453.837 PV3H2B0NN-341 1203MRA A22NZBGANGA A22NZBMMNGA A22NZBNANGA A22NZBMANGA A22NZBMA1X03EC56 A3A-5123-02 A3A-7140 A3A-7340 A3U-TMW-A2C-5M A595