





## NOTE:

1. ALL DIMENSIONS IN MM [INCH]

CONTACT CONFIGURATION

- 2. GENERAL TOLERANCE: X.X=±0.4 X.XX=±0.25
- 3. TERMINAL NUMBERS FOR REF ONLY
- 4. MECHANICAL LIFE: 100,000 OPERATIONS
- 5. INSULATION RESISTANCE: 1,000 MILLI-OHM MIN.
- 6. OPERATING TEMP.: -25°C to 55°C
- ▲ 7. LED VOLTAGE: 6VDC GREEN
  - 8. ▲ DENOTES CRITICAL PARAMETER.

С	22191	UPDATED NOTE #4	3/15/16	MJR	€ E+SWITCH*				
В	18029	Parts Description was 50-001-06	3/19/08	rc					
Α	14453	RELEASED FOR PRODUCTION	11/3/04	AR	TITLE D16EER11HGRNGRN				
REV	PCR NO	DESCRIPTION	DATE	BY					
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED					SCALE 2:1	DATE 11/3/2004	DR AR	XF0611P	REV C

10.80 [.425 in] 7.20 [.283 in]

> 28.5±.50 [1.12±.02 in]

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by E-Switch manufacturer:

Other Similar products are found below:

8940K2012 LW1L-M1C10V-A LW1L-M1C70-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M22-D-R-GB0/K11 M7E-HRN2 67021K512 67081K512X 701PB580 7190K101 7199K101 810K12910 810KSV30B MML21EA2ADK MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8442K3 8450K1 860K11911T01A 861901 861K11911T01A07 861K13810T00A14 861K13911 8646AB6X718UL 8646ABUL 9001KXRK 907AYY100 PMHD155A1 95-313.000 9533CD4+U574+U4922 95-414.000 99-450.837 99-453.837 PV3H2B0NN-341 1203MRA A22NZBGANGA A22NZBMMNGA A22NZBNANGA A22NZBMANGA A22NZBMA1X03EC56 A3A-5123-02 A3A-7140 A3A-7340 A3U-TMW-A2C-5M A595