







NOTES:

- 1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4 $X.XX = \pm 0.25$
- TERM, NOS. FOR REF. ONLY

- 24.00 CONTACT RATING: 4A @125VAC/28VDC, 2A @250VAC DIELECTRIC STRENGTH: 1KV RMS min. at sea level ELECTRICAL LIFE: 10,000 make-and-break cycles at full load.
- MATERIALS:

CONTACTS: Silver Plated CU (Q Contact material)
TERMINALS: GOLD Plated Cu (Q Contact material)
MOUNTING NUT: Nickel Plated zinc alloy
CONTACT SPRING: Piano Wire KEYS (2): Brass with code no. A126 LOCK: Bright NI plated zinc alloy with NI facing TUMBLER Mechanism: 4—disc tumbler cylinder.

RE V.

ECN No.

REMOVED

TABULATION

10/10/01 DATE

TITLE

CYKD CJB

SCALE

DATE

10/10/01

1:1

DESCRIPTION



CIRCUIT: DP (CONTACT CO	
(90' INDEXING)	® 2

Pos. 1

8-1, 4-5	POS, 1	CONNECTED	SWITCH
1-3, 5-7	P0S, 2	TERMINAL #	FUNCTION

LEGEND

- = Detent Positions (45° or 90°)
- =Key pull possible in these positions

E-SWITCH®

K0130Q-A126

봈 CJBDMC

K200243

REV

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Keylock Switches category:

Click to view products by E-Switch manufacturer:

Other Similar products are found below:

89496-09 58J1007 58J8A45-01B05N 719-0201-000 719-0202-000 719-0702-000 719-5504-000 84800-04 GKNC33L GKNC3L

PVA2OAH5 HA1K-2C2VA-2 14-136.025K 14-235.022K AS6H-2K2A AS6M-2K1B AS6Q-2K2A AS6Q-3K2A 1571487-1 HW4K-2BF20

KEY-AS6 KH3C-20C 8928K493 2SWK131AL102 AS6M-2K1A AS6Q-2K1PB 51-401.036D 51-401.036K 51-414.036D HW1K-31BF20

HW1K-3HF20 Y1112-2027CLFT 51-155.025D 51-295.022D 51-404.036D 51-405.036D 51-415.036D 1-1437597-8 58J8A36-01B04N

58M1422 86945-05 719-0204-000 719-0205-000 719-0801-000 719-0804-000 719-0805-000 88422-18 58J8A90-01C02N 58J9P36
01B09N 58J8A36-01C03N