


CIRCUIT: SPDT
NON-SHORTING



- NOTES:
1. ALL DIMENSIONS IN MM.
 2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 - ▲ 4. RATING: DC 30V, 0.3A
 - ▲ 5. ACTUATION FORCE: 230 ± 100 GF
 6. TOTAL TRAVEL: 3.5 MM
 7. TRAVEL TO LOCK: 2.5 MM
 8. ▲ DENOTES CRITICAL PARAMETER.
 9. 2002/95/EC (ROHS) COMPLIANT

C	22327	Update Print, Redraw in new format	5/27/16	MW
B	15621	new tooling for cap	12/20/05	PH
A	12472	RELEASED	10/10/02	CB
REV	PCR NO	DESCRIPTION	DATE	BY



TITLE LC1258EENP1RLGR				
SCALE	DATE	DR	DWG	REV
3:1	10/10/2002	BLR	XP0110A	C

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pushbutton Switches](#) category:

Click to view products by [E-Switch](#) manufacturer:

Other Similar products are found below :

[8940K2012](#) [LW1L-M1C10V-A](#) [LW1L-M1C70-A](#) [LW2L-A1C20M-GD](#) [LW2L-M1C20M-A](#) [60324L](#) [M22-D-R-GB0/K11](#) [M7E-HRN2](#)
[67021K512](#) [67081K512X](#) [701PB580](#) [7190K101](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [MML21EA2ADK](#) [MML21KA3ABK](#)
[MML23KA3AC05K-001](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#) [861K11911T01A07](#)
[861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [8646ABUL](#) [9001KXRK](#) [907AYY100](#) [PMHD155A1](#) [95-313.000](#)
[9533CD4+U574+U4922](#) [95-414.000](#) [99-450.837](#) [99-453.837](#) [PV3H2B0NN-341](#) [1203MRA](#) [A22NZBGANGA](#) [A22NZBMMNGA](#)
[A22NZBNANGA](#) [A22NZMPATRA](#) [A2PMA1X03EC56](#) [A3A-5123-02](#) [A3A-7140](#) [A3A-7310](#) [A3A-7340](#) [A3U-TMW-A2C-5M](#) [A595](#)