



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: x.x=±0.4mm
x.xx=±0.25mm
 3. RATING: DC 30V, 0.3A
 - ▲ 4. OPERATING FORCE: 300±150gf
 5. TRAVEL: 3.5mm TO MAKE
2.5mm TO LOCK
 6. LIFE CYCLES: 10,000 CYCLES
 7. OPERATING TEMPERATURE: -20°C TO 80°C
 8. CONTACT RESISTANCE: 200mΩ MAX.
 9. INSULATION RESISTANCE: 100MΩ MIN.
 10. ▲ DENOTES CRITICAL PARAMETER.
 - ▲ 11. PLUNGER MATERIAL: NYLON 6/6
 - ▲ 12. PLUNGER COLOR: WHITE(NATURAL)

| | | | | |
|-----|--------|---------------------|---------|----|
| C | 15981 | ADD DIMENSIONS | 4/21/06 | CT |
| B | 15819 | EDIT PLUNGER LENGTH | 2/23/06 | PH |
| A | 15750 | RELEASE | 2/9/06 | PH |
| REV | PCR NO | DESCRIPTION | DATE | BY |

E-SWITCH®

TITLE LC2255EENP-NYLON 6/6

| | | | | |
|-------|----------|----|---------|-----|
| SCALE | DATE | DR | DWG | REV |
| 3:1 | 2/9/2006 | PH | P070182 | C |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pushbutton Switches](#) category:

Click to view products by [E-Switch](#) manufacturer:

Other Similar products are found below :

[8940K2012](#) [LW1L-M1C10V-A](#) [LW1L-M1C70-A](#) [LW2L-A1C20M-GD](#) [LW2L-M1C20M-A](#) [60324L](#) [M22-D-R-GB0/K11](#) [M7E-HRN2](#)
[67021K512](#) [67081K512X](#) [701PB580](#) [7190K101](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [MML21EA2ADK](#) [MML21KA3ABK](#)
[MML23KA3AC05K-001](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#) [861K11911T01A07](#)
[861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [8646ABUL](#) [9001KXRK](#) [907AYY100](#) [PMHD155A1](#) [95-313.000](#)
[9533CD4+U574+U4922](#) [95-414.000](#) [99-450.837](#) [99-453.837](#) [PV3H2B0NN-341](#) [1203MRA](#) [A22NZBGANGA](#) [A22NZBMMNGA](#)
[A22NZBNANGA](#) [A22NZMPATRA](#) [A2PMA1X03EC56](#) [A3A-5123-02](#) [A3A-7140](#) [A3A-7310](#) [A3A-7340](#) [A3U-TMW-A2C-5M](#) [A595](#)