


NOTE:

- 1. ALL DIMENSIONS IN MM [INCH]
- 2. GENERAL TOLERANCE: $X.X = \pm 0.4$

 $X.XX = \pm 0.25$

- 3. TERMINAL NUMBERS FOR REF ONLY
- 4. CIRCUIT: SPST OFF-MOMENTARY ON
- 5. CONTACT MATERIAL: Gold over SILVER
- ▲ 6. RATING: 125mA @ 125 VAC 100mA @ 50 VDC
 - 7. ELECTRIC LIFE: 500,000 CYCLES AT FULL LOAD
 - 8. CONTACT RESISTANCE: 50 milli-OHM max. (INITIAL)
 - 9. INSULATION RESISTANCE: 1,000 MEGA-OHM min. @ 500VDC
- 10. DIELECTRIC STRENGTH: 1,000 VAC rms.
- 11. OPERATING FORCE: 350 gf +/- 150 gf
- 12. OPERATING TEMPERATURE: -30°C to +85°C
- 13. CONTACT BOUNCE: 10ms MAX.
- ▲ 14. TRAVEL: 1.5mm
 - 15. PANEL THICKNESS RANGE: 0.8 1.8mm
 - 16. ▲ DENOTES CRITICAL PARAMETER.
 - 17. 2011/65/EU (ROHS) COMPLIANT
- ▲ 18. HARDWARE INCLUDED:
 - 1. T081100 RUBBER SEAL (1)
 - 19. SEAL RATING: IP67 AT THE FRONT PANEL



REV	PCR NO	DESCRIPTION	DATE	BY				
Е	21594	CHANGE NOTE 19: IP67 WAS IP65	9/24/14	EBP				
F	22441	ADDED BOTTOM VIEW	8/11/16	MJR				
G	23328	note 15 to .8 - 1.8mm	4/25/18	MW				

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

(⇒ E+SWITCH°											
▼											
TITLE RP8100B1M1CEBLKWHTYEL											
SCALE 3:2	DATE 2/20/2009	DR BLR	DWG ST081031		REV G						

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by E-Switch manufacturer:

Other Similar products are found below:

8940K2012 LW1L-M1C10V-A LW1L-M1C70-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M22-D-R-GB0/K11 M7E-HRN2 67021K512 67081K512X 701PB580 7190K101 7199K101 810K12910 810KSV30B MML21EA2ADK MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8442K3 8450K1 860K11911T01A 861901 861K11911T01A07 861K13810T00A14 861K13911 8646AB6X718UL 8646ABUL 9001KXRK 907AYY100 PMHD155A1 95-313.000 9533CD4+U574+U4922 95-414.000 99-450.837 99-453.837 PV3H2B0NN-341 1203MRA A22NZBGANGA A22NZBMMNGA A22NZBNANGA A22NZBMANGA A22NZBMA1X03EC56 A3A-5123-02 A3A-7140 A3A-7340 A3U-TMW-A2C-5M A595