


SERIES TS2 SWITCHES



SMT SNAP ACTION SWITCH



MECHANICAL SPECIFICATIONS

Mechanical Life:	3,000,000 cycles
Force:	70 ± 20 gf

ELECTRICAL SPECIFICATIONS

Contact Rating:	0.1A @125 VAC or 48 VDC
Contact Resistance (Initial Max.):	300 mOhms @ 5VDC
Insulation Resistance:	100 MOhms min @500VDC
Dielectric Strength (1 Min.):	1,000V
Bounce:	5m Second Max

FEATURES & BENEFITS

- Surface mount termination
- Subminiature package size
- Designed for higher reliability applications

APPLICATIONS / MARKETS

- Appliance
- Timing controls
- Testing/instrumentation
- Gaming and vending machines

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature:	-25°C to +85°C
------------------------	----------------


HOW TO ORDER





Example Ordering Number

TS20 100F070S

Specifications subject to change without notice.



ACTUATOR AND OPERATING FORCE CHART			
Actuator	Operating Force	Pre-Travel (P.T.)	Operating Point (O.P.)
00	070	0.2 +/- 0.1mm	3.3 +/- 0.3mm



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Basic / Snap Action Switches](#) category:

Click to view products by [E-Switch](#) manufacturer:

Other Similar products are found below :

[5SM901-S12](#) [5SM9-S12N195](#) [01.098.1358.1](#) [602EN532](#) [602EN535-RB](#) [602HE5-RB1](#) [604HE162](#) [604HE223-6B](#) [624HE17-RB](#) [6HM82](#)
[6HM89](#) [6SE1](#) [6SX1-H58](#) [70500216](#) [70599106](#) [MBD5B1](#) [MBH2731](#) [73-316-0012](#) [EXD-AR20](#) [79211923](#) [79218589](#) [7AS12](#)
[MIL30126AB6BBMD4A12XAU](#) [ML-1155](#) [ML-1376](#) [831010C3.0](#) [831090C2.EL](#) [83131904](#) [84212012](#) [8AS239](#) [8HM73-3](#) [8SX26-H33](#)
[914CE1-6G](#) [PL-100](#) [11SM1077-H4](#) [11SM1077-H58](#) [11SM1-TN107](#) [11SM405](#) [11SM8423-H2](#) [11SX37-T](#) [11SX48-H58](#) [11SM2442-T](#)
[11SM76-T](#) [11SM77-H58](#) [11SM77-T](#) [11SM863-T](#) [11SM866](#) [A7CN-1M-1-LEFT](#) [A831700C7.0](#) [121EN187-R](#)