


SWITCH SCHEMATIC (MOMENTARY)





PCB MOUNTING


NOTES:


- 1. ALL DIMENSIONS IN MM
- 2. GENERAL TOLERANCE: $X.X = \pm 0.4$ $X.XX = \pm 0.25$
- 3. TERM. NOS. FOR REFERENCE ONLY.
- 4. CONTACT RATING: 0.1A Max. @ 28VDC
- ▲ 5. CONTACT MATERIAL: GOLD
 - 6. ELECTRICAL LIFE: 200,000 Typical
 - 7. MECHANICAL LIFE: 1,000,000 CYCLES TYP.
 - 8. OPERATING TEMP: -40°C to +85°C
 - 9. OPERATING FORCE: $200 \pm 100 \text{ gf}$
 - 10. CONTACT RESISTANCE: 100 MILLI-OHM INITIAL TYP. MAX.
- 11. DIELECTRIC STRENGTH: 1000 VAC FOR 1 MINUTE
- 12. TRAVEL TO MAKE: 2.20mm ± 0.2
- 13. 2011/65/EU (ROHS) COMPLIANT
- 14. ▲ DENOTES CRITICAL PARAMETER
- ▲ 15. LED COLOR: RED: 1 CHIP, 2.1-2.5 VDC@20mA

GRN: 1 CHIP, 3.2-4.0 VDC@20mA BLU: 1 CHIP, 3.1-3.8 VDC@20mA









С	22858	update Note 15	5/23/17	MW
В	22350	SHOW "E" ON BOTTOM VIEW	6/16/16	MW
Α	21185	RELEASED FOR PRODUCTION	8/1/13	EBP
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E+SWITCH°								
TITLE ULP12OAP1RSFCL1RGB								
SCALE 3:2	DATE 8/1/2013	DR EBP	DWG B800064	REV C				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by E-Switch manufacturer:

Other Similar products are found below:

8940K2012 LW1L-M1C10V-A LW1L-M1C70-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M22-D-R-GB0/K11 M7E-HRN2 67021K512 67081K512X 701PB580 7190K101 7199K101 810K12910 810KSV30B MML21EA2ADK MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8442K3 8450K1 860K11911T01A 861901 861K11911T01A07 861K13810T00A14 861K13911 8646AB6X718UL 8646ABUL 9001KXRK 907AYY100 PMHD155A1 95-313.000 9533CD4+U574+U4922 95-414.000 99-450.837 99-453.837 PV3H2B0NN-341 1203MRA A22NZBGANGA A22NZBMMNGA A22NZBNANGA A22NZBMANGA A22NZBMA1X03EC56 A3A-5123-02 A3A-7140 A3A-7340 A3U-TMW-A2C-5M A595