



ETA-USA

The Power Professionals


AOPS1500

1500W AC/DC



Features

- Small Size
- Built in PFC circuit
- Wide Input voltage range 100-240 VAC
- Over voltage protection
- Overcurrent protection
- 4 Yr warranty**



MODEL/CHANNEL		Unit	AOPS1500 -5	AOPS1500 -9	AOPS1500 -12	AOPS1500 -15	AOPS1500 -24	AOPS1500 -48	
OUTPUT	Nominal Voltage	[V]	5	9	12	15	24	48	
	Setting Voltage Range	[V]	4.95~5.05	8.91~9.09	11.88~12.12	14.85~15.15	23.76~24.24	47.52~48.48	
	Current	[A]	240	150	125	100	63	32	
	Voltage Adjustment	[V]	Voltage adjustment trim is +/- 15%						
	Rated Power	[W]	1200	1350	1500	1500	1512	1536	
	Line Regulations	[mV]	25	45	60	75	120	240	
	Load Regulations	[mV]	100	45	60	75	120	240	
	Temperature Drift	[mV]	75	135	180	225	360	720	
	Ripple & Noise(pk-pk)	[mV]	150	150	150	150	150	200	
	Start-up, Rise Time typ.	[ms]	1500 typ., 100 typ., (AC IN 110/220V, lo=100%)						
Hold-up Time typ.	[ms]	10(AC IN 110V, lo=100%), 15 (15 IN 220 V, lo=100%)							
INPUT	Voltage, Frequency	[V]	AC 100~240V (AC90~264V), 50/60Hz (43~63) or DC127~370 V						
	Current Typ. 110V 220V	[A]	14 7	15 7.5	16 7.8	16 7.8	16 7.8	16 7.8	
	Efficiency 110V 220V	[%]	78 80	82 85	83 87	83 87	86 90	87 91	
	Power Factor 110V 220V	-	.98(lo=100%) .95(lo=100%)						
	Inrush Current Typ.110V 220V	[A]	30 (Ta=25 C. Cold Start) 60 (Ta=25C, Cold Start)						
	Leakage Current 110V 1mA Max 220V	[mA]	0.6 (Typ.) 1.0 (Typ.)						
Function	Over Current Protection ⁽²⁾	[A]	Works at 105~135% rating Protection type Constant current limiting unit will shut down after 5 sec. (Re-power on to recover)						
	Auxiliary Power (AUX)	-	12V/0.1A (only for remote ON/OFF control)						
	Remote Sensing	-	Available						
	Remote ON.OFF	-	Available						
	Alarm Signal	-	POK (Open collector output)						
	Cooling/O.T.P	-	Forced air cooling / Fan						
Electrical Isolation	(1) Input - Output	-	AC 3.0 KV 1min., cut-off: 20mA / DC 500V 100 MO						
	(2) Input - F.G	-	AC 2.0 KV 1min., cut-off: 20mA / DC 500V 100 MO						
	(3) Output - F.G	-	AC 0.5 KV 1min., cut-off: 100mA / DC 500V 100 MO						
Environment	Operating temp. &	-	-10 ~70 C. 20~90% RH (NON condensing)						
	Storage temp. & Humidity	-	-20 ~85 C. 20~90% RH (NON condensing)						
	Vibration	-	10~55Hz @ 1 G 3minutes PERIOD, 30minutes along X,Y & Z axis						
Dimension	Size(WxHxD) / Weight	mm/g	126.5 x 82 x 280/ 3800						
Safety	CB, CE, RU	-	EN60950-1						
Emission	Conducted Emission	-	Complied with EN55022-A						
PFHC	Harmonic Content	-	Complied with IEC61000-3-2-3						



ETA-USA

16170 Vineyard Blvd. Suite 180 Morgan Hill, CA 95037 <http://www.eta-usa.com>
 Toll-free (US only): 800-ETA-POWR (800-382-7697) Telephone: 408 778-2793 FAX: 408-779-2753

©2014 ETA-USA All Rights Reserved

ETA-USA reserves the right to make changes to the products and specifications without prior notice. Please contact the factory for latest information.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [AC/DC Power Modules](#) category:

Click to view products by [ETA](#) manufacturer:

Other Similar products are found below :

[VI-HAM-CM](#) [ERP-350-12](#) [KPSB25-12-J](#) [KPSB25-15-J](#) [KPSB25-24-J](#) [KPSB25-36-J](#) [KPSB25-5-J](#) [KPSB6-12-J](#) [KPSB6-5-J](#) [TMPS 03-112](#)
[TMPS 03-115](#) [TMPS 03-124](#) [IRM-03-9S](#) [LFWLT300-CK](#) [TMPS 03-109](#) [TPP 40-112](#) [TPP 65-105](#) [TPP 65-112](#) [VOF-275-48](#) [RAC04-](#)
[12DC/277-E](#) [RAC04-05DC/277-E](#) [KMS15-9](#) [RAC04-0512DC/277-E](#) [PFE700SA-48/T](#) [MFM-15-12](#) [MFM-15-5](#) [MFM-20-12](#) [MFM-20-5](#)
[MPM-05-12](#) [MPM-05-5](#) [MPM-10-24](#) [MPM-10-5](#) [MPM-15-12](#) [MPM-15-24](#) [MPM-15-5](#) [MPM-20-12](#) [MPM-20-24](#) [MPM-20-5](#) [MPM-30-12](#)
[MPM-30-24](#) [MPM-30-5](#) [RAC01-05SGA](#) [RAC01-05SGB](#) [RAC02-05SGB](#) [RAC02-12SGA](#) [RAC02-12SGB](#) [RAC03-05SGA](#) [RAC03-05SGB](#)
[RAC03-12SGA](#) [RAC03-3.3SGA](#)