

## STATIC SHIELDING FILM

20-87x-xxxx, 20-771-xxxx

Metal-In static shielding bags made out of polyester/polyethylene films for packaging ESD sensitive devices. Heat sealable, those bags are available with or without zipper.

### Film construction\* :

Dissipative coating
<b>Polyester</b>
Aluminium
<b>Polyethylene</b>
Dissipative coating

### Standard compliance :

IEC 61340-5-1  
RoHS compliant



	Material and features 20-771-xxxx	Material and features 20-87x-xxxx
<b>Thickness</b>	50µm (2 mil. Inch) +/- 10%	76µ (3 mil. Inch) +/- 10%
<b>Tensile strength</b>	MD > 5500 psi / TD > 5500 psi (ASTM D-882-91, method A)	MD > 5000 psi / TD > 5500 psi (ASTM D-882-91, method A)
<b>Tear strength</b>	MD > 2.0 lbs / TD > 2.8 lbs (ASTM-D-1004-94)	MD > 2.0 lbs / TD > 2.8 lbs (ASTM-D-1004-94)
<b>Puncture strength</b>	> 10 lbs (FTMS 101C, Method 2065.1)	> 12 lbs (FTMS 101C, Method 2065.1)
<b>MVTR</b>	< 0.35 gram/100 in <sup>2</sup> / 24H (ASTM-F1249)	< 0.25 gram/100 in <sup>2</sup> / 24H (ASTM-F1249)
<b>Light transmission</b>	40% (+/-5%)	40% (+/-5%)
<b>Heat sealable</b>	250/375°F; 0.5 to 3.5 sec. 30 to 70 psi	250/375°F; 0.5 to 3.5 sec. 30 to 70 psi
<b>Warranty period and Storage conditions**</b>		3 years (environment ≤ 30C/60%RH) 3 years (environment ≤ 40C/90%RH)

### Electrical properties:

Surface resistance: < 10e11 Ohm (both surface), IEC 61340-2-3  
Volume resistance: < 10e11 Ohm (both surface), IEC 61340-2-3  
Static shielding: < 20 nJ (ESD S11.31)  
Static shielding: Capacitive probe < 25V (EIA541)  
Static decay time: < 0.05 seconds

### Bag specifications:

All bags dimensions are internal dimensions. The 1st dimension is the opening, the 2nd is the height.

Dimensions (for zipper bags): from 76x76mm to 914x762mm  
Dimensions (for non-zip bags): from 50x100mm to 1000x762mm  
Seal sizes: ≤ 6mm  
Printing: Standard with ESD requirements, approx 50x50mm,  
Yellow or Black. Date code (YYMM).

### Options:

Standard sizes available from stock, customized sizes available on request.  
Customized printing on request.

\*There may be color variations but all ESD properties are guaranteed \*\*Subcondition: packaging should not be perforated.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Eurostat manufacturer](#):*

Other Similar products are found below :

[20-007-0305](#) [20-007-0406](#) [20-007-0508](#) [20-007-0608](#) [20-007-0610](#) [20-007-0810](#) [20-007-0812](#) [20-007-0816](#) [20-007-1012](#) [20-007-1216](#) [20-007-1620](#) [20-008-0305](#) [20-008-0406](#) [20-008-0610](#) [20-008-0812](#) [20-008-1012](#) [20-008-1216](#) [20-010-0006](#) [20-010-0007](#) [20-011-0305](#) [20-011-0406](#) [20-011-0608](#) [20-011-0610](#) [20-011-0812](#) [20-011-1214](#) [20-011-1216](#) [20-011-1620](#) [20-011-1824](#) [20-012-0305](#) [20-012-0406](#) [20-012-0508](#) [20-012-0610](#) [20-012-0810](#) [20-012-0812](#) [20-012-1012](#) [20-012-1216](#) [20-013-0003](#) [20-014-0002](#) [20-014-0006](#) [20-019-6029](#) [20-053-0006](#) [20-053-0035](#) [20-053-0070N](#) [20-053-0560](#) [20-054-0002](#) [20-054-0003](#) [20-062-0031](#) [20-063-0011](#) [20-071-0430](#) [20-071-0816](#)