

HEELGROUNDER

30-560-0043/0044/0053

Slip resistant heelgrounder, designed with a fast-fastening black plastic buckle and a ribbon for insertion in the shoe.

Product Specifications

Conductive ribbon:

Surface resistance $\leq 10e5 \Omega$

Length = 57 cm for 30-560-0044

Length = 87 cm for 30-560-0053 (toe grounder)

Double layer conductive rubber cup:

-Outer surface: Conductive, Black, surface resistance $\leq 10e5 \Omega$

-Inner surface: Antistatic, Ivory, surface resistance $\leq 10e11 \Omega$

Point to point resistance: $<1x10e9 \Omega$

Resistor: Each grounder is built in with a 1.5 M Ω resistor

Marking: Each grounder is marked with 'Eurostat'

Compliant to: IEC 61340-5-1



30-560-0044



30-560-0053

General Usage

- Heelgrounders are to be worn on an ESD-floor.
- Recommended to be worn on each feet.
- Heelgrounders are reusable and hand-washable. Be sure to use mild detergents
- Test on a regular basis the heel grounder by using a footwear test station

Options

Heelgrounder with longer ribbon (60cm) 30-560-0043

Also available without the 'Eurostat' branding

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Antistatic Control Products](#) category:

Click to view products by [Eurostat](#) manufacturer:

Other Similar products are found below :

[13020](#) [13490](#) [13881](#) [13883](#) [14404](#) [2202SP](#) [2229](#) [2230](#) [37061](#) [42470](#) [09813](#) [09857](#) [04563](#) [09037](#) [09813](#) [66070](#) [98132](#) [73741](#) [13868](#)
[13457](#) [13245](#) [13420](#) [13205](#) [13135](#) [91070](#) [66085](#) [13080](#) [13806](#) [19863](#) [09121](#) [73831](#) [07501](#) [66086](#) [66121](#) [16316](#) [13331](#) [ZN-A2502](#) [ZJ-](#)
[SD100](#) [1900-8X12](#) [1910-10X12](#) [82A3](#) [1900-6X8](#) [1900-7-15](#) [12917](#) [2231](#) [19866](#) [20-014-0002](#) [20-082-0010](#) [20-082-1012](#) [STS1327](#)