5.25" format format Mobile Intel® QM57 Express Chipset SBC

ANTARES



FEATURES

High performance – Intel Core i7/Core i5 processor technology

Power efficient – Low power consumption with fanless option

Robust – Wide -20 to +60 C operating temperature

Feature rich – 4 video output, x4 PCle, dual Mini-PCle, SIM support, GbE

Advanced – Support for hyperthreading, virtualisation & remote management

Future Proof – Consistency and longevity of supply

- · Multi-media infotainment
- Machine control
- Kiosks
- HMI
- Manufacturing machinery
- Communications control
- Data concentrators

The ANTARES is a 5.25" single board computer based on the new Mobile Intel QM57 Express Chipset. Designed to offer high performance with low power dissipation, the ANTARES is available with Intel Core i7 or Core i5 processor options and is ideal for use in compact spaces with restricted ventilation.

Traditional embedded system requirements are well catered for with features such as Watchdog, GPIO, four serial ports, an integrated SD/MMC Flash port for accessing storage cards and Mini PCIe expansion for wireless modules such as Wi-Fi, Bluetooth and cellular modems. The ANTARES supports advanced features such as virtualisation, hyperthreading and remote system management via Intel's AMT feature (available even if the operating system has crashed), making it simple to add sophisticated capabilities to any embedded design. Coupled to a wide operating temperature range, options for fanless operation, and long term chipset support, the ANTARES embedded PC is ideal for applications in commercial, industrial and transportation projects requiring high performance computing within a rugged and reliable platform.

The ANTARES is supported by rapid application Development Kits for Windows Embedded Standard, Windows 7 and Fedora Linux.



ANTARES

Specifications

5.25" format format Mobile Intel® QM57 Express Chipset SBC



System Architecture

| PROCESSOR | Intel® Core™ i5 520E 2.4GHz |
|-----------------------|---|
| | Intel® Core™ i7 610E 2.53GHz |
| | Intel® Core™ i7 620LE 2GHz |
| | Intel® Core™ i7 620UE 1.06GHz |
| | Intel® Celeron® P4505 1.86GHz |
| CHIPSET | Mobile Intel® QM57 Express Chipset |
| SUPPORTED OS | Windows Embedded Standard, Windows 7 and Fedora Linux |
| MEMORY | Up to 8GB |
| PCI EXPRESS | 1 x PCI Express x 4 |
| | 2 x PCI Express MiniCard sockets with SIM support |
| | Support for up to 2 simultaneous independent displays GRAPHICS LVDS, CRT, |
| | HDMI 1.3 (DVI with cable adapter) |
| USB SUPPORT | 4 x USB front panel connectors |
| | 4 x USB (internal) |
| | 2 x USB on PCI Express MiniCard sockets |
| ETHERNET | 2 x Gigabit Ethernet ports supporting 10/100/1000baseT |
| | Intel 82577 - PXE/Intel AMT |
| | Intel 82574L - PXE |
| SERIAL PORTS | 3 x RS232 |
| | 1 x RS232/RS485/RS422 (software selectable) |
| GPIO | 16 x GPIO (5V) |
| | 8 x inputs, 8 x outputs |
| | SMBus interface |
| TPM | Atmel AT97SC3204 TPM 1.2 factory fit option |
| THERMAL SOLUTION | Fanless option available |
| BIOS | Phoenix Trusted Core BIOS |
| H/W MONITORING | Software monitoring of temperatures and voltages |
| SERIAL ATA | 4 x SATA connectors for direct cable connect. |
| | BIOS support for host swap and for eSATA connection, |
| | RAID mode 0, 1, 5 and 10 supported |
| FLASH MEMORY | SD/MMC card socket |
| | BIOS boot capability |
| | SDHC support for cards up to 32GB |
| WATCHDOG | Watchdog timer support |
| OPERATING TEMPERATURE | -20°C to +60°C |
| | |

Development Kit

The ANTARES Development Kit is available in the following variants;

- ANTARES Standard DevKit, with a 8.4" flat panel display & touchscreen
- ANTARES No-LCD DevKit, with the perspex base only (no display set)

The ANTARES Development Kit comes pre-loaded with the following operating systems;

- Windows Embedded Standard
- Windows 7
- Fedora Linux

Systems and Enclosures

The ANTARES is available as a board-only solution, and also within a 1U high, 19" rackmount enclosure, providing a ready-to-go platform for embedded and industrial PC applications.

Note: The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.



North America

sales.na@eurotech.com

Europe, Middle East and Africa sales.emea@eurotech.com

Latin America sales.la@eurotech.com

Asia Pacific sales.ap@eurotech.com

ETH_ANTARES_DS_02/2011

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Development Boards & Kits - x86 category:

Click to view products by Eurotech manufacturer:

Other Similar products are found below:

 conga-MEVAL
 iQ7-DB-MATX-R10
 IT6/COMe Carrier
 DFR0453
 ETX-Proto
 Q7-BASE-R01
 Starterkit-CFE-E-2176M-3DIMM/M48G

 Starterkit-COM Express 6
 Starterkit-COM Express 6 PLUS
 VIZI-AI LEC-AL-E3940-AI-4G-32G/EMEA
 VPX-R300
 AKX00002

 AKX00002SL
 CEB94701
 7000-54864-102-101
 ARDUINO2.AL.B
 ARDUINO.AL.B
 GT.PDKW
 IOTGTWY.DK110
 IOTGTWY.DK200

 IOTGTWY.DK300
 IOTGTWY.DK50
 MIKROE-2582
 102010028
 110060064
 110060382
 110060577
 SOM-DB5800-00A2E
 ROM-DB7500-SCA1E

 Conga-QEVAL/Qseven
 2.0
 conga-QKIT
 X7EVAL/ind
 68300-0000-00-0
 MIKROE-2546
 DEV-13033