

# ReliaCELL 10-20

- **Global Cellular Support for:**
  - 2G GSM
  - 2.5G CDMA 1x-RTT
  - 3G CDMA EV-DO Rev A
  - 3G UMTS/HSPA
  - 4G LTE Cat 3 and 4 with UMTS/GSM fallback
- **Simple USB Connectivity**
- **Ready to Deploy – certified and carrier approved**
- **Ruggedized for commercial and industrial applications**
- **Optional GPS capability**



## FEATURES

**Ruggedized - IP67 Mountable** - The enclosure design makes the ReliaCELL 10-20 ideally suited for harsh environments; whether it is indoors or outside, it provides the cellular connectivity for your application or appliance needs

**Easy Cellular Technology Migration** - The ReliaCELL 10-20's unique concept allows for easy integration with your appliance or IoT device, swapping ReliaCELL models as cellular technology updates are needed, and avoiding time-consuming redesigns and massive hardware replacement costs

**No Cellular Certification Costs** - When using the ReliaCELL as the cellular module for your M2M or IoT device, it has all of the cellular certifications completed allowing for rapid deployment of new product developments

**Easy Installation** - The ReliaCELL 10-20 connects to your device by way of USB 2.0. Once plugged in and screwed onto a flat surface, it is sealed and waterproof to IP67 rating

**Standard Software Drivers** - Ready for deployment with standard Linux and Windows software drivers to enable cellular connectivity

The ReliaCELL 10-20 is a rugged cellular adapter that is easily mountable to flat surfaces. Deployable for products sold globally, the ReliaCELL 10-20 offers a distinctive approach to providing cellular connectivity within the M2M, IoT and Internet appliance marketplace. With its rugged and small design, it simplifies product development, Time-to-Market and costs associated with implementing a cellular solution. It becomes an easy addition to existing or new applications sealing onto the surface of an enclosure, weatherproof or not, with a simple USB connection and SMA connectors for antennas.

Enabling cellular technology is one of the toughest and most time-consuming challenges enterprise customers face and the ReliaCELL 10-20 simplifies this aspect of their solution. The ReliaCELL 10-20 modularizes the cellular component of embedded product development uniquely to allow it to be added to systems without making compromises on ruggedization. Now customers save time and money while avoiding the hassle of certifying with cellular carriers since the ReliaCELL 10-20 is already certified.

The ReliaCELL 10-20 is offered in several cellular technologies, including the latest 4G LTE UE categories, providing the flexibility to adapt should your product roadmap or application requirements evolve from 2G to 3G to 4G. Simply switching from a 2G to a 3G ReliaCELL solution, for example, will allow you to maintain the key system components of your appliance without incurring significant hardware costs or the lost time and resources associated with recertification of your device.

## Variants

ReliaCELL Model	-21	-25 -26	-30 -32	-34 (GPS) -35 (no GPS) -36 -37	-42	-43	-44
CELLULAR TECHNOLOGY	2G Quad Band GPRS	3G Dual Band CDMA 1xRTT	3G Dual Band EV-DO Rev. A	3G Penta Band HSPA+	4G LTE Cat 3 (UMTS Fallback)	4G LTE Cat 4 (UMTS/GSM Fallback)	
UPLOAD	16-24 Kbps	Up to 153 Kbps	Up to 1.8 Mbps	Up to 5.76 Mbps	Up to 100 Mbps	Up To 150 Mbps	
DOWNLOAD	32-48 Kbps	Up to 153 Kbps	Up to 3.1 Mbps	Up to 21 Mbps	Up to 50 Mbps	Up to 50 Mbps	
BANDS/FREQUENCIES	GSM/GPRS: Bands 2,3,5,8	800/1900 MHz		UMTS: Bands 1,2,5,6,8,10 GSM/GPRS/EDGE: Bands 2,3,5,8	LTE: Bands 2,4,5,17 UMTS: Bands 2,5	LTE: Bands 2,4,5,12,13 UMTS: Bands 2,5	LTE: Bands 1,3,7,8,20 UMTS: Bands 1,8 GSM: Bands 3,8
GNSS	<b>Constellation</b>	None	None	GPS, Galileo, GLONASS, BeiDou		None	None
	<b>Accuracy</b>	None	None	3m	0.4m	None	None
	<b>Tracking sensitivity</b>	None	None	-166 dBm	-161 dBm	None	None
	<b>Time to First Fix (TIFF)</b>	None	None	1.8s hot / 30s warm / 42s cold		None	None
	<b>Data output</b>	None	None	NMEA 0183		None	None
ENVIRONMENT	<b>Operating Temp</b>	-40°C to +85°C					
	<b>Regulatory and Safety</b>	FCC, CE, IC (ISED), UL	FCC, UL	FCC, UL	-34/-35: FCC, CE, IC (ISED), UL, MX -36: KR regulatory -37: TELEC (Japan) JATE	FCC, CE, UL	
	<b>Shock and Vibration</b>	Shock: Mil-STD-810F / Vibration: SAE J1455					
	<b>Environmental</b>	RoHS2, REACH					
MARKET CERTIFICATIONS	NA EU	NA (US)	NA (US)	-34/-35: NA,EU -36: KR -37: JP	NA (US)	NA (US)	EU
CARRIER CERTIFICATIONS	PTCRB, AT&T, T-Mobile Bell, Rogers	-25: Verizon -26: Sprint	-30: Verizon -32: Sprint	-34/-35: PTCRB, AT&T, T-Mobile Bell, Rogers	PTCRB, AT&T	Verizon	

## Specifications

INTERFACES	<b>USB</b>	1x USB 2.0 Type A Compatible for Cellular Only						
	<b>Dual SIM</b>	Yes	n/a	n/a	Yes	Yes	Yes	Yes
ANTENNAS	<b>Cellular</b>	SMA (Main & Diversity, where applicable)						
	<b>GPS</b>	SMA (Optional - not on all modules)						
POWER	<b>Input</b>	5VDC@500mA Typical						
PHYSICAL	<b>Enclosure</b>	Black Polycarbonate				Gray Polycarbonate		
	<b>Ingress Protection</b>	IP67						
	<b>Mounting</b>	(4x) M2.5 screws, metric						

Note: The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Multiprotocol Modules](#) category:*

*Click to view products by [Eurotech](#) manufacturer:*

Other Similar products are found below :

[NINA-W102-00B](#) [AIW-355 DQ-N01](#) [AIW-355 DQ-C01](#) [EWM-W188M201E](#) [EWM-W192K1](#) [PCM-24S2WF-BE](#) [ATWINC3400-MR210CA122](#) [ESP32-WROVER-B](#) [ESP32-WROVER-IB](#) [INP1010-A1-ITP](#) [INP1011-A2-ITP](#) [M1003GXT00](#) [ATWINC3400-MR210CA122-T](#) [ATWINC3400-MR210CA131](#) [TWR0083](#) [RS9113-NB0-D0N](#) [WYSBHVGXG](#) [WYSBMVGXB](#) [ESP32-WROOM-32](#) [cs-superb-03](#) [cs-superb-04](#) [TEL0135](#) [ReliaCELL10-20-26](#) [POL-2G-KIT](#) [POL-3G-KIT](#) [ENWF9201AZEF](#) [STM32WB5MMGH6TR](#)