

## Thick Film Chip Resistor — CR Series



### Application

- Consumer electrical
- Home Appliance: Air conditioner, Refrigerator
- Computer & relative products: Main board
- Communication equipment: Cell phone, Fax machine
- Power equipment: Power supply, Illumination equipment
- Measuring instrument: Electric meter, Navigation equipment

### Features

- Small size and light weight
- Reliability, high quality

### Type Dimension



### Dimension

Unit: mm

| TYPE   | L               | W               | H               | $l_1$           | $l_2$           |
|--------|-----------------|-----------------|-----------------|-----------------|-----------------|
| CR0201 | $0.60 \pm 0.03$ | $0.30 \pm 0.03$ | $0.23 \pm 0.05$ | $0.15 \pm 0.05$ | $0.15 \pm 0.05$ |
| CR0402 | $1.00 \pm 0.10$ | $0.50 \pm 0.05$ | $0.30 \pm 0.05$ | $0.15 \pm 0.10$ | $0.20 \pm 0.10$ |
| CR0603 | $1.60 \pm 0.20$ | $0.80 \pm 0.15$ | $0.40 \pm 0.10$ | $0.30 \pm 0.20$ | $0.30 \pm 0.10$ |
| CR0805 | $2.00 \pm 0.20$ | $1.25 \pm 0.15$ | $0.50 \pm 0.15$ | $0.30 \pm 0.15$ | $0.40 \pm 0.15$ |
| CR1206 | $3.05 \pm 0.10$ | $1.60 \pm 0.20$ | $0.55 \pm 0.15$ | $0.40 \pm 0.20$ | $0.50 \pm 0.20$ |
| CR1210 | $3.05 \pm 0.10$ | $2.50 \pm 0.20$ | $0.55 \pm 0.15$ | $0.50 \pm 0.20$ | $0.50 \pm 0.20$ |
| CR1812 | $4.50 \pm 0.10$ | $3.10 \pm 0.20$ | $0.55 \pm 0.05$ | $0.55 \pm 0.20$ | $0.70 \pm 0.20$ |
| CR2010 | $5.00 \pm 0.20$ | $2.50 \pm 0.20$ | $0.55 \pm 0.10$ | $0.60 \pm 0.20$ | $0.60 \pm 0.20$ |
| CR2512 | $6.30 \pm 0.20$ | $3.20 \pm 0.20$ | $0.55 \pm 0.10$ | $0.60 \pm 0.20$ | $0.60 \pm 0.20$ |

## Standard Electrical Specifications

| Item<br>Type | Rated Power<br>at 70°C | Max Working<br>Voltage | Max Overload<br>Voltage | T.C.R.<br>(PPM/°C) | Resistance Range     |                  |            |        |
|--------------|------------------------|------------------------|-------------------------|--------------------|----------------------|------------------|------------|--------|
|              |                        |                        |                         |                    | B(±0.1%)<br>D(±0.5%) | F(±1%)<br>G(±2%) | J(±5%)     |        |
| CR0201       | 0.05 W                 | 25V                    | 50V                     | -200/+400          | -                    | 1Ω~9.9Ω          |            |        |
|              |                        |                        |                         | ±200               | -                    | 10Ω~10MΩ         |            |        |
| CR0402       | 0.063 W                | 50V                    | 100V                    | ±400               | -                    | 1Ω~9.9Ω          |            |        |
|              |                        |                        |                         | ±300               | -                    | 10Ω~990Ω         |            |        |
|              |                        |                        |                         | ±200               | 10Ω~1MΩ              | 1KΩ~10MΩ         |            |        |
| CR0603       | 0.1 W                  | 75V                    | 150V                    | ±400               | -                    | 1Ω~9.9Ω          |            |        |
|              |                        |                        |                         | ±200               | -                    | -                | 10Ω~10MΩ   |        |
|              |                        |                        |                         | ±100               | 10Ω~1MΩ              | 10Ω~10MΩ         | -          |        |
| CR0805       | 0.125 W                | 150V                   | 300V                    | ±400               | -                    | 1Ω~9.9Ω          |            |        |
|              |                        |                        |                         | ±200               | -                    | -                | 10Ω~10MΩ   |        |
|              |                        |                        |                         | ±100               | 10Ω~1MΩ              | 10Ω~10MΩ         | -          |        |
| CR1206       | 0.25 W                 | 200V                   | 400V                    | ±300               | -                    | 1Ω~10Ω           |            |        |
|              |                        |                        |                         | ±200               | -                    | -                | 10.2Ω~10MΩ |        |
|              |                        |                        |                         | ±100               | 10.2Ω~1MΩ            | 10.2Ω~10MΩ       | -          |        |
| CR1210       | 0.5 W                  |                        |                         | ±300               | -                    | 1Ω~10Ω           |            | 1Ω~10Ω |
|              |                        |                        |                         | ±200               | -                    | -                | 10.2Ω~10MΩ |        |
|              |                        |                        |                         | ±100               | 10.2Ω~1MΩ            | 10.2Ω~10MΩ       | -          |        |
| CR1812       | 0.75 W                 |                        |                         | ±300               | -                    | 1Ω~10Ω           |            | -      |
|              |                        |                        |                         | ±200               | -                    | -                | 10.2Ω~10MΩ |        |
|              |                        |                        |                         | ±100               | 10.2Ω~1MΩ            | 10.2Ω~10MΩ       | -          |        |
| CR2010       | 0.75 W                 |                        |                         | ±300               | -                    | 1Ω~10Ω           |            | -      |
|              |                        |                        |                         | ±200               | -                    | -                | 10.2Ω~10MΩ |        |
|              |                        |                        |                         | ±100               | 10.2Ω~1MΩ            | 10.2Ω~10MΩ       | -          |        |
| CR2512       | 1 W                    | ±300                   | -                       | 1Ω~10Ω             |                      | -                |            |        |
|              |                        | ±200                   | -                       | -                  | 10.2Ω~10MΩ           |                  |            |        |
|              |                        | ±100                   | 10.2Ω~1MΩ               | 10.2Ω~10MΩ         | -                    |                  |            |        |

- For non-standard parts, please contact our sales dept.
- Operating Temperature Range : -55°C ~ +155°C.
- Type CR1210/1812/2010/2512 : 1Ω~10Ω (Alloy Film)
- Type CR1210/1812/2010/2512 : >10Ω (Thick Film)

| Type                    | 0201     | 0402 | 0603 | 0805 | 1206 | 1210 | 1812 | 2010 | 2512 |
|-------------------------|----------|------|------|------|------|------|------|------|------|
| Jumper Resistance Value | 50mΩ Max |      |      |      |      |      |      |      |      |
| Jumper Rated Current    | 0.5A     | 1A   |      |      | 2A   |      |      |      |      |

## ● Low Ohm Chip Resistor

### ■ Standard Electrical Specifications

| Item<br>Type | Rated Power<br>at 70°C | Rated Voltage<br>Range | Max Overload<br>Voltage | T.C.R.<br>(PPM/°C) | Resistance Range<br>(mΩ) |  |
|--------------|------------------------|------------------------|-------------------------|--------------------|--------------------------|--|
|              |                        |                        |                         |                    | F(±1%)、J(±5%)            |  |
| CR0402       | 0.063 W                | 0.17~0.25V             | 0.624 V                 | ±800               | 470~990                  |  |
| CR0603       | 0.1 W                  | 0.1~0.31V              | 0.775 V                 | ±800               | 100~330                  |  |
|              |                        |                        |                         | ±600               | 331~990                  |  |
| CR0805       | 0.125 W                | 0.04~0.35V             | 0.875 V                 | ±1800              | 10~50                    |  |
|              |                        |                        |                         | ±800               | 51~100                   |  |
|              |                        |                        |                         | ±600               | 101~990                  |  |
| CR1206       | 0.25 W                 | 0.05~0.5V              | 1.25 V                  | ±1800              | 10~50                    |  |
|              |                        |                        |                         | ±800               | 51~100                   |  |
|              |                        |                        |                         | ±600               | 101~990                  |  |
| CR1210       | 0.5 W                  | 0.07~0.7V              | 1.75 V                  | ±1800              | 10~50                    |  |
|              |                        |                        |                         | ±800               | 51~100                   |  |
|              |                        |                        |                         | ±600               | 101~990                  |  |
| CR1812       | 0.75 W                 | 0.08~0.8V              | 2.15 V                  | ±1800              | 10~50                    |  |
|              |                        |                        |                         | ±800               | 51~100                   |  |
|              |                        |                        |                         | ±600               | 101~990                  |  |
| CR2010       | 0.75 W                 | 0.08~0.8V              | 2.15 V                  | ±1800              | 10~50                    |  |
|              |                        |                        |                         | ±800               | 51~100                   |  |
|              |                        |                        |                         | ±600               | 101~990                  |  |
| CR2512       | 1 W                    | 0.1~0.99V              | 2.475V                  | ±1800              | 10~50                    |  |
|              |                        |                        |                         | ±800               | 51~100                   |  |
|              |                        |                        |                         | ±600               | 101~990                  |  |

● For non-standard parts, please contact our sales dept.

● Operating Temperature Range : -55°C ~ +155°C.

## ● High Ohm Chip Resistor

### ■ Standard Electrical Specifications

| Item<br>Type | Rated Power<br>at 70°C | Max Working<br>Voltage | Max Overload<br>Voltage | T.C.R.<br>(PPM/°C) | Resistance Range |         |       |        |
|--------------|------------------------|------------------------|-------------------------|--------------------|------------------|---------|-------|--------|
|              |                        |                        |                         |                    | F(±1%)           | J(±5%)  |       |        |
| CR0402       | 0.063 W                | 50V                    | 100V                    | ±200               | 10.1 MΩ          | 10.1 MΩ |       |        |
| CR0603       | 0.1 W                  | 75V                    | 150V                    |                    |                  |         |       |        |
| CR0805       | 0.125 W                | 150V                   | 300V                    |                    |                  |         |       |        |
| CR1206       | 0.25 W                 | 200V                   | 400V                    |                    |                  |         | ~     | ~      |
| CR1210       | 0.5 W                  |                        |                         |                    |                  |         |       |        |
| CR2010       | 0.75 W                 |                        |                         |                    |                  |         | 54 MΩ | 100 MΩ |
| CR2512       | 1 W                    |                        |                         |                    |                  |         |       |        |

● For non-standard parts, please contact our sales dept.

● Operating Temperature Range : -55°C ~ +155°C.

## ● Trimmable Chip Resistor – TCR series

### ■ Standard Electrical Specifications

| Item<br>Type | Rated Power<br>at 70 °C | Max Working<br>Voltage | Max Overload<br>Voltage | T.C.R.<br>(PPM/°C) | Resistance<br>Tolerance | Resistance<br>Range |
|--------------|-------------------------|------------------------|-------------------------|--------------------|-------------------------|---------------------|
| TCR0402      | 0.063 W                 | 50V                    | 100V                    | ±200               | ±15%<br>±20%<br>±30%    | 10Ω~1MΩ             |
| TCR0603      | 0.1 W                   | 75V                    | 150V                    |                    |                         |                     |
| TCR0805      | 0.125 W                 | 150V                   | 300V                    |                    |                         |                     |
| TCR1206      | 0.25 W                  | 200V                   | 400V                    |                    |                         |                     |
| TCR1210      | 0.5 W                   |                        |                         |                    |                         |                     |
| TCR1812      | 0.75 W                  |                        |                         |                    |                         |                     |
| TCR2010      | 0.75 W                  |                        |                         |                    |                         |                     |
| TCR1218      | 1 W                     |                        |                         |                    |                         |                     |
| TCR2512      | 1 W                     |                        |                         |                    |                         |                     |

● For non-standard parts, please contact our sales dept.

● Operating Temperature Range : -55°C ~ +155°C.

### ■ Parts Number Explanation

#### ■ Example:

| CR           | 0603                                                                 | J                                                                                                       | 10R                | P                                                                | 05                                                                              |          |
|--------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|--------------------|------------------------------------------------------------------|---------------------------------------------------------------------------------|----------|
| Product Type | Size(Inch)                                                           | Resistor<br>Tolerance                                                                                   | Resistors<br>Value | Package                                                          | Quantity                                                                        | Optional |
| CR<br>TCR    | 0201<br>0402<br>0603<br>0805<br>1206<br>1210<br>1812<br>2010<br>2512 | B : ±0.1%<br>D : ±0.5%<br>F : ±1%<br>G : ±2%<br>J : ±5%<br>K : ±10%<br>L : ±15%<br>M : ±20%<br>N : ±30% |                    | P、Q : Paper Taping<br>E : Embossed Taping<br>D : Packed in a Bag | 04 : 4000PCS<br>05 : 5000PCS<br>10 : 10000PCS<br>40 : 40000PCS<br>50 : 50000PCS |          |

## Appendix For SMD Chip Resistor

### ● Packaging Information



### ■ Dimension

Unit: mm

| TYPE                | SIZE |              | A       | φB       | φC     | φD      | W        | φM      |
|---------------------|------|--------------|---------|----------|--------|---------|----------|---------|
| 0201/0402           | 7"   | 10K/Reel     | 2.0±0.5 | 13.5±1.0 | 21±1.0 | 60±1.0  | 11.5±2.0 | 178±2.0 |
| 0402                | 13"  | 40K/50K Reel | 2.0±0.5 | 13.5±1.0 | 21±1.0 | 100±1.0 | 11.5±2.0 | 330±2.0 |
| 0603/0805/1206/1210 | 7"   | 5K/Reel      | 2.0±0.5 | 13.5±1.0 | 21±1.0 | 60±1.0  | 11.5±2.0 | 178±2.0 |
| 0603/0805/1206      | 10"  | 10K/Reel     | 2.0±0.5 | 13.5±1.0 | 21±1.0 | 100±1.0 | 11.5±2.0 | 254±2.0 |
|                     | 13"  | 20K/Reel     | 2.0±0.5 | 13.5±1.0 | 21±1.0 | 100±1.0 | 11.5±2.0 | 330±2.0 |
| 2010/2512/1812      | 7"   | 4K/Reel      | 2.0±0.5 | 13.5±1.0 | 21±1.0 | 60±1.0  | 16.0±2.0 | 178±2.0 |

### ■ Tapping Specification



### ■ Dimension

Unit: mm

| Packaging  | Type | A        | B        | W       | E        | F        | G       | H        | T        | φD                                  | P       |
|------------|------|----------|----------|---------|----------|----------|---------|----------|----------|-------------------------------------|---------|
| Paper Type | 0201 | 0.45±0.1 | 0.75±0.1 | 8.0±0.2 | 1.75±0.1 | 3.5±0.05 | 4.0±0.1 | 2.0±0.05 | 0.35±0.1 | 1.50 <sup>+0.10</sup> <sub>-0</sub> | 2.0±0.1 |
|            | 0402 | 0.70±0.1 | 1.20±0.1 | 8.0±0.2 | 1.75±0.1 | 3.5±0.05 | 4.0±0.1 | 2.0±0.05 | 0.45±0.1 |                                     | 4.0±0.1 |
|            | 0603 | 1.05±0.2 | 1.80±0.2 | 8.0±0.2 | 1.75±0.1 | 3.5±0.05 | 4.0±0.1 | 2.0±0.05 | 0.60±0.1 |                                     |         |
|            | 0805 | 1.55±0.2 | 2.30±0.2 | 8.0±0.2 | 1.75±0.1 | 3.5±0.05 | 4.0±0.1 | 2.0±0.05 | 0.75±0.1 |                                     |         |
|            | 1206 | 1.90±0.2 | 3.50±0.2 | 8.0±0.2 | 1.75±0.1 | 3.5±0.05 | 4.0±0.1 | 2.0±0.05 | 0.75±0.1 |                                     |         |
|            | 1210 | 2.85±0.2 | 3.50±0.2 | 8.0±0.2 | 1.75±0.1 | 3.5±0.05 | 4.0±0.1 | 2.0±0.05 | 0.75±0.1 |                                     |         |



**Dimension**

Unit: mm


| Packaging     | Type | A        | B        | W      | E        | F        | G       | H        | T        | φD                                  | φD1      | T1        | P       |
|---------------|------|----------|----------|--------|----------|----------|---------|----------|----------|-------------------------------------|----------|-----------|---------|
| Embossed Type | 2010 | 2.80±0.2 | 5.60±0.2 | 12±0.1 | 1.75±0.1 | 5.5±0.05 | 4.0±0.1 | 2.0±0.05 | 0.23±0.1 | 1.50 <sup>+0.10</sup> <sub>-0</sub> | 1.50±0.1 | 0.85±0.15 | 4.0±0.1 |
|               | 2512 | 3.40±0.2 | 6.70±0.2 | 12±0.1 | 1.75±0.1 | 5.5±0.05 | 4.0±0.1 | 2.0±0.05 | 0.23±0.1 |                                     | 1.50±0.1 | 0.85±0.15 |         |
|               | 1812 | 3.30±0.2 | 4.60±0.2 | 12±0.1 | 1.75±0.1 | 5.5±0.05 | 4.0±0.1 | 2.0±0.05 | 0.23±0.1 |                                     | 1.50±0.1 | 0.85±0.15 |         |

## ■ Packing Material Data / Storage Data

### ■ Front & Back Lead Dimension



### ■ Top Adhesive Peel Off Strength : 10~70g



### ■ Package

| Inner Box Size |            |
|----------------|------------|
| Reel           | Size H(mm) |
| 1              | 13         |
| 2              | 24         |
| 3              | 36         |
| 5              | 60         |
| 10             | 113        |



| External Box Size |             |            |             |
|-------------------|-------------|------------|-------------|
| Contain (Kpcs)    | Length (mm) | Width (mm) | Height (mm) |
| 25K               | 180         | 180        | 60          |
| 50K               | 180         | 180        | 110         |
| 150K              | 430         | 200        | 200         |
| 300K              | 400         | 400        | 200         |



### ■ Storage Data :

Storage time at the environment temp:  $25\pm 5^\circ\text{C}$  & humidity:  $60\pm 20\%$  is valid for one year from the date of delivery.

## ● Reliability Test and Requirement

| Test Item                                     | Test Method              | Procedure                                                                                                                           | Requirements                                                                           |
|-----------------------------------------------|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| Temperature Coefficient of Resistance (T.C.R) | JIS C 5201-1 clause 4.8  | -55°C or +155°C, 25°C is the reference temperature                                                                                  | Refer to Ratings                                                                       |
| Short Time Overload                           | JIS C 5201-1 clause 4.13 | General : 2.5 times RCWV or Max. Overload voltage whichever is less for 5 seconds.                                                  | ±1 : ±(1.0%+0.05 Ω)<br>±5 : ±(2.0%+0.1 Ω)<br>Value <1 Ω : ±(2.0%+0.1 Ω)                |
| IR Reflow                                     | Sony SS-00254            |                                                   | ±1 : ±(1.0%+0.05 Ω)<br>±5 : ±(1.0%+0.05 Ω)                                             |
| Leaching                                      | Sony SS-00254-9          | 260±5°C for 30 seconds.                                                                                                             | >95% Coverage                                                                          |
| Soldering Heat                                | JIS C 5201-1 clause 4.18 | 260±5°C for 10 seconds.                                                                                                             | ±1 : ±(0.5%+0.05 Ω)<br>±5 : ±(1.0%+0.05 Ω)<br>Value <1 Ω : ±(1.0%+0.05 Ω)              |
| Temperature Cycling                           | JIS C 5201-1 clause 4.19 | -55°C to +155°C, 5 cycles                                                                                                           | 0.1%、0.5%、1% : ±(0.5%+0.05 Ω)<br>2%、5% : ±(1.0%+0.10 Ω)<br>Value <1 Ω : ±(1.0%+0.10 Ω) |
| Electric Iron                                 | Sony SS-00254-5          | Preheating temperature : 350±10°C<br>Electric iron preheating time : 3+1/-0 sec                                                     | ±1 : ±(1.0%+0.05 Ω)<br>±5 : ±(1.0%+0.05 Ω)<br>Value <1 Ω : ±(1.0%+0.05 Ω)              |
| Resistance to Solvent                         | JIS C 5201-1 clause 4.29 | The tested resistor be immersed into isopropyl alcohol of 20~25°C for 60 secs.<br>Then the resistor is left in the room for 48 hrs. | ±1 : ±(0.5%+0.05 Ω)<br>±5 : ±(0.5%+0.05 Ω)<br>Value <1 Ω : ±(1.0%+0.05 Ω)              |
| Load Life in Humidity                         | JIS C 5201-1 clause 4.24 | 40±2°C, 90~95% R.H. RCWV or Max. working voltage whichever is less for 1000 hrs with 1.5 hrs "ON" and 0.5 hr "OFF" .                | 0.1%、0.5%、1% : ±(1.0%+0.05 Ω)<br>2%、5% : ±(2.0%+0.05 Ω)<br>Value <1 Ω : ±(2.0%+0.05 Ω) |
| Load Life (Endurance)                         | JIS C 5201-1 clause 4.25 | 70±2°C, RCWV or Max. working voltage whichever is less for 1000 hrs with 1.5 hrs "ON" and 0.5 hr "OFF" .                            | 0.1%、0.5%、1% : ±(1.0%+0.05 Ω)<br>2%、5% : ±(3.0%+0.10 Ω)<br>Value <1 Ω : ±(3.0%+0.10 Ω) |
| Insulation Resistance                         | JIS C 5201-1 clause 4.6  | 100V for 1 minute.                                                                                                                  | ≥ 10G Ω                                                                                |
| Terminal Bending Strength                     | JIS C 5201-1 clause 4.33 | Bending once for 5 seconds<br>D : 0402、0603、0805=5mm<br>1206、1210、1812=3mm<br>2010、2512 =2mm                                        | ±1 : ±(1.0%+0.05 Ω)<br>±5 : ±(1.0%+0.05 Ω)                                             |



## ● General Information

### ■ Recommend Land Pattern Design



### ■ Dimension

Unit: mm

| Item \ Type | 0201 | 0402 | 0603 | 0805 | 1206 | 1210 | 1812 | 2010 | 2512 |
|-------------|------|------|------|------|------|------|------|------|------|
| A           | 0.25 | 0.60 | 0.80 | 1.30 | 2.20 | 2.00 | 3.11 | 3.80 | 4.90 |
| B           | 1.10 | 1.60 | 2.40 | 2.90 | 4.20 | 4.40 | 5.91 | 6.60 | 8.10 |
| C           | 0.32 | 0.70 | 1.00 | 1.45 | 1.80 | 2.70 | 3.30 | 2.70 | 3.40 |

## ■ Performance Characteristics

### ■ Power Derating Curve



Power rating or current rating is in the case based on continuous full-load at ambient temperature of 70°C. For operation at ambient temperature in excess of 70°C, the load should be derated in accordance with figure of derating Curve.

### ■ Voltage Rating or Current Rating

Resistance Range:  $\geq 1 \Omega$

Rated Voltage: The resistor shall have a DC continuous working voltage or a RMS AC continuous working voltage at commercial-line frequency and wave form corresponding to the power rating, as determined formula as following:

$$E(\text{RCWV}) = \sqrt{P \times R}$$

E=Rated voltage(V)  
 P=Power rating(W)  
 R=Nominal resistance( $\Omega$ )



## Standard Resistance Values in a Decade

Marking code:

- 1%: marking code, please refer to E96 and E24 data form as below  
 Ex: 120K, The marking code is 1203 in E24  
 121K, The marking code is 1213 in E96
- 5%: marking code, please refer to E24 data form as below  
 Ex: 120K, The marking code is 124 in E24
- Note: 0201/0402 series resistor has no marking code.
- Type: 0603 1% marking code, please refer to E-96 multiplier code.

| E192 | E96 | E48 | E192 | E96 | E48 | E192 | E96 | E48 | E192 | E96 | E48 | E192       | E96        | E48       |           |
|------|-----|-----|------|-----|-----|------|-----|-----|------|-----|-----|------------|------------|-----------|-----------|
| 100  | 100 | 100 | 169  | 169 | 169 | 287  | 287 | 287 | 487  | 487 | 487 | 825        | 825        | 825       |           |
| 101  |     |     | 172  |     |     | 291  |     |     | 493  |     |     | 835        |            |           |           |
| 102  | 102 |     | 174  | 174 |     | 294  | 294 |     | 499  | 499 |     | 845        | 845        |           |           |
| 104  |     |     | 176  |     |     | 298  |     |     | 505  |     |     | 856        |            |           |           |
| 105  | 105 | 105 | 178  | 178 | 178 | 301  | 301 | 301 | 511  | 511 | 511 | 866        | 866        | 866       |           |
| 106  |     |     | 180  |     |     | 305  |     |     | 517  |     |     | 876        |            |           |           |
| 107  | 107 |     | 182  | 182 |     | 309  | 309 |     | 523  | 523 |     | 887        | 887        |           |           |
| 109  |     |     | 184  |     |     | 312  |     |     | 530  |     |     | 898        |            |           |           |
| 110  | 110 | 110 | 187  | 187 | 187 | 316  | 316 | 316 | 536  | 536 | 536 | 909        | 909        | 909       |           |
| 111  |     |     | 189  |     |     | 320  |     |     | 542  |     |     | 920        |            |           |           |
| 113  | 113 |     | 191  | 191 |     | 324  | 324 |     | 549  | 549 |     | 931        | 931        |           |           |
| 114  |     |     | 193  |     |     | 328  |     |     | 556  |     |     | 942        |            |           |           |
| 115  | 115 | 115 | 196  | 196 | 196 | 332  | 332 | 332 | 562  | 562 | 562 | 953        | 953        | 953       |           |
| 117  |     |     | 198  |     |     | 336  |     |     | 569  |     |     | 965        |            |           |           |
| 118  | 118 |     | 200  | 200 |     | 340  | 340 |     | 576  | 576 |     | 976        | 976        |           |           |
| 120  |     |     | 203  |     |     | 344  |     |     | 583  |     |     | 988        |            |           |           |
| 121  | 121 | 121 | 205  | 205 | 205 | 348  | 348 | 348 | 590  | 590 | 590 |            |            |           |           |
| 123  |     |     | 208  |     |     | 352  |     |     | 597  |     |     |            |            |           |           |
| 124  | 124 |     | 210  | 210 |     | 357  | 357 |     | 604  | 604 |     | <b>E24</b> | <b>E12</b> | <b>E6</b> | <b>E3</b> |
| 126  |     |     | 213  |     |     | 361  |     |     | 612  |     |     | 10         | 10         | 10        | 10        |
| 127  | 127 | 127 | 215  | 215 | 215 | 365  | 365 | 365 | 619  | 619 | 619 | 11         |            |           |           |
| 129  |     |     | 218  |     |     | 370  |     |     | 626  |     |     | 12         | 12         |           |           |
| 130  | 130 |     | 221  | 221 |     | 374  | 374 |     | 634  | 634 |     | 13         |            |           |           |
| 132  |     |     | 223  |     |     | 379  |     |     | 642  |     |     | 15         | 15         | 15        |           |
| 133  | 133 | 133 | 226  | 226 | 226 | 383  | 383 | 383 | 649  | 649 | 649 | 16         |            |           |           |
| 135  |     |     | 229  |     |     | 388  |     |     | 657  |     |     | 18         | 18         |           |           |
| 137  | 137 |     | 232  | 232 |     | 392  | 392 |     | 665  | 665 |     | 20         |            |           |           |
| 138  |     |     | 234  |     |     | 397  |     |     | 673  |     |     | 22         | 22         | 22        | 22        |
| 140  | 140 | 140 | 237  | 237 | 237 | 402  | 402 | 402 | 681  | 681 | 681 | 24         |            |           |           |
| 142  |     |     | 240  |     |     | 407  |     |     | 690  |     |     | 27         | 27         |           |           |
| 143  | 143 |     | 243  | 243 |     | 412  | 412 |     | 698  | 698 |     | 30         |            |           |           |
| 145  |     |     | 246  |     |     | 417  |     |     | 706  |     |     | 33         | 33         | 33        |           |
| 147  | 147 | 147 | 249  | 249 | 249 | 422  | 422 | 422 | 715  | 715 | 715 | 36         |            |           |           |
| 149  |     |     | 252  |     |     | 427  |     |     | 723  |     |     | 39         | 39         |           |           |
| 150  | 150 |     | 255  | 255 |     | 432  | 432 |     | 732  | 732 |     | 43         |            |           |           |
| 152  |     |     | 258  |     |     | 437  |     |     | 741  |     |     | 47         | 47         | 47        | 47        |
| 154  | 154 | 154 | 261  | 261 | 261 | 442  | 442 | 442 | 750  | 750 | 750 | 51         |            |           |           |
| 156  |     |     | 264  |     |     | 448  |     |     | 759  |     |     | 56         | 56         |           |           |
| 158  | 158 |     | 267  | 267 |     | 453  | 453 |     | 768  | 768 |     | 62         |            |           |           |
| 160  |     |     | 271  |     |     | 459  |     |     | 777  |     |     | 68         | 68         | 68        |           |
| 162  | 162 | 162 | 274  | 274 | 274 | 464  | 464 | 464 | 787  | 787 | 787 | 75         |            |           |           |
| 164  |     |     | 277  |     |     | 470  |     |     | 796  |     |     | 82         | 82         |           |           |
| 165  | 165 |     | 280  | 280 |     | 475  | 475 |     | 806  | 806 |     | 91         |            |           |           |
| 167  |     |     | 284  |     |     | 481  |     |     | 816  |     |     |            |            |           |           |

According to IEC publication 63

## ■ mΩ Resistance Codes

| Resistance | Code | 0603 Code | Resistance | Code | 0603 Code | Resistance | Code | 0603 Code | Resistance | Code | 0603 Code | Resistance | Code | 0603 Code |
|------------|------|-----------|------------|------|-----------|------------|------|-----------|------------|------|-----------|------------|------|-----------|
| 10mΩ       | R010 | 010       | 65mΩ       | R065 | 065       | 0.12Ω      | R120 | R12       | 0.27Ω      | R270 | R27       | 0.56Ω      | R560 | R56       |
| 15mΩ       | R015 | 015       | 68mΩ       | R068 | 068       | 0.13Ω      | R130 | R13       | 0.30Ω      | R300 | R30       | 0.60Ω      | R600 | R60       |
| 20mΩ       | R020 | 020       | 70mΩ       | R070 | 070       | 0.15Ω      | R150 | R15       | 0.33Ω      | R330 | R33       | 0.65Ω      | R650 | R65       |
| 30mΩ       | R030 | 030       | 75mΩ       | R075 | 075       | 0.16Ω      | R160 | R16       | 0.36Ω      | R360 | R36       | 0.68Ω      | R680 | R68       |
| 40mΩ       | R040 | 040       | 80mΩ       | R080 | 080       | 0.18Ω      | R180 | R18       | 0.40Ω      | R400 | R40       | 0.70Ω      | R700 | R70       |
| 50mΩ       | R050 | 050       | 90mΩ       | R090 | 090       | 0.20Ω      | R200 | R20       | 0.43Ω      | R430 | R43       | 0.75Ω      | R750 | R75       |
| 56mΩ       | R056 | 056       | 0.10Ω      | R100 | R10       | 0.22Ω      | R220 | R22       | 0.47Ω      | R470 | R47       | 0.80Ω      | R800 | R80       |
| 60mΩ       | R060 | 060       | 0.11Ω      | R110 | R11       | 0.25Ω      | R250 | R25       | 0.50Ω      | R500 | R50       | 0.90Ω      | R900 | R90       |

Revision : April 11, 2018

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Thick Film Resistors](#) category:*

*Click to view products by [Ever Ohms](#) manufacturer:*

Other Similar products are found below :

[MCR03EZPFX3162](#) [MCR004YZPJ332](#) [201007J022KT4E](#) [201007F1653T4E](#) [201007F6652T4E](#) [0603WAF137KT5E](#) [RTT204702FTE](#)  
[RTT203000FTE](#) [RTT2056R0FTE](#) [CR2010F470KE04Z](#) [RTT018451FTH](#) [RTT021802DTH](#) [0402WGF510LTCE](#) [0201WMJ0200TEE](#)  
[TR0603B26K7P0550Z](#) [0201WMF5102TEE](#) [1210W2J047KT5E](#) [YLR12-2-4F-W](#) [HOT\(0.25x1.3\)-3.2-0R-I](#) [HOT\(0.4x1.5\)-5.2-0R-I](#)  
[HoT\(0.45x1.5\)-8.2-0R-I](#) [0201WMF1103TEE](#) [0201WMF7152TEE](#) [1210W2J0124T5E](#) [201007J010LT4E](#) [201007J0360T4E](#) [201007J0430T4E](#)  
[0805W8F931KT5E](#) [1206W4F5231T5E](#) [1210W2J0620T5E](#) [201007J0822T4E](#) [0201WMF1005TCE](#) [0201WMF1212TCE](#) [0201WMF1373TCE](#)  
[0201WMF1400TCE](#) [0201WMF2000TEE](#) [0201WMF2001TCE](#) [0201WMF226JTCE](#) [0201WMF2672TCE](#) [0201WMF2803TCE](#)  
[0201WMF357JTCE](#) [0201WMF3743TCE](#) [0201WMF430JTCE](#) [0201WMF4990TCE](#) [0201WMF5104TCE](#) [0201WMF510JTEE](#)  
[0201WMF5110TCE](#) [0201WMF6652TEE](#) [0201WMF6812TCE](#) [0201WMF8200TCE](#)