

■ Precision Product Thin Film Chip Resistor — TP Series



Top view



Bottom view

■ Applications

- Computer & relative products
- Communication devices
- Measuring instrument
- Converters
- Printing equipment

■ Features

- Excellent long-term stability
- The variance of reliability test is reduced to $\pm 0.1\%$
- Low TCR down to $\pm 5 \text{ ppm}/^\circ\text{C}$
- Tight tolerance down to $\pm 0.01\%$
- Halogen free and lead free
- RoHS compliant

■ Parts Number Explanation

■ Example:

TP	1206	B	10K0	P	05	10	Z
Product Type	Size (Inch)	Tolerance	Resistance	Package	Quantity (PCS)	TCR (ppm/°C)	Optional
TP Series Precision Product Thin Film Chip Resistor	0402 0603 0805 1206 1210 2010 2512	T : $\pm 0.01\%$ A : $\pm 0.05\%$ B : $\pm 0.1\%$ C : $\pm 0.25\%$ D : $\pm 0.5\%$ F : $\pm 1.0\%$	4 digits EX. 22R0 = 22 Ω 100R = 100 Ω 2K20 = 2.2 K Ω 22K0 = 22 K Ω 100K = 100 K Ω 1M00 = 1 M Ω	P : Paper Taping (0603~1210) Q : Paper Taping (0402) E : Embossed Taping	04 : 4000 05 : 5000 10 : 10000	05 : ± 5 10 : ± 10 15 : ± 15 25 : ± 25	Z : Default Code



**TP Series Precision Product Thin Film
Chip Resistor Product Specifications**

Document No.	S-10-12-61-02
Released Date	2021/05/19
Page No.	2/9

Standard Electrical Specifications

項目 Item 型別 Type	額定功率 Rated Power at 70°C	最大 工作電壓 Max Working Voltage	最大 過負載電壓 Max Overload Voltage	溫度係數 T.C.R. (PPM/°C)	阻值範圍 Resistance Range						
					T ±0.01%	A ±0.05%	B ±0.1%	C ±0.25%	D ±0.5%	F ±1.0%	
TP0402	0.063W	50V	100V	±5	49.9 Ω ~ 12 KΩ	20 Ω ~ 12 KΩ					
				±10, ±15		10 Ω ~ 68 KΩ					
				±25		4.7 Ω ~ 220 KΩ					
TP0603	0.1W	75V	150V	±5	49.9 Ω ~ 30 KΩ	20 Ω ~ 30 KΩ					
				±10, ±15		10 Ω ~ 332 KΩ					
				±25		4.7 Ω ~ 680 KΩ					
TP0805	0.125W	150V	300V	±5	49.9 Ω ~ 50 KΩ	20 Ω ~ 50 KΩ					
				±10, ±15		10 Ω ~ 680 KΩ					
				±25		4.7 Ω ~ 1 MΩ					
TP1206	0.25W	200V	400V	±5	49.9 Ω ~ 100 KΩ	20 Ω ~ 100 KΩ					
				±10, ±15		10 Ω ~ 1 MΩ					
				±25		4.7 Ω ~ 1.5 MΩ					
TP1210	0.25W			400V	±5	49.9 Ω ~ 100 KΩ	20 Ω ~ 100 KΩ				
					±10, ±15		10 Ω ~ 100 KΩ				
					±25		4.7 Ω ~ 1 MΩ				
TP2010	0.5W			400V	±5	49.9 Ω ~ 100 KΩ	20 Ω ~ 100 KΩ				
					±10, ±15		10 Ω ~ 100 KΩ				
					±25		4.7 Ω ~ 1 MΩ				
TP2512	0.75W	400V	±5	49.9 Ω ~ 100 KΩ	20 Ω ~ 100 KΩ						
			±10, ±15		10 Ω ~ 100 KΩ						
			±25		4.7 Ω ~ 1 MΩ						



- Operating Temperature Range : -55°C ~ +155°C.
- For non-standard parts, please contact our sales department.

■ **Construction**



①	Alumina Substrate	④	Bottom Inner Electrode	⑦	Side Inner Electrode
②	Resistive Layer	⑤	Protective Overcoat	⑧	Nickel Barrier
③	Top Inner Electrode	⑥	Marking	⑨	Solder coating (Sn)

■ **Dimensions**



Unit : mm

TYPE	L	W	H	l ₁	l ₂
TP0402	1.00 ± 0.10	0.50 ± 0.05	0.30 ± 0.05	0.20 ± 0.10	0.20 ± 0.10
TP0603	1.60 ± 0.15	0.80 ± 0.10	0.45 ± 0.10	0.30 ± 0.20	0.30 ± 0.20
TP0805	2.00 ± 0.15	1.25 ± 0.15	0.55 ± 0.10	0.35 ± 0.20	0.40 ± 0.20
TP1206	3.10 ± 0.15	1.60 ± 0.15	0.55 ± 0.10	0.45 ± 0.20	0.50 ± 0.20
TP1210	3.10 ± 0.15	2.50 ± 0.15	0.55 ± 0.10	0.45 ± 0.20	0.50 ± 0.20
TP2010	5.00 ± 0.15	2.50 ± 0.15	0.55 ± 0.10	0.60 ± 0.20	0.60 ± 0.20
TP2512	6.30 ± 0.15	3.20 ± 0.15	0.55 ± 0.10	0.60 ± 0.20	0.60 ± 0.20



■ Performance Characteristics

■ Power Derating Curve

The Operating Temperature Range: $-55^{\circ}\text{C} \sim +155^{\circ}\text{C}$.

Power rating is in the case based on continuous full-load at ambient temperature of 70°C . For operation at ambient temperature in excess of 70°C , the load should be derated in accordance with figure of derating Curve.



■ Rated Voltage

Resistance Range: $\geq 1\Omega$

Rated Voltage: The resistor shall have a DC continuous working voltage or a RMS AC continuous working voltage at commercial-line frequency and wave form corresponding to the power rating, as determined formula as following:

$$V = \sqrt{P \times R}$$

V = Rated voltage (V)

P = Rated power (W)

R = Nominal resistance (Ω)



**TP Series Precision Product Thin Film
Chip Resistor Product Specifications**

Document No.	S-10-12-61-02
Released Date	2021/05/19
Page No.	5/9


Reliability Tests and Requirements

Test Item	Test Method	Procedure	Requirements
Temperature Coefficient of Resistance (T.C.R)	JIS-C-5201-1 4.8 IEC-60115-1 4.8	At 25 / -55°C and 25°C / +125°C, 25°C is the reference temperature	Refer to Standard Electrical Specifications
Short Time Overload	JIS-C-5201-1 4.13 IEC-60115-1 4.13	2.5 times RCWW or Max. Overload voltage whichever is less for 5 seconds.	±(0.1%+0.05Ω) No Visual damage
Insulation Resistance	JJIS-C-5201-1 4.6 IEC-60115-1 4.6	Apply 100VDC for 1 minute.	≥10GΩ
Solderability	JIS-C-5201-1 4.17 IEC-60115-1 4.17	245±5°C for 3 seconds.	>95% Coverage No Visual damage
Resistance to Soldering Heat	JIS-C-5201-1 4.18 IEC-60115-1 4.18	260±5°C for 10 seconds.	±(0.1%+0.05Ω) No Visual damage
Leaching	JIS-C-5201-1 4.18 IEC-60068-2-58 8.2.1	260±5°C for 30 seconds.	>95% Coverage No Visual damage
Rapid Change of Temperature	JIS-C-5201-1 4.19 IEC-60115-1 4.19	-55°C to +155°C, 300 cycles	±(0.2%+0.05Ω) No Visual damage
High Temperature Exposure	JIS-C5201-1 4.25 IEC 60068-2-2	At 155±5°C for 1000 hours.	±(0.2%+0.05Ω)
Resistance to Solvent	JIS-C-5201-1 4.29	The tested resistor be immersed into isopropyl alcohol of 20~25°C for 60 secs. Then the resistor is left in the room for 48 hrs.	±(0.1%+0.05Ω) No Visual damage
Damp Heat with Load	JIS-C-5201-1 4.24 IEC-60115-1 4.24	40±2°C, 90~95% R.H. RCWW or Max. working voltage whichever is less for 1000 hrs with 1.5 hrs "ON" and 0.5 hr "OFF"	±(0.1%+0.05Ω)
Biased Humidity	MIL-STD-202 Method 103	1,000 hours; 85°C / 85% RH, 10% of operating power. Measurement at 24±4 hours after test conclusion.	±(0.1%+0.05Ω)
Load Life (Endurance)	JIS-C-5201-1 4.25 IEC-60115-1 4.25.1	70±2°C, RCWW or Max. working voltage whichever is less for 1000 hrs with 1.5 hrs "ON" and 0.5 hr "OFF" .	±(0.1%+0.05Ω)
Bending Strength	JIS-C-5201-1 4.33 IEC-60115-1 4.33	Bending once for 5 seconds D : 0402、0603、0805 = 5mm 1206、1210 = 3mm 2010、2512 = 2mm	±(0.1%+0.05Ω) No Visual damage


● We can also provide AEC-Q200 test reports if required by customers.

Recommended Customer Soldering Parameters

Wave solder Temperature condition



Solder reflow Temperature condition




Rework temperature (hot air equipment) : 350°C, 3~5seconds

Recommended reflow methods

IR, vapor phase oven, hot air oven

If reflow temperatures exceed the recommended profile, devices may not meet the performance requirements.

Recommend Land Pattern Design




Unit: mm

Type	0402	0603	0805	1206	1210	2010	2512
Item A	0.50	0.80	1.30	2.20	2.00	3.80	4.90
Item B	1.60	2.40	2.90	4.20	4.40	6.60	8.10
Item C	0.70	1.00	1.40	1.70	2.70	2.70	3.40

■ **Packaging Information**


■ **Reel Dimensions**



Unit: mm

TYPE	SIZE	A	φB	φC	φD	W	φM
0402	7"	10K/Reel	2.0±0.5	13.5±1.0	21±1.0	60±1.0	178±2.0
0603/0805/1206/ 1210	7"	5K/Reel	2.0±0.5	13.5±1.0	21±1.0	60±1.0	178±2.0
2010/2512	7"	4K/Reel	2.0±0.5	13.5±1.0	21±1.0	16.0±2.0	178±2.0


■ **Paper Tape Dimensions**



Unit: mm

Type	A	B	W	E	F	G	H	T	φD	P
0402	0.70±0.10	1.20±0.10	8.0±0.20	1.75±0.10	3.5±0.05	4.0±0.10	2.0±0.05	0.45±0.10	1.50 ^{+0.10} ₋₀	2.0±0.10
0603	1.05±0.20	1.80±0.20	8.0±0.20	1.75±0.10	3.5±0.05	4.0±0.10	2.0±0.05	0.60±0.10		4.0±0.10
0805	1.55±0.20	2.30±0.20	8.0±0.20	1.75±0.10	3.5±0.05	4.0±0.10	2.0±0.05	0.75±0.10		
1206	1.90±0.20	3.50±0.20	8.0±0.20	1.75±0.10	3.5±0.05	4.0±0.10	2.0±0.05	0.75±0.10		
1210	2.85±0.20	3.50±0.20	8.0±0.20	1.75±0.10	3.5±0.05	4.0±0.10	2.0±0.05	0.75±0.10		

■ **Plastic Embossed Tape Dimensions**




Unit: mm

Type	A	B	W	E	F	G	H	T	φD	φD1	T1	P
2010	2.80±0.20	5.60±0.20	12±0.10	1.75±0.10	5.5±0.05	4.0±0.10	2.0±0.05	0.23±0.10	1.50 ^{+0.10} ₋₀	1.50±0.10	0.85±0.15	4.0±0.10
2512	3.40±0.20	6.70±0.20	12±0.10	1.75±0.10	5.5±0.05	4.0±0.10	2.0±0.05	0.23±0.10		1.50±0.10	0.85±0.15	

■ **Front & Back Lead Dimensions**



■ **Top Adhesive Peel Off Strength : 10~70g**




■ **Package**

Inner Box Size	
Reel	Size H(mm)
1	13
2	24
3	36
5	60
10	113



External Box Size			
Contain (Kpcs)	Length (mm)	Width (mm)	Height (mm)
25K	180	180	60
50K	180	180	110
150K	430	200	200
300K	400	400	200



■ **Storage Data :**

Storage time at the environment temp: $25\pm 5^{\circ}\text{C}$ & humidity: $60\pm 20\%$ is valid for one year from the date of delivery.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Thick Film Resistors - SMD category](#):

Click to view products by [Ever Ohms manufacturer](#):

Other Similar products are found below :

[CR-05FL7--150R](#) [CR-05FL7--698K](#) [CR-12JP4--680R](#) [CRCW04021K20FKEE](#) [CRCW04028R20JNEE](#) [CRCW06032K10FKEC](#)

[CRCW06036K80FKEE](#) [M55342K03B499DRS6](#) [M55342K06B14E0RS6](#) [M55342K06B1E78RS3](#) [M55342K06B6E19RWL](#)

[M55342K06B6E81RS3](#) [M55342K09B5D62RS6](#) [M55342M05B200DRWB](#) [M55342M06B26E7RS3](#) [M55342M06B4K70MS3](#)

[742C083750JTR](#) [MCR01MZPF1202](#) [MCR01MZPF1601](#) [MCR01MZPF1800](#) [MCR01MZPF6201](#) [MCR01MZPF9102](#) [MCR01MZPJ121](#)

[MCR01MZPJ125](#) [MCR01MZPJ751](#) [MCR03EZHZ103](#) [MCR03EZPF2004](#) [MCR03EZPJ270](#) [MCR03EZPJ821](#) [MCR10EZPF1102](#)

[MCR10EZPF2700](#) [MCR18EZPJ330](#) [RC1005F1152CS](#) [RC1005F1372CS](#) [RC1005F1912CS](#) [RC1005F2052CS](#) [RC1005F3011CS](#)

[RC1005F471CS](#) [RC1005F4751CS](#) [RC1005F5621CS](#) [RC1005F6041CS](#) [RC1005J121CS](#) [RC1005J122CS](#) [RC1005J154CS](#) [RC1005J180CS](#)

[RC1005J181CS](#) [RC1005J202CS](#) [RC1005J391CS](#) [RC1005J560CS](#) [RC1005J683CS](#)