

# Pocket Fold-up Thermometer

✓ **4.5" stainless steel probe adjusts from 0 to 180°**  
*With detents at 45°, 90°, 135° and 180°*

## Features:

- Wide °C/°F switchable temperature range  
-58 to 572°F (-50 to 300°C)
- Fold up probe 4.5" (114mm) adjusts from 0° to 180° for best measurement and viewing angle
- Large LCD display with 0.1 degree resolution
- Auto power off after 1 hour or when probe is placed in stored position
- Data Hold and Min/Max recordings
- Fast response time — one second under normal conditions
- Complete with wrist strap and one AAA battery



Specifications	
Range	-58 to 572°F (-50 to 300°C)
Accuracy	±1.8°F (-22 to 482°F); ±1°C (-30 to 250°C)
Resolution	0.1°/1° resolution
Dimensions	6.1 x 2.0 x 0.8" (154 x 50 x 20mm)
Weight	2.5oz (71g)

## Ordering Information:

39272 .....Pocket Fold-up Thermometer  
409992 .....Vinyl Pouch Carrying Case



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Environmental Test Equipment](#) category:*

*Click to view products by [Extech](#) manufacturer:*

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [S-11](#) [FLUKE-LDG](#) [382153](#) [FM100](#) [RH210](#) [382253](#) [MO290-P](#)  
[GEO-CABLE-REEL-50M](#) [T197914](#) [RD300-L](#) [IR11BD](#) [IR11GM](#) [IR12GM](#) [IR21BD](#) [IR31CE](#) [IR32BC](#) [IR33BC](#) [MP7217TC](#) [NGM-1](#) [SGX-](#)  
[7NH3](#) [UT381](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-NmHc-100](#) [3.000.401](#) [AX-7535](#) [CS-9S6SS-A](#) [P 2800 A](#) [P 2801](#) [P 2802](#) [P 5039](#) [P 5130](#) [P](#)  
[5055](#) [P 5060](#) [P 5065](#) [P 5086](#) [P 5090](#) [P 5110](#) [P 5115](#) [P 5135](#) [P 5140](#) [P 5145](#) [P 5150](#) [P 5160](#)