



Heavy Duty Hot Wire Thermo-Anemometer

Telescoping probe is designed to fit into small openings

And measures airflow down to 40ft/min (0.2m/s)

Features:

- Telescoping probe is ideal for measuring in HVAC ducts and other small vents; extends up to 7ft (2.1m) maximum length with cable
- Built-in RS-232 PC serial interface for connection to PC
- Extra large 1.4" (36mm) dual LCD display
- · MAX/MIN, Data Hold
- Complete with telescoping probe with cable, six AAA batteries and protective holster.
 NOTE: AC Adaptor not available for this model
- Optional Windows® compatible Data Acquisition Software and serial cable enable user to display and capture readings on a PC, with adjustable sample rate and alarms



Hot Wire Thermo-Anemometer 407123

| Specifications | Resolution | Basic Accuracy |
|-------------------------|----------------------------------|----------------|
| Air Velocity | | |
| 0.2 to 20m/s | 0.1m/s | ±3% |
| 40 to 3940ft/min | 1ft/min | |
| 0.5 to 45MPH | 0.1MPH | |
| 1.0 to 38.8knots | 0.1knots | |
| 0.7 to 72km/h | 0.1km/h | |
| Temperature & Windchill | | |
| 32 to 122°F | 0.1° | ±1.5°F |
| 0 to 50°C | 0.1° | ±0.8°C |
| Dimensions | 7 x 2.9 x 1.3" (178 x 74 x 33mm) | |
| Weight | 17oz (482g) | |

Ordering Information:

| 407123Heavy Duty Hot Wire Thermo-Anemometer | |
|---------------------------------------------------------------------------------|-----|
| 407123-NISTHeavy Duty Hot Wire Thermo-Anemometer w/ Calibration Traceable to NI | IST |
| 407001Data Acquisition PC Software and Serial Cable | |
| 407001-USBUSB Adaptor for 407001 | |



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160