

Laser Distance Meter

Laser measurement accurate to 0.06 inches

With Historical Storage that recalls the previous 20 records (measured or calculated results)

Features:

- Measures from 2" to 164' (0.05 to 50m)
- Automatically calculates Area and Volume
- Indirect measurement using Pythagorean theorem
- Continuous measurement function with Min/Max distance tracking updates every 0.5 seconds
- Addition/Subtraction
- Front or rear edge reference
- Low battery indicator
- Double molded housing (IP54)
- Auto power off
- Complete with carrying case and 2 AAA batteries



Measures up to 164ft (50m) with laser accuracy

Specifications	
Measurement Range	2" to 164' (0.05 to 50m)
Accuracy (up to 32'/10m)	±0.06" (±1.5mm)
Resolution	0.001" (0.001m)
Length Add calculation	99'11" (99.99m)
Area calculation	999.99 sq. ft. (999.99m ²)
Volume calculation	999.99 cu. ft. (999.99m ³)
Laser Power Off	after 30 seconds
Auto Power Off	after 3 minutes
Power Supply	2 AAA Batteries
Dimensions	4.5 x 1.9 x 1.1" (115 x 48 x 28mm)
Weight	5.3oz (150g)

Ordering Information:

DT300Laser Distance Meter



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Environmental Test Equipment](#) category:

Click to view products by [Extech](#) manufacturer:

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [S-11](#) [FLUKE-LDG](#) [382153](#) [FM100](#) [RH210](#) [382253](#) [MO290-P](#)
[GEO-CABLE-REEL-50M](#) [T197914](#) [RD300-L](#) [IR11BD](#) [IR11GM](#) [IR12GM](#) [IR21BD](#) [IR31CE](#) [IR32BC](#) [IR33BC](#) [LM100](#) [NGM-1](#) [SGX-](#)
[7NH3](#) [UT381](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-NmHc-100](#) [AX-7535](#) [CS-9S6SS-A](#) [P 1115](#) [P 2800 A](#) [P 2802](#) [P 5039](#) [P 5130](#) [P 5055](#) [P](#)
[5060](#) [P 5065](#) [P 5086](#) [P 5090](#) [P 5110](#) [P 5115](#) [P 5135](#) [P 5140](#) [P 5150](#) [P 5160](#) [P 5165](#) [P 5170](#)