

## **EasyView™ Light Meter with Memory**

Store and recall up to 50 measurements

With realtive or real time clock stamp

## **Features:**

- Wide measurement range to 99,990Fc (999,900Lux) with resolution of 0.001Fc and 0.01Lux
- · Luminous intensity (candela) calculations
- Ripple function excludes the effect of stray light from the primary light source measurement
- Auto Power off with disable feature
- Multiple point average function
- Timed-Hold, Relative in absolute value or % deviation, and Comparator function with high low alarms
- · Cosine and color corrected, CNS 5119 Class II
- Complete with built-in stand, light sensor and protective cover with 36" (0.9m) cable, protective holster, 6 AAA batteries, and carrying case





in direct sunlight

## **Ordering Information:**

EA33	.EasyView™ L	ight Meter wit	h Memory
EA33-NIST	.EA33 with N	IST Certificate	_

Specifications	
Display Counts	999,999 count LCD
Fc Range	9.999Fc, 99.99Fc, 999.9Fc, 9,999Fc, 99,990Fc
Lux Range	99.99Lux, 999.9Lux, 99999Lux, 99,990Lux, 999,900Lux
Max. Resolution	0.001Fc/0.01Lux
Basic Accuracy	±3%
Cosine & Color Corrected:	Yes
Dimensions:	5.9 x 2.8 x 1.4" (150 x 72 x 33mm)
Weight:	11.29oz (320g)



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 UT353 382253

MO290-P GEO-CABLE-REEL-50M T197914 RD300-L RD300-S IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC

MP7217TC NGM-1 UT381 VQ21TSB F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801

P 2802 P 5039 P 5055 P 5060 P 5065 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160