

IR260 Compact InfraRed Thermometer

Compact non-contact InfraRed (IR) Thermometer measures up to 752°F (400°C) with built-in laser pointer to identify target area and improve aim. Adjustable emissivity for better accuracy when measuring temperature on different surface materials.







Checking for heat loss around windows and doors



Detect hot spots on circuit breaker panels



Features

- Take non-contact temperature measurements from -4 to 752°F (-20 to 400°C)
- 12:1 distance to spot (target) ratio
- Built-in laser pointer identifies target area with on/off button
- Programmable high/low alarm alerts user visually and audibly when temperature exceeds set limits (audible alarm can be muted)
- Adjustable emissivity for better accuracy on variety of surfaces

- · Automatic Data Hold when trigger released
- MAX/MIN function stores maximum and minimum readings with easy recall
- Bright white backlighting illuminates display for taking measurements at night or in areas with low background light levels
- Auto power off ~9 seconds after trigger is released
- Overrange and low battery indicators
- Complete with two AA batteries

Specifications

IR Temperature Range	-4 to 752°F (-20 to 400°C)
Basic Accuracy	±2% of reading or ±3.6°F/2°C
Max resolution	0.1°F/°C
Distance to Target	12:1
Emissivity	0.1 to 1.00 (adjustable)
Dimensions	6.8x3.8x1.8" (172x97x46mm)
Weight	8oz (226g)

Ordering

IR260 Compact InfraRed Thermometer



UPC Code: 793950422618

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160