

CAT IV Insulation Tester/MultiMeter with Wireless PC Interface



With a full-featured True RMS MultiMeter in a single, compact instrument

Features:

- Wireless USB interface transmits measurement data to a PC
- Backlit super large triple display
- 125V, 250V, 500V, and 1000V test voltages
- Insulation Resistance from $0.001 M\Omega$ to $4000 M\Omega$
- Auto discharge of capacitive voltage
- Lock Power On Function for hands-free operation
- Data Hold and Auto Power Off
- Min/Max and Relative mode
- Waterproof (IP67) rugged double-molded design
- · Complete with remote receiver with USB cable, Windows® compatible software, heavy duty test leads, alligator clip test lead, Type K bead wire temperature probe with adapter, carrying case, and 6 x AA batteries



Measure the insulation resistance of transformer windings



Only a True RMS meter can give accurate readings of distorted waveforms





Continuous data streaming to your PC in real time

9	EXTECH 500	000 1
AUTO		5.5
True RMS	MultiMeter & II	nsulation Tester + PeakHOLD
STORE	MAX MIN	REL HOLD
RANGE	INSULATION	AC+DC EXIT
LOCK	TEST	¥4 usa
Allessa.	DA OFF	Activity V _{sc}
4-20 mAx		mV Acres
μA	1	Hzw
	-	4
C€	MG300	IP67
104	on A	V Hz %Temp Ω++-0it-
20A for 30 eve	sec MAX ry 15 min A C	AT IV 600V
1000	mA 10A 500mA FUSED	СОМ

Specifications	Range	Resolution	Accuracy	
Insulation Tester				
Insulation Resistance	4 Μ Ω , 4 0Μ Ω , 4 00Μ Ω , 4 000Μ Ω	$0.001 M\Omega$	±3%	
Insulation Test Voltages	125V, 250V, 500V, 1000V			
Multimeter				
AC Voltage	1000V	0.1mV	±1%	
DC Voltage	1000V	0.01mV	±0.06%	
AC Current	10A	0.1µA	±1.5%	
DC Current	10A	0.01µA	±1.0%	
Resistance	40ΜΩ	0.01Ω	±0.3%	
Capacitance	40mF	0.001nF	±3.5%	
Frequency	100MHZ	0.001HZ	±0.1%	
Duty Cycle	0.1 to 99.9%	0.01	±1.2%	
Temperature	-58 to 2192°F	0.1°F	±1% + 4.5°F	
	-50 to 1200°C	0.1°C	±1% + 2.5°C	
4-20mA%	-25 to 125%	0.01%		
Continuity/Diode	Yes			
Power source	6 x AA batteries			
Dimensions	7.8 x 3.6 x 1.9" (200 x 92 x 50mm)			
Weight	20.5oz (582g)			

Ordering Information:

MG300CAT IV Insulation Tester/True RMS MultiMeter w/Wireless PC Interface (915MHz) MG300-NISTMG300 with Certificate of Calibration Traceable to NIST

MG302CAT IV Insulation Tester/True RMS MultiMeter w/Wireless PC Interface (433MHz)

MG302-NISTMG302 with Certificate of Calibration Traceable to NIST

TL805.....Double Injected Test Leads

(NOTE: USA, Mexico, and Canada use 915MHz model and majority of other countries use 433MHz model)







X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Insulation Testers / Megohmmeters category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

MG320 380320 BM15 307A 308A MG310 380260 380363 MG325 MG500 IM75 FLUKE-1503 63800-2850