# **Waterproof pH Pens**

Easy-to-use, rugged, and economical pH pens

Choice of models with/without Temperature measurement

#### **Features:**

- · Waterproof housing (meets IP67) protects meter from damage operating in a wet environment
- · Easy to calibrate single CAL key with automatic pH buffer recognition (4, 7, and 10pH)
- Choice of 3 point calibration for better accuracy
- · Convenient pen size fits into your pocket
- · Data hold freezes reading on display
- · Low battery indicator
- · Auto power off saves battery life with disable function option
- · Complete with built in electrode, sensor cap, inner pH electrode protection cap, and 4 LR44 button batteries

#### Model PH50:

• pH range: 2 to 12pH

#### **Model PH60:**

- pH range: 0 to to 14pH
- Temperature range: 32 to 122°F (0 to 50°C)
- Automatic Temperature Compensation
- Dual LCD displays both pH and Temperature readings



### **Ordering Information:**

PH50	Waterproof pH Pen
PH60	Waterproof pH Pen with Temperature
PH103	Trinak huffers (6ea - 4 7 10nH & 2 Rinse solutions)



Specifications	Model PH50	Model PH60	
pH	2.0 to 12.0pH	0.0 to 14.0pH	
Temperature	_	32 to 122°F (0 to 50°C)	
Resolution	0.1pH, 0.1°	0.1pH, 0.1°	
Accuracy	±0.3pH	±0.2pH; ±1°F/±0.5°C	
Power	Four LR44 button batteries		
Dimension	6 x 1.5 x 0.9" (152 x 37 x 24mm)		
Weight	2.3oz (65g)		



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160