

SMD High Current Molded Inductors - FCH1040 - Series

FCH1040-Series

●Features:


- Ultra low cost
- Shielded constructions
- High current rating up to DC 45Amp
- High frequency range up to 5MHz
- Very low DC resistance
- Low Noise
- RoHS compliant

●Applications:

- PDA/Notebook/Desktop/Server applications
- DC/DC converter




1.Shapes and Dimensions (形状及尺寸)




2. Schematic:

recommendation: (mm)



3. layout



SMD High Current Molded Inductors -FCH1040 - Series

4. FCH1040 -Series:

Part Number (品名)	Inductance (uH) ±20% (电感值)	DCR(mΩ) (直流阻抗)		Isat DC Current (A) (饱和电流)	Irms DC Current (A) (温升电流)
		Typical	MAX	Typical	Typical
FCH1040-R15M	0.15	0.60	0.65	60.0	45.0
FCH1040-R20M	0.20	0.60	0.76	60.0	35.0
FCH1040-R22M	0.22	0.60	0.76	60.0	35.0
FCH1040-R30M	0.30	0.75	0.95	42.0	38.0
FCH1040-R33M	0.33	0.87	1.00	45.0	35.0
FCH1040-R36M	0.36	1.10	1.26	38.0	35.0
FCH1040-R47M(点焊)	0.47	2.30	3.00	35.0	30.0
FCH1040-R47M(打扁)	0.47	1.30	1.50	35.0	30.0
FCH1040-R56M	0.56	1.80	2.00	30.0	25.5
FCH1040-R68M	0.68	1.80	2.40	29.0	25.0
FCH1040-R80M	0.80	2.50	3.00	25.0	20.0
FCH1040-1R0M	1.00	3.50	4.2	23.0	18.0
FCH1040-1R5M	1.50	4.60	5.3	22.0	15.0
FCH1040-2R2M	2.20	5.80	7.6	17.0	14.0
FCH1040-3R3M	3.30	9.00	12.0	15.0	13.0
FCH1040-4R7M	4.70	13.00	15.5	13.0	9.0
FCH1040-5R6M	5.60	16.00	23.0	11.5	8.2
FCH1040-6R8M	6.80	19.80	23.0	11.0	7.8
FCH1040-8R2M	8.20	27.0	31.0	9.0	7.5
FCH1040-100M	10.00	31.0	36.0	9.0	7.2
FCH1040-150M	15.00	48.5	56.0	6.5	5.5
FCH1040-220M	22.00	52.0	68.5	6.0	5.1
FCH1040-330M	33.00	86	98	5.0	4.0
FCH1040-470M	47.00	131	150	4.0	3.0
FCH1040-680M	68.00	213	240	3.5	2.9
FCH1040-101M	100.00	330	370	2.0	1.8
FCH1040-151M	151.00	376	481	2.0	1.5

Remark:

<1>Inductance: 100KHz 0.1V

<2>Tolerance of inductance:±20%


<3>Isat: The value of curret indicates that inductance drops 30%(Typcial) from its initial value

<4>Irms:The value of current indicates that the temperature of the coil is increase 40°C (Typical)

<5>Test condition: Ta= 25°C

SMD High Current Molded Inductors -FCH1040 - Series


5.FCH1040-Series



5.1 Reel Dimensions & Packing Unit (卷轴尺寸及包装数量)

Part Number 品名	Dimensions of Reel 卷轴尺寸				Packaging Unit 包装数
	A	B	C	W	
FCH1040/1050/1060	330	100.0±2.00	13.5±1.0	24.0±0.50	1000pcs/r/800pcs/r

6. Reflow Profile for SMT Components



	Package Thickness 封装厚度	Package Volume 封装体积		
		<350 mm ³	350~2000 mm ³	>2000 mm ³
PB-Free Assembly 无铅装配	<1.6mm	260°C	260°C	260°C
	1.6~2.5mm	260°C	250°C	245°C
	≥2.5mm	250°C	245°C	245°C

※ Reflow is referred to standard IPC/JEDEC J-STD-020D.
回流焊参照标准 IPC/JEDEC J-STD-020D.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Inductors](#) category:

Click to view products by [FANGCHENG](#) manufacturer:

Other Similar products are found below :

[CR32NP-100KC](#) [70F224AI](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#)
[PE-53601NL](#) [PE-53602NL](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2-R47-R](#) [HC8-1R2-R](#)
[HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-4R7M](#) [RCP1317NP-391L](#) [DH2280-4R7M](#) [DS1608C-106](#) [B10TJ](#) [B82498B3101J000](#) [ELJ-](#)
[RE27NJF2](#) [1812CS-153XJ](#) [1812CS-183XJ](#) [1812CS-223XJ](#) [1812LS-104XJ](#) [1812LS-105XJ](#) [1812LS-124XJ](#) [1812LS-154XJ](#) [1812LS-223XJ](#)
[1812LS-224XJ](#) [1812LS-563XJ](#) [1812LS-683XJ](#) [1812LS-824XJ](#) [NIN-FB101JTR110F](#) [NIN-FB471JTR62F](#) [NIN-FC1R5JTR220F](#) [NIN-](#)
[HCR15JTRF](#) [NIN-HCR33JTRF](#) [NIN-HDR22JTRF](#) [NIN-HDR82JTRF](#) [NIN-HK2N7STRF](#) [NIN-PA150KTR370F](#) [NIN-PB100KTR550F](#)