



金属化聚酯膜电容器(浸渍型) Metallized polyester film capacitor(Dipped)

■ 外形图 Outline Drawing

| | Forming Lead Shapes | | | |
|--|-------------------------------------|-----------------|-----------------|-----------------|
| | I | II | III | IV |
| | | | | |
| | P > F | | P < F | |
| | 0mm < P-F < 3mm | 3mm < P-F < 8mm | 3mm < F-P < 5mm | 0mm < F-P < 3mm |
| | F ± 0.8mm; A < 5.0mm; B=4.5 ± 0.5mm | | | |

■ 特点

- 金属化聚酯膜,无感卷绕结构
- 体积小,自愈性好
- 阻燃性环氧粉末包封 (UL94/V-0)

■ 主要用途

- 用于开关电源、电子镇流器和变频器等中间电路直流滤波 (如: DC-Link、PFC等)


■ Features

- Metallized polyester film, non-inductive wound construction
- Small size and Excellent self-healing property
- Flame retardation epoxy resin coating (UL94/V-0)

■ Typical Applications

- As intermediate circuit capacitors for SMPS, electronic ballast, inverter (i.e. DC-link, DC-filter and P.F.C)

α : The series product is only recommended to use in DC-filter or DC-blocking circuits. It means the voltage applied to the capacitors must be unidirectional ripple voltage. The typical voltage curve is as follows reference. If you have any questions for this note, please feel free to contact with our technical engineer.



Here: $V_1 \geq 0, V_2 \leq U_R, V_{rms} = (V_2 - V_1) \div \sqrt{2}, I_{rms} = 2\pi f \times C \times (V_2 - V_1) \div \sqrt{2}$
 U_R is the rated voltage of the capacitor

■ 技术要求 Specifications

| | | | | | |
|---|---|--------------|--------|--------|--------|
| 引用标准 Reference Standard | GB/T 7332 (IEC 60384-2) | | | | |
| 气候类别 Climatic Category | 55/105/21 | | | | |
| 额定温度 Rated Temperature | 85°C | | | | |
| 工作温度范围 Operating Temperature Range | -55°C ~ 105°C (+85°C to +105°C: decreasing factor 1.25% per °C for U_R) | | | | |
| 额定电压 Rated Voltage | 250V, 400V/450V, 520V, 630V | | | | |
| 电容量范围 Capacitance Range | 0.010μF ~ 10.0μF | | | | |
| 电容量偏差 Capacitance Tolerance | ± 5%(J), ± 10%(K), ± 20%(M) | | | | |
| 耐电压 Voltage Proof | 1.6 U_R (5s) | | | | |
| 损耗角正切 Dissipation Factor | ≤ 0.8% (20°C , 1kHz) | | | | |
| 绝缘电阻 Insulation Resistance | R ≥ 30 000MΩ, $C_N \leq 0.33\mu F$ RC _N ≥ 5 000s, $C_N > 0.33\mu F$ (20°C , 100V, 1min) | | | | |
| 最大脉冲爬升速率 Maximum Pulse Rise Time(dV/dt): 若实际工作电压 U 比额定电压 U_R 低, 电容器可工作在更高的 dV/dt 场合, 这样 dV/dt 允许值应为右表值乘以 U_R/U 。 If the working voltage(U) is lower than the rated voltage(U_R), the capacitor can be worked at a higher dV/dt. In this case, the maximum allowed dV/dt is obtain by multiplying the right value with U_R/U . | U_R (V) | dV/dt (V/μs) | | | |
| | | P=7.5 | P=10.0 | P=15.0 | P=22.5 |
| | 250 | 80 | 60 | 50 | 30 |
| | 400/450 | 150 | 120 | 100 | 50 |
| | 520 | 200 | 180 | 150 | 80 |
| 630 | 350 | 300 | 200 | 100 | |

产品编码说明 Part number system

■ 18位产品代码如下：

The 18 digits part number is formed as follow:

| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----|----|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 |
| C | 2 | 2 | | | | | | | | | | | | | | | |

| | | | |
|---------|--|----------------|--|
| 第1~3位 | 型号代码 C22=CL21X | Digit 1 to 3 | Series code C22=CL21X |
| 第4~5位 | 直流额定电压 2E=250V 2G=400V 2S=450V 2T=520V 2J=630V | Digit 4 to 5 | DC rated voltage 2E=250V 2G=400V 2S=450V 2T=520V 2J=630V |
| 第6~8位 | 标称容量 举例：103=10 × 10 ³ pF=0.01μF | Digit 6 to 8 | Rated capacitance value For example: 103=10 × 10 ³ pF=0.01μF |
| 第9位 | 容量偏差 J= ± 5% K= ± 10% M= ± 20% | Digit 9 | Capacitance tolerance J= ± 5%,K= ± 10%,M= ± 20% |
| 第10位 | 引线脚距P 3=7.5mm 4=10.0mm 6=15.0mm 9=22.5mm | Digit 10 | Pitch 3=7.5mm 4=10.0mm 6=15.0mm 9=22.5mm |
| 第11位 | 内部特征码 | Digit 11 | Internal use |
| 第12~15位 | 引线加工和包装代码 | Digit 12 to 15 | Lead form and packaging code |
| 第16~18位 | 内部特征码 | Digit 16 to 18 | Internal use |

■ Table 1 引线加工和包装代码 lead form and packaging code

| 第 12 位 Digit 12 | | 第 13 位 Digit 13 | | 第 14 位 Digit 14 | | 第 15 位 Digit 15 | |
|-----------------|---|-----------------|---------------------------------|-----------------|------------------------------|-----------------|--|
| 代码 Code | 说明 explanation | 代码 Code | 说明 explanation | 代码 Code | 说明 explanation | 代码 Code | 说明 explanation |
| A | 弹带包装 ammo-pack | 2 | F=5.0mm | 1 | 表示弯脚 kinked | A | 产品在连续的两个载带孔之间 each cap. between two consecutive holes P3=12.7mm,H=20.0mm (For pitch=7.5mm) |
| | | 3 | F=7.5mm | | | E | P3=25.4mm;H=20.0mm (For pitch=10.0/15.0mm) |
| | | 4 | F=10.0mm | | | | (Detail information refer to pag 18) |
| 6 | F=15.0mm | | | | | | |
| F | 引线成型 lead kinked | 2 | F=5.0mm | 0 | B=4.5mm (the length of B) | 0 | B 的长度偏差 ± 0.5mm B Length tolerance ± 0.5mm |
| 3 | F=7.5mm | | | | | | |
| 4 | F=10.0mm | | | | | | |
| 6 | F=15.0mm | | | | | | |
| Y | 直脚 straight lead “Y” in the figure above | 代码 Code | 说明 explanation | | | 0 | 引线长度偏差 ± 0.5mm Length tolerance ± 0.5mm |
| | | 45 | 引线长度 4.5mm lead length 4.5mm | | | | |

第 12-15 位代码为 “C000” 表示标准的引线长度 (20mm ~ 30mm)
Digit 12-15 code “C000” means standard lead length (20mm ~ 30mm)



■ 外形尺寸 Dimensions (mm)

小型化 Miniature version

| 250Vdc | | | | | | |
|------------------------|----------|----------|----------|------|-----|--------------------|
| C _N (μF) | W max | H max | T max | P | d | Part number |
| 0.22 | 9.8 | 7.9 | 4.0 | 7.5 | 0.5 | C222E224-3S****+++ |
| 0.27 | 9.8 | 8.8 | 4.1 | 7.5 | 0.5 | C222E274-3S****+++ |
| 0.33 | 9.8 | 9.1 | 4.5 | 7.5 | 0.5 | C222E334-3S****+++ |
| 0.47 | 9.8 | 11.4 | 5.0 | 7.5 | 0.5 | C222E474-3S****+++ |
| 0.56 | 9.8 | 12.9 | 5.1 | 7.5 | 0.5 | C222E564-3S****+++ |
| 0.68 | 9.8 | 13.4 | 5.6 | 7.5 | 0.5 | C222E684-3S****+++ |
| 0.82 | 9.8 | 13.9 | 6.1 | 7.5 | 0.5 | C222E824-3S****+++ |
| 1.00 | 9.8 | 14.5 | 6.7 | 7.5 | 0.5 | C222E105-3S****+++ |
| 0.33 | 12.3 | 7.9 | 4.1 | 10.0 | 0.6 | C222E334-4S****+++ |
| 0.47 | 12.3 | 9.6 | 4.2 | 10.0 | 0.6 | C222E474-4S****+++ |
| 0.56 | 12.3 | 9.9 | 4.7 | 10.0 | 0.6 | C222E564-4S****+++ |
| 0.68 | 12.3 | 10.3 | 5.1 | 10.0 | 0.6 | C222E684-4S****+++ |
| 0.82 | 12.3 | 10.8 | 5.5 | 10.0 | 0.6 | C222E824-4S****+++ |
| 1.00 | 12.3 | 11.3 | 6.1 | 10.0 | 0.6 | C222E105-4S****+++ |

| 520Vdc | | | | | | |
|------------------------|----------|----------|----------|------|-----|--------------------|
| C _N (μF) | W max | H max | T max | P | d | Part number |
| 0.033 | 9.8 | 7.7 | 3.9 | 7.5 | 0.5 | C222T333-3S****+++ |
| 0.047 | 9.8 | 8.8 | 4.1 | 7.5 | 0.5 | C222T473-3S****+++ |
| 0.068 | 9.8 | 9.4 | 4.8 | 7.5 | 0.5 | C222T683-3S****+++ |
| 0.10 | 9.8 | 10.8 | 5.8 | 7.5 | 0.5 | C222T104-3S****+++ |
| 0.15 | 9.8 | 11.9 | 7.0 | 7.5 | 0.5 | C222T154-3S****+++ |
| 0.068 | 12.3 | 8.7 | 4.0 | 10.0 | 0.6 | C222T683-4S****+++ |
| 0.10 | 12.3 | 9.9 | 4.5 | 10.0 | 0.6 | C222T104-4S****+++ |
| 0.15 | 12.3 | 10.7 | 5.3 | 10.0 | 0.6 | C222T154-4S****+++ |
| 0.22 | 12.3 | 13.3 | 6.0 | 10.0 | 0.6 | C222T224-4S****+++ |
| 0.33 | 12.3 | 14.6 | 7.3 | 10.0 | 0.6 | C222T334-4S****+++ |

| 400Vdc/450Vdc [#] | | | | | | |
|----------------------------|----------|----------|----------|------|-----|--------------------|
| C _N (μF) | W max | H max | T max | P | d | Part number |
| 0.047 | 9.8 | 6.9 | 3.7 | 7.5 | 0.5 | C222G473-3S****+++ |
| 0.068 | 9.8 | 7.8 | 4.0 | 7.5 | 0.5 | C222G683-3S****+++ |
| 0.082 | 9.8 | 8.7 | 4.0 | 7.5 | 0.5 | C222G823-3S****+++ |
| 0.10 | 9.8 | 9.0 | 4.4 | 7.5 | 0.5 | C222G104-3S****+++ |
| 0.12 | 9.8 | 9.3 | 4.7 | 7.5 | 0.5 | C222G124-3S****+++ |
| 0.15 | 9.8 | 10.8 | 5.1 | 7.5 | 0.5 | C222G154-3S****+++ |
| 0.18 | 9.8 | 11.2 | 5.5 | 7.5 | 0.5 | C222G184-3S****+++ |
| 0.22 | 9.8 | 11.8 | 6.0 | 7.5 | 0.5 | C222G224-3S****+++ |
| 0.27 | 9.8 | 12.4 | 6.6 | 7.5 | 0.5 | C222G274-3S****+++ |
| 0.10 | 12.3 | 8.4 | 3.8 | 10.0 | 0.6 | C222G104-4S****+++ |
| 0.12 | 12.3 | 8.7 | 4.0 | 10.0 | 0.6 | C222G124-4S****+++ |
| 0.15 | 12.3 | 9.0 | 4.4 | 10.0 | 0.6 | C222G154-4S****+++ |
| 0.18 | 12.3 | 9.4 | 4.7 | 10.0 | 0.6 | C222G184-4S****+++ |
| 0.22 | 12.3 | 10.3 | 4.9 | 10.0 | 0.6 | C222G224-4S****+++ |
| 0.27 | 12.3 | 10.8 | 5.4 | 10.0 | 0.6 | C222G274-4S****+++ |
| 0.33 | 12.3 | 12.3 | 5.4 | 10.0 | 0.6 | C222G334-4S****+++ |
| 0.47 | 12.3 | 13.9 | 6.6 | 10.0 | 0.6 | C222G474-4S****+++ |
| 0.68 | 12.3 | 16.8 | 7.4 | 10.0 | 0.6 | C222G684-4S****+++ |
| 0.82 | 12.3 | 17.5 | 8.2 | 10.0 | 0.6 | C222G824-4S****+++ |
| 1.00 | 12.3 | 18.4 | 9.1 | 10.0 | 0.6 | C222G105-4S****+++ |

- 备注: 1. “-”表示容量偏差。 “-”=capacitance tolerance code, M=±20%,K=±10%,J=±5%
 2. “****”表示引线加工和包装代码(见table 1)。“****”=lead form and packaging code (refer to table 1)
 3. “#”当额定电压为450Vdc时,第4~5位是2S。
 “#” when the rated voltage is 450Vdc,the digit 4~5 is 2S.

■ 外形尺寸 Dimensions (mm)

| 250Vdc | | | | | | |
|------------------------|----------|----------|----------|------|-----|-------------------|
| C _N (μF) | W max | H max | T max | P | d | Part number |
| 0.10 | 9.8 | 7.7 | 4.0 | 7.5 | 0.5 | C222E104-30****++ |
| 0.15 | 9.8 | 8.3 | 4.5 | 7.5 | 0.5 | C222E154-30****++ |
| 0.22 | 10.0 | 9.9 | 4.9 | 7.5 | 0.5 | C222E224-30****++ |
| 0.33 | 10.0 | 10.4 | 5.7 | 7.5 | 0.5 | C222E334-30****++ |
| 0.47 | 10.0 | 11.8 | 6.3 | 7.5 | 0.5 | C222E474-30****++ |
| 0.68 | 10.0 | 13.9 | 6.9 | 7.5 | 0.5 | C222E684-30****++ |
| 1.0 | 10.0 | 15.3 | 8.4 | 7.5 | 0.5 | C222E105-30****++ |
| 0.33 | 12.5 | 9.0 | 5.2 | 10.0 | 0.6 | C222E334-40****++ |
| 0.47 | 12.5 | 10.8 | 5.4 | 10.0 | 0.6 | C222E474-40****++ |
| 0.68 | 12.5 | 11.7 | 6.3 | 10.0 | 0.6 | C222E684-40****++ |
| 1.0 | 12.5 | 14.4 | 7.4 | 10.0 | 0.6 | C222E105-40****++ |
| 1.5 | 12.5 | 16.9 | 8.4 | 10.0 | 0.6 | C222E155-40****++ |
| 2.2 | 12.5 | 19.7 | 9.5 | 10.0 | 0.6 | C222E225-40****++ |
| 0.47 | 17.8 | 9.3 | 4.7 | 15.0 | 0.8 | C222E474-60****++ |
| 0.68 | 17.8 | 10.0 | 5.4 | 15.0 | 0.8 | C222E684-60****++ |
| 1.0 | 17.8 | 12.0 | 6.5 | 15.0 | 0.8 | C222E105-60****++ |
| 1.5 | 17.8 | 14.2 | 7.2 | 15.0 | 0.8 | C222E155-60****++ |
| 2.2 | 17.8 | 16.6 | 8.0 | 15.0 | 0.8 | C222E225-60****++ |
| 3.3 | 17.8 | 19.3 | 9.2 | 15.0 | 0.8 | C222E335-60****++ |
| 4.7 | 17.8 | 21.2 | 11.0 | 15.0 | 0.8 | C222E475-60****++ |
| 1.0 | 25.5 | 10.9 | 5.5 | 22.5 | 0.8 | C222E105-90****++ |
| 1.5 | 25.5 | 12.9 | 5.9 | 22.5 | 0.8 | C222E155-90****++ |
| 2.2 | 25.5 | 13.9 | 6.9 | 22.5 | 0.8 | C222E225-90****++ |
| 3.3 | 25.5 | 16.4 | 7.8 | 22.5 | 0.8 | C222E335-90****++ |
| 4.7 | 25.5 | 18.8 | 8.7 | 22.5 | 0.8 | C222E475-90****++ |
| 6.8 | 25.5 | 20.6 | 10.5 | 22.5 | 0.8 | C222E685-90****++ |
| 10.0 | 25.5 | 23.0 | 12.9 | 22.5 | 0.8 | C222E106-90****++ |

| 400Vdc/450Vdc [#] | | | | | | |
|----------------------------|----------|----------|----------|------|-----|-------------------|
| C _N (μF) | W max | H max | T max | P | d | Part number |
| 0.033 | 10.0 | 7.1 | 4.0 | 7.5 | 0.5 | C222G333-30****++ |
| 0.047 | 10.0 | 7.1 | 4.0 | 7.5 | 0.5 | C222G473-30****++ |
| 0.068 | 10.0 | 8.0 | 4.4 | 7.5 | 0.5 | C222G683-30****++ |
| 0.10 | 10.0 | 9.7 | 5.1 | 7.5 | 0.5 | C222G104-30****++ |
| 0.15 | 10.0 | 10.6 | 6.0 | 7.5 | 0.5 | C222G154-30****++ |
| 0.22 | 10.3 | 12.1 | 6.7 | 7.5 | 0.5 | C222G224-30****++ |
| 0.10 | 12.5 | 9.1 | 4.4 | 10.0 | 0.6 | C222G104-40****++ |
| 0.15 | 12.5 | 9.7 | 5.1 | 10.0 | 0.6 | C222G154-40****++ |
| 0.22 | 12.5 | 11.1 | 5.7 | 10.0 | 0.6 | C222G224-40****++ |
| 0.33 | 12.5 | 13.2 | 6.2 | 10.0 | 0.6 | C222G334-40****++ |
| 0.47 | 12.5 | 15.4 | 6.8 | 10.0 | 0.6 | C222G474-40****++ |
| 0.68 | 12.5 | 16.8 | 8.2 | 10.0 | 0.6 | C222G684-40****++ |
| 1.0 | 12.5 | 19.6 | 9.4 | 10.0 | 0.6 | C222G105-40****++ |
| 0.22 | 17.8 | 10.3 | 4.9 | 15.0 | 0.8 | C222G224-60****++ |
| 0.33 | 17.8 | 11.1 | 5.7 | 15.0 | 0.8 | C222G334-60****++ |
| 0.47 | 17.8 | 13.1 | 6.1 | 15.0 | 0.8 | C222G474-60****++ |
| 0.68 | 17.8 | 15.3 | 6.8 | 15.0 | 0.8 | C222G684-60****++ |
| 1.0 | 17.8 | 17.2 | 8.7 | 15.0 | 0.8 | C222G105-60****++ |
| 1.5 | 17.8 | 20.1 | 10.0 | 15.0 | 0.8 | C222G155-60****++ |
| 2.2 | 17.8 | 22.3 | 12.2 | 15.0 | 0.8 | C222G225-60****++ |
| 0.47 | 25.5 | 11.3 | 5.9 | 22.5 | 0.8 | C222G474-90****++ |
| 0.68 | 25.5 | 13.3 | 6.3 | 22.5 | 0.8 | C222G684-90****++ |
| 1.0 | 25.5 | 14.4 | 7.4 | 22.5 | 0.8 | C222G105-90****++ |
| 1.5 | 25.5 | 16.9 | 8.3 | 22.5 | 0.8 | C222G155-90****++ |
| 2.2 | 25.5 | 19.6 | 9.5 | 22.5 | 0.8 | C222G225-90****++ |
| 3.3 | 25.5 | 21.8 | 11.7 | 22.5 | 0.8 | C222G335-90****++ |

- 备注: 1. “-”表示容量偏差。 “-” =capacitance tolerance code, M= ±20%,K= ±10%,J= ±5%
 2. “****”表示引线加工和包装代码(见table 1)。“****”=lead form and packaging code (refer to table 1)
 3. “#”当额定电压为450Vdc时,第4~5位是2S。
 “#” when the rated voltage is 450Vdc,the digit 4~5 is 2S.



■ 外形尺寸 Dimensions (mm)

| 520Vdc | | | | | | |
|------------------------|----------|----------|----------|------|-----|--------------------|
| C _N (μF) | W max | H max | T max | P | d | Part number |
| 0.022 | 9.8 | 7.5 | 4.0 | 7.5 | 0.5 | C222T223-30****+++ |
| 0.033 | 9.8 | 8.5 | 4.4 | 7.5 | 0.5 | C222T333-30****+++ |
| 0.047 | 9.8 | 9.6 | 4.7 | 7.5 | 0.5 | C222T473-30****+++ |
| 0.068 | 9.8 | 10.4 | 5.4 | 7.5 | 0.5 | C222T683-30****+++ |
| 0.068 | 12.5 | 9.6 | 4.7 | 10.0 | 0.6 | C222T683-40****+++ |
| 0.10 | 12.5 | 10.9 | 5.5 | 10.0 | 0.6 | C222T104-40****+++ |
| 0.15 | 12.5 | 11.9 | 6.5 | 10.0 | 0.6 | C222T154-40****+++ |
| 0.22 | 12.5 | 14.1 | 7.1 | 10.0 | 0.6 | C222T224-40****+++ |
| 0.33 | 12.5 | 15.6 | 8.6 | 10.0 | 0.6 | C222T334-40****+++ |
| 0.10 | 17.8 | 9.4 | 4.7 | 15.0 | 0.8 | C222T104-60****+++ |
| 0.15 | 17.8 | 10.2 | 5.5 | 15.0 | 0.8 | C222T154-60****+++ |
| 0.22 | 17.8 | 11.6 | 6.1 | 15.0 | 0.8 | C222T224-60****+++ |
| 0.33 | 17.8 | 13.7 | 6.7 | 15.0 | 0.8 | C222T334-60****+++ |
| 0.47 | 17.8 | 14.9 | 7.9 | 15.0 | 0.8 | C222T474-60****+++ |
| 0.68 | 17.8 | 17.5 | 8.9 | 15.0 | 0.8 | C222T684-60****+++ |
| 1.0 | 17.8 | 20.9 | 10.7 | 15.0 | 0.8 | C222T105-60****+++ |
| 1.5 | 17.8 | 23.4 | 13.2 | 15.0 | 0.8 | C222T155-60****+++ |
| 0.33 | 25.5 | 12.4 | 5.4 | 22.5 | 0.8 | C222T334-90****+++ |
| 0.47 | 25.5 | 13.3 | 6.3 | 22.5 | 0.8 | C222T474-90****+++ |
| 0.68 | 25.5 | 15.5 | 7.0 | 22.5 | 0.8 | C222T684-90****+++ |
| 1.0 | 25.5 | 18.5 | 8.4 | 22.5 | 0.8 | C222T105-90****+++ |
| 1.5 | 25.5 | 20.4 | 10.3 | 22.5 | 0.8 | C222T155-90****+++ |
| 2.2 | 25.5 | 22.6 | 12.5 | 22.5 | 0.8 | C222T225-90****+++ |

| 630Vdc | | | | | | |
|------------------------|----------|----------|----------|------|-----|--------------------|
| C _N (μF) | W max | H max | T max | P | d | Part number |
| 0.010 | 9.8 | 7.6 | 4.1 | 7.5 | 0.5 | C222J103-30****+++ |
| 0.015 | 9.8 | 7.6 | 4.1 | 7.5 | 0.5 | C222J153-30****+++ |
| 0.022 | 9.8 | 8.1 | 4.6 | 7.5 | 0.5 | C222J223-30****+++ |
| 0.033 | 9.8 | 9.2 | 5.1 | 7.5 | 0.5 | C222J333-30****+++ |
| 0.047 | 9.8 | 10.5 | 5.5 | 7.5 | 0.5 | C222J473-30****+++ |
| 0.068 | 9.8 | 11.9 | 6.2 | 7.5 | 0.5 | C222J683-30****+++ |
| 0.10 | 9.8 | 13.1 | 7.7 | 7.5 | 0.5 | C222J104-30****+++ |
| 0.047 | 12.5 | 9.6 | 4.6 | 10.0 | 0.6 | C222J473-40****+++ |
| 0.068 | 12.5 | 10.3 | 5.3 | 10.0 | 0.6 | C222J683-40****+++ |
| 0.10 | 12.5 | 11.2 | 6.5 | 10.0 | 0.6 | C222J104-40****+++ |
| 0.15 | 12.5 | 13.9 | 6.9 | 10.0 | 0.6 | C222J154-40****+++ |
| 0.22 | 12.5 | 15.3 | 8.3 | 10.0 | 0.6 | C222J224-40****+++ |
| 0.10 | 17.8 | 10.6 | 5.1 | 15.0 | 0.8 | C222J104-60****+++ |
| 0.15 | 17.8 | 12.5 | 5.5 | 15.0 | 0.8 | C222J154-60****+++ |
| 0.22 | 17.8 | 13.5 | 6.5 | 15.0 | 0.8 | C222J224-60****+++ |
| 0.33 | 17.8 | 14.8 | 7.8 | 15.0 | 0.8 | C222J334-60****+++ |
| 0.47 | 17.8 | 16.3 | 9.2 | 15.0 | 0.8 | C222J474-60****+++ |
| 0.68 | 17.8 | 19.1 | 10.4 | 15.0 | 0.8 | C222J684-60****+++ |
| 1.0 | 17.8 | 22.8 | 12.6 | 15.0 | 0.8 | C222J105-60****+++ |
| 1.5 | 17.8 | 25.8 | 15.6 | 15.0 | 0.8 | C222J155-60****+++ |
| 0.22 | 25.5 | 11.2 | 5.7 | 22.5 | 0.8 | C222J224-90****+++ |
| 0.33 | 25.5 | 12.2 | 6.7 | 22.5 | 0.8 | C222J334-90****+++ |
| 0.47 | 25.5 | 14.3 | 7.3 | 22.5 | 0.8 | C222J474-90****+++ |
| 0.68 | 25.5 | 15.7 | 8.7 | 22.5 | 0.8 | C222J684-90****+++ |
| 1.0 | 25.5 | 20.0 | 9.8 | 22.5 | 0.8 | C222J105-90****+++ |
| 1.5 | 25.5 | 22.2 | 12.1 | 22.5 | 0.8 | C222J155-90****+++ |
| 2.2 | 25.5 | 24.9 | 14.8 | 22.5 | 0.8 | C222J225-90****+++ |

备注: 1. “-”表示容量偏差。 “-”=capacitance tolerance code, M=±20%,K=±10%,J=±5%
2. “****”表示引线加工和包装代码(见table 1)。“****”=lead form and packaging code (refer to table 1)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Film Capacitors](#) category:

Click to view products by [FARATRONIC](#) manufacturer:

Other Similar products are found below :

[M83421/01-3089R](#) [703-6G](#) [F450KG153J250ALH0J](#) [750-1018](#) [MEB684J2A](#) [FKP1-1000160010P15](#) [FKP1-1500160010P15](#)
[82EC1100DQ50K](#) [MMWAF150KME](#) [PCY2130F30153](#) [PME261JB5220KR19T0](#) [A521HH333M035C](#) [QXJ2E474KTPT](#) [QXL2B333KTPT](#)
[QXM2G104K](#) [B32234-.033@250V-K](#) [B32520C6332K000](#) [B32522C6104K000](#) [B32523Q3155J](#) [B32676E6755K](#) [B81133-C1104-M3](#)
[MTC355L1](#) [217-0716-001](#) [PA225L30](#) [221A10-120](#) [CB182K0184J--](#) [KP1830-247/061-G](#) [SCD105K122A3-22](#) [SCD205K122A3-24](#)
[F601BL225K063CL60A](#) [FKP1-2202KV5P15](#) [PCX2339F65224](#) [PCX2339F65334](#) [2222 368 55105](#) [2222 370 21683](#) [QXL2E473KTPT](#)
[445450-1](#) [B32524Q6155J](#) [46KI3100JBM1K](#) [4DCNAQ4450ZA0J](#) [MKP383510063JKP2T0](#) [MKT182022263473](#) [WMC08P22](#) [WMF4S68](#)
[YE333](#) [ECQ-W4223KZ](#) [EEC2G805HQA415](#) [PA103L30](#) [82DC3100DQ50J](#) [82EC2150DQ50K](#)