


Data sheet Product CAB 5 Z S




PCB connectors>Jumpers
grid 5.08 mm; for 0.6...0.64 mm wire wrap pins and \varnothing 0.6...0.7 mm The flexible contacts are shorting two pins. The jumpers can be mounted behind and next to each other.

Features

grid:	5.08 mm
surface of contact:	5.0 μ m tin
surface contact / contact sleeve:	<ul style="list-style-type: none"> • 0.5 μm Au • 1 μm Au • 5 μm Sn
no. of contacts:	2
version:	closed, hole for test probe
insert depth:	4...5.5mm
nominal current:	3 A
nominal voltage:	250 V AC
insulating body material:	PA 66
temperature range:	-40°C... +105°C
colour:	black

Technical Drawing



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Fisher](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)