

Male headers soldering technique

□ 0.635 mm, standard

| | | | | | | | |
|-------------------------|--|------|-------|---|-----------|------|-------|
| | | | | | | | |
| art. no. | dim. [mm] | | | art. no. | dim. [mm] | | |
| | A | B | C | | A | B | C |
| SL 11 112 ... | 11.20 | 3.00 | 5.40 | SL 1 025 ... | 11.20 | 2.60 | 5.80 |
| SL 11 124 ... | 12.40 | 3.00 | 6.60 | SL 1 053 ... | 13.90 | 5.80 | 5.30 |
| SL 11 139 ... | 13.90 | 3.00 | 8.10 | SL 1 078 ... | 16.40 | 5.80 | 7.80 |
| SL 11 164 ... | 16.40 | 3.00 | 10.60 | SL 1 104 ... | 19.00 | 5.80 | 10.40 |
| SL 11 190 ... | 19.00 | 3.00 | 13.20 | SL 1 128 ... | 21.40 | 5.80 | 12.80 |
| SL 11 214 ... | 21.40 | 3.00 | 15.60 | SL 1 154 ... | 24.00 | 5.80 | 15.40 |
| SL 11 240 ... | 24.00 | 3.00 | 18.20 | SL 1 179 ... | 26.50 | 5.80 | 17.90 |
| SL 11 265 ... | 26.50 | 3.00 | 20.70 | SL 1 230 ... | 31.60 | 5.80 | 23.00 |
| SL 11 316 ... | 31.60 | 3.00 | 25.80 | | | | |
| | | | | | | | |
| art. no. | dim. [mm] | | | art. no. | dim. [mm] | | |
| | A | B | C | | A | B | C |
| SL 22 112 ... | 11.20 | 3.00 | 5.40 | SL 2 025 ... | 11.20 | 2.60 | 5.80 |
| SL 22 124 ... | 12.40 | 3.00 | 6.60 | SL 2 053 ... | 13.90 | 5.80 | 5.30 |
| SL 22 139 ... | 13.90 | 3.00 | 8.10 | SL 2 078 ... | 16.40 | 5.80 | 7.80 |
| SL 22 164 ... | 16.40 | 3.00 | 10.60 | SL 2 104 ... | 19.00 | 5.80 | 10.40 |
| SL 22 190 ... | 19.00 | 3.00 | 13.20 | SL 2 128 ... | 21.40 | 5.80 | 12.80 |
| SL 22 214 ... | 21.40 | 3.00 | 15.60 | SL 2 154 ... | 24.00 | 5.80 | 15.40 |
| SL 22 240 ... | 24.00 | 3.00 | 18.20 | SL 2 179 ... | 26.50 | 5.80 | 17.90 |
| SL 22 265 ... | 26.50 | 3.00 | 20.70 | SL 2 230 ... | 31.60 | 5.80 | 23.00 |
| SL 22 316 ... | 31.60 | 3.00 | 25.80 | | | | |
| please indicate: | ... no. of contacts one row 1-36 two rows 2-72 | | | ... surface S = selective gold-plated G = gold-plated Z = tin-plated | | | |

Every pin length is available on request.

PC connector design DIL → H 2
 Female headers 2.54 solder → G 27
 Technical data → G 73 - 76
 Fem. head. 2.54 solder, put through → G 28

Female headers 2.54 SMD → G 41 - 44
 Special male & female headers → G 18
 High-prec. fem. headers 2.54 sold. → G 30 - 33
 Bar magazine → G 20 - 21

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fisher manufacturer](#):

Other Similar products are found below :

[LA 9/150 24V](#) [FR 55 35 100 ME](#) [FR 80 42 100 ME](#) [GEL 28 30](#) [GEL 28 50](#) [GEL 45 10](#) [GEL 45 50](#) [GEL 60 10](#) [RL 17 160 B ME](#) [RL 17 200 B ME](#) [AKG 33 20 80 ME](#) [EMB 215 150 SA](#) [ICKS36X36X10](#) [ICKSR40X30](#) [LA 17 150 230](#) [LA 21 150 230](#) [LA 21 150 24](#) [LA 27 K 100 12](#) [LA 27 K 100 24](#) [LA 27 K 150 12](#) [LA 27 K 50 24](#) [SK4615AL](#) [SK56920AL](#) [SK56950SA](#) [SK57210SA](#) [SK57225SA](#) [SK58420AL](#) [SK 622 1000 SA](#) [SK 622 200 AL](#) [SK 622 200 SA](#) [SK 623 100 SA](#) [SK 626 1000 SA](#) [SK 627 1000 AL](#) [SK 627 200 AL](#) [SK 627 200 SA](#) [SK LED R 65 SA](#) [SK LED R 80 SA](#) [AKG 105 26 120 ME](#) [AKG 41 24 80 ME](#) [AKG 55 28 50 SA](#) [AKG 69 24 100 SA](#) [GE K 80 42 100 SA](#) [GEL 45 30](#) [GEL 60 25](#) [GEL F 15 10](#) [RL 17 220 B ME](#) [TUF 120 42 220 ME](#) [TUF 55 16 200 SA](#) [ICKS25X25X12.5](#) [KN3041 SLS 30X12 SCHWARZ](#)