

DB815

Foot Dispenser



A basic air-powered system, floor mounted and foot actuated. Includes a three-way air valve and built in air regulator, ideal for non-critical dispensing operations. As long as the foot pedal is depressed, fluid will be dispensed. The unit is suitable for all types of fluids. The model with suck-back option ensures that low viscosity liquids do not drip.

Features

- Economical & simple to use
- Wide range of applications
- Barrel suck-back ensures no dripping
- No electric needed

Sales & Support

Fisnar
Global Headquarters
Tel: 1 (973) 646-5044
www.fisnar.com

Fisnar Europe
European Headquarters
Tel: +00 44 (0) 1355 577 222
www.fisnareurope.co.uk

Fisnar Asia
Asia Headquarters
Tel: 852-2389-2827
www.fisnareurope.co.uk

Models

DB815	Foot dispenser
DB815-SB	Foot Dispenser w/ suck-back

Specifications

Cycle:	Maintained by user
Foot pedal:	Air valve in unit
Air Input:	70 - 100 psi
Air Output:	1 - 100 psi
Dimensions (WxDxH)	
DB815:	4.50" x 8.50" x 4.88"
DB815-SB:	4.50" x 8.50" x 5.38"
Weight	
DB815:	3.5 lbs.
DB815-SB:	3.8 lbs.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fisnar](#) manufacturer:

Other Similar products are found below :

[0401-08-000460](#) [0410-08-000318](#) [381-600-PB](#) [381-8425-AB](#) [381-8425-AC](#) [381-8425-PC](#) [560027D](#) [560047](#) [560048](#) [560049](#) [560050](#)
[560051](#) [560069W-LF](#) [5601034](#) [5601035](#) [5601036](#) [5601051](#) [5601053](#) [5601054](#) [5601056](#) [5601058](#) [5601071](#) [5601129](#) [5601157](#) [5601159](#)
[5601160](#) [5601161](#) [5601162](#) [5601163](#) [5601164](#) [5601165](#) [5601167](#) [5601170](#) [5601172](#) [5601173](#) [5601238](#) [0401-08-000174](#) [5601240](#)
[0401-08-000176](#) [5601245](#) [0401-08-000181](#) [5601247](#) [0401-08-000183](#) [5601252](#) [5601275](#) [5601276](#) [5601277](#) [5601278](#) [5601280](#) [5601309](#)
[5601354](#) [5601358](#) [5601380](#) [5601469](#)