





dimensions in millimetres

LED RECESSED PROFILE



The most important features:

- excellent heat dissipation
- designed and manufactured in Poland
- cover made of polycarbonate UV & heat resistant

Application:

- home and shop furniture assembly
- stairs assembly
- wall and ceiling lighting decorations





Specifications	
Available colours	silver, white, black
Material	anodized aluminium
Application	recessed tiles
LED strip width	up to 12 mm
Basic length	1000 mm
Additional lengths	2020 mm, 3000 mm, 4150 mm

Product code Product description FIX-GLG2-xx-1M LED Surface Profile SU2 FIX-COV-ML-PVC-1000 LED profile Cover PCV milky FIX-GLG2-xx-EC-O Cover end cap (with wire hole) x2 pcs

*xx - AS - silver andoda, WL - white, BL - black

LED profile GLG2 cover



LED profile GLG2 accessories





Easy cover assembly

Thanks to the use of a semi-circular cover slot, the installation is trouble-free, and disassembly does not damage the cover



Easy cover assembly

Thanks to the use of a semi-circular cover slot, the installation is trouble-free, and disassembly does not damage the cover



Paint

In addition to anodized profiles (silver, inox stainless steel, black), in the case of wholesale orders, it is possible to order powder coated profiles in any color from the RAL palette.



Even more light

The innovative method for cover assembly we have developed ensures maximum use of the space inside the profile. Thanks to this, we have minimized the diffraction phenomenon, leaving much more space for light.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fix & Fasten manufacturer:

Other Similar products are found below:

4-5 4-6 BCG-250 BUB-72H CC-1S CC-2 CC-3 CC-4 CC-5 CC-6 CC-7S CGLA-4 CGLA-4S CGLA-6 CGLA-8 CM-19S CRS-7045-M5-20 F8040UL FCA-1 FCA-3 FCA-5 FCA-6 FF-1 FF-11 FF-12 FF-2 FF-35 FF-6 FF-7 FF-8 FIX-2-2 FIX-2-2.5 FIX-2-3 FIX-2-4 FIX-2-6 FIX-3.0X23-PRO FIX-3.0X23-WH FIX-3-10 FIX-3-12 FIX-3-13 FIX-3-14 FIX-3-15 FIX-3-16 FIX-3-18 FIX-3-2 FIX-3-20 FIX-3-2.5 FIX-3-25 FIX-3-3 FIX-3-30