

## **Temperature Accessories**

### **Contact Probes**

#### **80PK-1 and 80PJ-1 Bead Probe**

- 80PK-1 : Type-K thermocouple for general purpose applications • 80PJ-1 operates
- with J-type thermometers
- Measurement range: -40 to 260°C

#### **80BK Low-cost Integrated DMM** Probe

- Type-K thermocouple with standard banana iack
- Convenient one piece construction
- Compatible with DMMs with temperature measurement functions
- Measurement range : -40 to 260°C

#### **80PK-2A Immersion Probe**

- Type-K thermocouple for use in liquids and gels
- Measurement range: -40 to 982°C

#### **80PK-3A Surface Probe**

- Type-K thermocouple for flat or curved surfaces such as plates and rollers
- Measurement range: 0 to 260°C

#### **80PK-4A Air Probe**

- Type-K thermocouple for use in air or gases, except halides and sulfides
- Bead protected by perforated baffle
- Measurement range: -40 to 816°C

#### **80PK-5A and 80PT-5A Piercing** Probe

- 80PK-5A : Type-K thermocouple suitable for food industry, liquids and gels except halides and sulfides
- 80PT-5A operates with T-type thermometers • Measurement range: -40 to 260°C



- **80PK-6A Exposed Probe**
- Type-K thermocouple provides fast response for non-reducing air and gases, except halides, sulfides, and vacuums
- Measurement range: -40 to 816°C

#### **80PK-7 Industrial Surface Probe**

- Type-K thermocouple for surfaces in rugged environment
- Durable ribbon sensor
- Measurement range: -127 to 600°C

#### **80PK-8 Pipe Clamp Temperature** Probe

- Type-K thermocouple for fast temperature and superheat measurements of pipe surfaces • Durable ribbon sensor
- Measurement range: -29 to 149°C for pipe diameters from 6.4 to 34.9mm



#### **80PK-9 and 80PJ-9 General Purpose Probe**

- 80PK-9 : Type-K thermocouple surface, air and non-caustic
- gases • 80PJ-9 operates with J-type
- thermometers • Measurement range :
  - -40°C to 260°C

#### **80T-150U Universal Temperature** Probe

- Compatible with Fluke DMM
- High accuracy, fast reading for low voltage (below 24Vac, 60V dc) applications
- Measurement range: -50 to 150°C
- or 1mV/°F (switchable)



• Output: 1mV/°C

#### **80TK Thermocouple Module**

- Converts a DMM to a
- thermometer • For use with type-K thermocouples in low voltage applications (below 24Vac,



- 60V dc) • Measurement
  - range: -50 to 1000°C (probe dependent)





## **Temperature Accessories**

#### **Non-Contact Probes**

#### 80T-IR & 80PK-IR Infrared Temperature Probes

- Ideal for applications where object being measured cannot be touched
- Provides instant and highly repeatable readings
- 80T-IR (for DMMs) and 80PK-IR (for digital thermometers) have automatic shut-off after 10 minutes
- Senses infrared energy emitted by an object
  Measurement range: -18 to 260°C





## **Other Temperature Accessories**

#### 80CK-M & 80CJ-M type K & J Male

- Mini-Connectors • Isothermal screw terminal for K or J wire
- Suitable for up to 20 guage thermocouple wire
- Color coded to industry standards (K-yellow, J-black)
- Two per package

#### 80AK

- Adapts Type-K thermocouple mini-connector to dual banana plug inputs
- Measurement range and accuracy: probe dependent
- Suitable for low voltage applications (below 30V AC, 60V DC)

#### 80PK-EXT, 80PJ-EXT and 80PT-EXT Extension Wire Kits

- Extending and repairing J, K ot T-type thermocouple wires
- Kit includes 3 meters of thermocouple wire and 1 pair of male/female mini-connectors
- Maximum continuous exposure temperature : 260°C
- 80PK-EXT is compatible with K-type thermometers, 80PJ-EXT is designed for Jtype thermometers and PT-EXT for T-type thermometers



#### Thermocouple Plug Kits 700TC1

A kit of 10 mini-plug connectors Type J (black), one Type K (yellow), one Type T (blue), one Type E (purple), one Type B or CU (white), one Type L (J-DIN) (blue), one Type U (T-DIN) (brown), one Type C (red), one Type N (orange), one



#### 700TC2

A kit of 7 mini-plug connectors Type J (black), two Type K (yellow), two Type T (blue), one Type R/S (green), one



744 787

••

••

1

thermometers																																					
Temperature Probe Compatibility Chart												Ì				Ì		ĺ							ĺ		ĺ										
																									ľ						$\square$	ľ	1				
																														1 I						.	
																						۱,		38						1 I						.	
		12B																					series	33/						1 I						.	
	0	1						日	Ξ [;	8060A / 8062A												9	se	က်						1 I						.	
	7-600	12 /			H			Series	26/79 Series III	8		Ħ	Ξİ									5	t   ;	2						1 I						.	
	4	/ 1			Series III	73 Series III	21/75 Series	E	EI.	~	S.	85 Series III	87 Series III	Series	189 Series		~		Series			100/000 11/27/23/27	5 1	/32						1 I						.	
	0	Ξ			jų.	i ii	S	S	S.	A	Ξ.	Ë,	Ξ.	er	Į.		41B		١ğ			5	3	33						1 I						.	
	7-300	$\sim$				N N	E I	23/77	Ë   ?	6	83 Series	Š	Ϋ́	20	6	2	$\sim$	0	ől		45 EOG/EOD		0.		ß		~	-		0		~	4	2	741B	743B	4
Contact Droken	1	10	16	27	2	73	21	133	28	8	8	85	28	187	<u>8</u>	86	33	123	190	43	142	8   5		30/	705	712	713	714	715	716	TIT	718	724	725	2	4	744
Contact Probes 80PK-1 through 80PK-9			2	1	<u>,</u>	1	1	1	1	1	1	1	1	2	2	1		1	1	1	1			-		_		•	_		$\vdash$	<u> </u>	•	•	•	•	-
80T-150U		•	4	1		1			•								-		•		1	-	-	-		-			•		$\vdash$	<u> </u>	i			•	
80PJ-1, 80PJ-9		•		•	-	•	-	-	-	-	-	-	-	•	-	•	-	•	-	-	-			-		-		•	-	$ \neg $	$ \rightarrow$	-		ŏ		ŏ	
80PT-5A					-			-	-		-		-		-		-		-	-	+			-		-		ě	-	-+		-		ě		ě	
80BK			•				-	+	-		-		-	•	•		-		-	-		+	-					-	-	-+		-	+-	<u> </u>	-	-	-
Non-Contact Probes																																	1	1			
80T-IR		٠	•	۲	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•					•				٠								
80PK-IR			2											2	2													•					•	•	•	•	۲
Miscellaneous																																					
80AK			۰											•																							
SOTK		•	•	٠	٠	•	•	•	•	•	•	•	•	•	•	•		•	•	•					•				۲				•	•	•	•	•
80CK-M			<u> </u>					-+	$\rightarrow$	_	_	_	_		_				_					_		_		•			$\vdash$	—	<b>↓●</b>	<b>↓</b> ●			
SOCJ-M			<u> </u>	-	<u> </u>		_	+	+	+	$\rightarrow$		_		_		_		_	-+				_		_		•			$\vdash$		╇	1.		-	-
80PK-EXT, 80PJ-EXT 80PT-EXT								_	—	_	_		_		_		_		_		-			_		_		•			$\vdash$	—	•		•	•	
OUP1-EA1																												•						•		•	•

Pub\_ID: 10015-eng Rev. 02 1: Requires 80TK 2: Requires 80AK

# cy:





this product is available from:



Thurlby Thandar Instruments Ltd.

Glebe Road, Huntingdon Cambs. PE29 7DR England **Tel: 01480 412451** Fax: 01480 450409 email: sales@tti-test.com web: www.tti-test.com

TTi is an official technical distributor for the Fluke Test Tools and Bench Instruments range in the UK.

We aim to keep many of the most popular products in stock for immediate delivery.

We can provide technically based advice on the use of these products and our sales engineers will be pleased to arrange a demonstration.



**Measurably Better Value** 

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Test Probes category:

Click to view products by Fluke manufacturer:

Other Similar products are found below :

 6214
 6474
 815003
 923832-BK-B
 P-KIT-1
 KT-MS001
 925250-R
 923848-C
 973368101
 972318101
 972318100
 MXHQ87WJ3000
 PK2 

 5MM-102
 382254
 TAS90
 VL1735/45
 973368100
 972327100
 972327101
 973995101
 CT3982B-120
 CT4386
 PP023-1
 PK1 

 5MM-125
 PK1-5MM-127
 PP026-1
 P6139B-PK10
 PQ215
 PQ219
 PQ218
 GE.3421
 GE.1511
 GE.1521
 GE.2511
 HVP15B
 TT 

 SI7002
 4005
 4011
 4015
 4016
 4018
 P TK-100
 P TK-250/100
 UTH05
 402-IEC-RT
 402-IEC-SW