

TECHNICAL DATA

Fluke 902 FC True-rms Wireless HVAC Clamp Meter



If you are an HVAC technician, you need a reliable clamp meter to keep up with your demanding world. The Fluke 902 FC delivers the features necessary to diagnose and repair HVAC systems. Additionally, with Fluke Connect® you can trend measurements, create and send reports right from the field, safely stay away from live equipment while taking measurements, and more.

Measurement capability

- 600 A ac current measurement
- 600 V ac and dc voltage measurement
- Temperature measurement from -10 °C to 400 °C (14 °F to 752 °F)
- 1000 µF capacitance measurement
- DC Current measurement to 200 µA
- True-rms voltage and current for accurate measurements on non-linear signals
- Resistance measurement to 60 kΩ
- Min and max recording to capture variations automatically

Features

- Get more done faster and safer than before by connecting your meter to Fluke Connect and capture measurements wirelessly. Save your measurement to Fluke Cloud™ storage for further analysis or comparison to earlier inspection data.
 - Read measurements on your phone at a safe distance, wearing less PPE while your meter takes the arc blast zone risks, not you.
 - Instantly trend and monitor measurements live on your phone screen for better troubleshooting results.



LOG AND TREND MEASUREMENTS

Transmit results wirelessly via Fluke Connect®

SAFETY RATING

CAT III 600V / CAT IV 300V

BACKLIT DISPLAY

For working in low-lighting spaces

HVAC SPECIFIC FEATURES

Extended resistance range to measure a broad set of thermistors, µA DC current range to measure flame sensor current, contact temperature, and capacitance

WARRANTY

Three-years





Features (continued)

- Create and email reports right from the field. When team collaboration is needed use Fluke Connect ShareLive™ video call to share live measurements and discuss next steps with colleagues.
- Don't risk transcription errors, save your measurements directly to your meter from your smartphone with the press of a button.
- CAT III 600V / CAT IV 300V safety rating
- TPAK magnetic hanging strap (optional) allows you to conveniently hang the meter while using the probes
- Ergonomic design fits in your hand and can be used while wearing personal protective equipment
- Large, easy-to-read backlit display
- Three-year warranty
- Soft carrying case
- Auto shut-off maximizes battery life so the meter works when you need it
- Measurement range feature automatically changes switch positions

Specifications

| General specifications | | | | |
|------------------------|-----------------------------------|------------|---|--|
| Function | Range | Resolution | Accuracy | Crest factor (50Hz or 60Hz) |
| A ac (via Jaw) | 60/600 A | 0.01/0.1 A | 2.0 % ± 5 digit (45-65 Hz) 2.5 % ± 5 digit (65-400 Hz) | 2.5 at 220 A 3.0 at 180 A >1.4 at 600 A Add 2 % kΩ for CF>2 |
| V ac | 600 V | 0.1 V | 1.5 % ± 5 digits (45-400Hz) | |
| V dc | 600 V | 0.1 V | 1 % ± 5 digits | |
| Ohms | 600/6,000/60,000 Ω | 0.1/1/10 | 1 % ± 5 digits | |
| µA | 200 µA | 0.1 µA | 1 % ± 4 digits | |
| Contact temperature | 10 to 400 °C (14 °F to 752 °F) | 0.1 C/F | 1 % ± 8 digits | |
| Capacitance | 100.0/1000 µF | 0.1/1 µF | 1% +/- 4 digits | |
| Continuity beeper | | | | |
| Beeper volume | 75 dBA nom. 15 cm from case front | | | |
| On threshold | <=30 Ω | | | |

Specifications (continued)

| Mechanical and general specifications | |
|---|---|
| Maximum voltage between any terminal and earth ground | 600 V |
| Battery type | 2 AA alkaline batteries, NEDA 15A, IEC LR6 |
| Temperature | Operating: -10 °C to +50 °C (14 °F to + 122 °F) Storage: -40 °C to +60 °C (-40 °F to + 140 °F) |
| Operating humidity | Non-condensing <10 °C (50 °F) |
| | ≤90 % RH @ 10 °C to 30 °C (50 °F to 86 °F) |
| | ≤75 % RH @ 30 °C to 40 °C (86 °F to 104 °F) |
| | ≤45 % RH @ 40 °C to 50 °C (104 °F to 122 °F) |
| Altitude | Operating: 3,000 m (9,842 ft) Storage: 12,000 m (39,370 ft) |
| Dimensions | 230 mm x 83.7 mm x 45.4 mm (9.06 in x 3.30 in x 1.39 in) |
| Weight (meter only) | 419 g (14 oz) |
| Safety | IEC 61010-1, Pollution Degree 2 IEC 61010-2-032: CAT III 1000 V / CAT IV 600 V IEC 61010-2-033: CAT III 1000 V / CAT IV 600 V |
| IP Rating | IEC 60529: IP30, non-operating |
| Radio Frequency Certification | FCC ID:T68-FBLE IC:6627A-FBLE |
| Electromagnetic Compatibility (EMC) | International: IEC 61326-1: Portable, Electromagnetic Environment, IEC 61326-2-2 CISPR 11: Group 1, Class A Korea (KCC): Class A Equipment (Industrial Broadcasting & Communication Equipment) USA (FCC): 47 CFR 15 subpart B. This product is considered an exempt device per clause 15.103. |
| Temperature coefficients | Add 0.1 × specified accuracy for each degree C above 28 °C or below 18 °C |

Ordering information

902 FC HVAC Clamp Meter

Included

- 902 FC HVAC Clamp Meter
- One pair TL75 Test leads
- One 80BK Integrated DMM Temperature Probe
- Two AA alkaline batteries
- Soft carrying case
- Users' manual
- Statement of Calibration Practices

Optional accessories

TPAK Magnetic Hanging Strap



Set up and sustain preventive maintenance practices with ease to help you oversee your complex world with the Fluke Connect® system of software and over 40 wireless test tools.

- Maximize uptime and make confident maintenance decisions with data you can trust and trace.
- Save measurements to the Fluke Cloud™ and associate with an asset so your team can consult both historical and current measurements from one location.
- Collaborate with ease by sharing your measurement data with team members with ShareLive™ video calls and emails.
- Wireless one-step measurement transfer with AutoRecord™ measurements eliminates transcription errors, clipboards, notebooks and multiple spreadsheets.
- Generate reports with multiple measurement types to provide status or next step recommendations.

Find out more at flukeconnect.com



All trademarks are the property of their respective owners. WiFi or cellular service required to share data. Smartphone, wireless service and data plan not included with purchase. First 5 GB of storage is free. Phone support details can be viewed at fluke.com/phones.

Fluke Connect is not available in all countries, check with your local Fluke representative.

Fluke. Keeping your world up and running.®

Fluke Europe B.V.
 P.O. Box 1186
 5602 BD Eindhoven
 The Netherlands
 Web: www.fluke.co.uk

For more information call:
 In Europe/M-East/Africa
 +31 (0)40 267 5100 or
 Fax +31 (0)40 267 5222

Fluke (UK) Ltd.
 52 Hurricane Way
 Norwich, Norfolk
 NR6 6JB
 United Kingdom
 Tel.: +44 (0) 20 7942 0700
 Fax: +44 (0) 20 7942 0701
 E-mail: industrial@uk.fluke.nl
 Web: www.fluke.co.uk

©2016 Fluke Corporation. All rights reserved.
 Data subject to alteration without notice.
 02/2016 Pub_ID: 13547-eng

Modification of this document is not permitted without written permission from Fluke Corporation.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Clamp Multimeters & Accessories](#) category:

Click to view products by [Fluke](#) manufacturer:

Other Similar products are found below :

[I800](#) [FLUKE 1630-2](#) [ZAPDUMOD-03](#) [ZARKMS-01-99](#) [UT233](#) [TESTO 770-3](#) [0590 7703](#) [AX-3550](#) [AX-M266C](#) [BM079](#) [BM089](#) [BM157](#)
[BM162](#) [BM197](#) [KEW2210R](#) [FLUKE 80I-110S](#) [FLUKE I200](#) [FLUKE I200S](#) [FLUKE I3000FLEX-24](#) [FLUKE I310S](#) [FLUKE I400](#) [CIE600](#)
[TESTO 770-2](#) [0590 7702](#) [34194A](#) [KEW2433R](#) [KEW8112](#) [FLUKE 772](#) [380976-K](#) [MA3110](#) [MA440](#) [MA443](#) [MA445](#) [FLUKE-374 FC](#)
[TA74](#) [AMP-320](#) [CM55](#) [CM46](#) [I200](#) [ACD-6 PRO](#) [FLUKE-1630-2FC](#) [I410](#) [CM44](#) [CM42](#) [FLK-A3000 FC](#) [FLUKE-376 FC](#) [ACD-14-PRO](#)
[MA610](#) [F201](#) [F205](#) [MA193 \(250 MM\)](#) [DIGIFLEX 4000A 350MM](#)