

# MPC7448 Hardware Specifications

## Addendum for the

### MC7448Txxnnnmxx Series

This document describes part-number-specific changes to recommended operating conditions and revised electrical specifications, as applicable, from those described in the general *MPC7448 RISC Microprocessor Hardware Specifications*. The MPC7448 is a PowerPC™ microprocessor built on Power Architecture™ technology.

Specifications provided in this document supersede those in the *MPC7448 RISC Microprocessor Hardware Specifications*, Rev. 3 or later, for the part numbers listed in Table A only. Specifications not addressed herein are unchanged. Because this document is frequently updated, refer to the website on the back page of this document or to your Freescale sales office for the latest version.

Note that headings and table numbers in this document are not consecutively numbered. They are intended to correspond to the heading or table affected in the general hardware specification.

Part numbers addressed in this document are listed in Table A.

*Freescale Part Numbers Affected:*

*MC7448THX1000Nx*  
*MC7448THX1267Nx*  
*MC7448THX1400Nx*  
*MC7448THX1700LD*  
*PPC7448THX1000Nx*  
*PPC7448THX1267Nx*  
*PPC7448THX1400Nx*

**Table A. Part Numbers Addressed by This Data Sheet**

Freescale Part Number	Operating Conditions			Significant Differences from Hardware Specifications
	CPU Frequency (MHz)	V <sub>DD</sub>	T <sub>j</sub> (°C)	
MC7448THX1000Nx	1000	1.0 V ± 50 mV	-40 to 105	Modified core frequency and voltage to reduce power consumption, extended operating temperature.
MC7448THX1267NC	1267	1.1 V ± 50 mV		
MC7448THX1267ND	1267	1.05 V ± 50 mV		
MC7448THX1400Nx	1400	1.15 V ± 50 mV <sup>2</sup>		
MC7448THX1700LD	1700	1.3 V +20/-50 mV		
PPC7448THX1000Nx <sup>1</sup>	1000	1.0 V ± 50 mV		
PPC7448THX1267NC <sup>1</sup>	1267	1.1 V ± 50 mV		
PPC7448THX1267ND <sup>1</sup>	1267	1.05 V ± 50 mV		
PPC7448THX1400Nx <sup>1</sup>	1400	1.15 V ± 50 mV <sup>2</sup>		

**Note:**

1. The P prefix in a Freescale part number designates a “Pilot Production Prototype” as defined by Freescale SOP 3-13. These parts have only preliminary reliability and characterization data. Before pilot production prototypes can be shipped, written authorization from the customer must be on file in the applicable sales office acknowledging the qualification status and the fact that product changes may still occur as pilot production prototypes are shipped.
- 2 See Section 5.1, “DC Electrical Characteristics,” for information regarding V<sub>DD</sub> specifications for 1400 MHz device.

## 4 General Parameters

Core power supply	1.3 V	(1700L MHz revision level D devices)
	1.15 V	(1400N MHz devices)
	1.1 V	(1267N MHz revision level C devices)
	1.05 V	(1267N MHz revision level D devices)
	1.0 V	(1000N MHz devices)

**Note:** See Section 5.1, “DC Electrical Characteristics,” for information regarding V<sub>DD</sub> specifications for 1400 MHz device.

## 5.1 DC Electrical Characteristics

Table 4 provides the recommended operating conditions for the MPC7448 part numbers described here.

**NOTE**

Table 4 describes the nominal operating conditions of the device. For information on the operation of the device at supported derated core voltage conditions, see Section 5.3, “Voltage and Frequency Derating.”

**Table 4. Recommended Operating Conditions<sup>1</sup>**

Characteristic	Symbol	Recommended Value					Unit	Notes
		1000N MHz	1267N MHz <sup>3</sup> Revision Level C	1267N MHz <sup>3</sup> Revision Level D	1400N MHz <sup>3</sup>	1700L MHz		
Core supply voltage	V <sub>DD</sub>	1.0 V ± 50 mV	1.1 V ± 50 mV	1.05 V ± 50 mV	1.15 V ± 50 mV	1.3 V +20/-50 mV	V	
PLL supply voltage	AV <sub>DD</sub>	1.0 V ± 50 mV	1.1 V ± 50 mV	1.05 V ± 50 mV	1.15 V ± 50 mV	1.3 V +20/-50 mV	V	2
Die-junction temperature	T <sub>j</sub>	-40 to 105	-40 to 105	-40 to 105	-40 to 105	-40 to 105	•C	

**Notes:**

1. These are the recommended and tested operating conditions. Some speed grades in addition support voltage derating; see Section 5.3, “Voltage and Frequency Derating.” Proper device operation outside of these conditions and those specified in Section 5.3, “Voltage and Frequency Derating,” is not guaranteed.
2. This voltage is the input to the filter discussed in Section 9.2.2, “PLL Power Supply Filtering,” in the hardware specifications and not necessarily the voltage at the AV<sub>DD</sub> pin, which may be reduced from V<sub>DD</sub> by the filter.
3. V<sub>DD</sub> and AV<sub>DD</sub> may be reduced in order to reduce power consumption if further maximum core frequency constraints are observed. See Section 5.3, “Voltage and Frequency Derating,” for specific information.

Table 7 provides the power consumption for the MPC7448 part numbers described by this document; see Section 11.1, “Part Numbers Addressed by This Specification,” for more information. The *MPC7448 RISC Microprocessor Hardware Specifications* presents guidelines on the use of these parameters for system design. For information on power consumption when dynamic frequency switching is enabled, see Section 9.8.5, “Dynamic Frequency Switching (DFS),” in the hardware specifications.

The power consumptions provided in Table 7 represent the power consumption of each speed grade when operated at the rated maximum core frequency (see Table 8). Freescale sorts devices by power as well as by core frequency, and power limits for each speed grade are independent of each other. Each device is tested at its maximum core frequency only. (Note that Deep Sleep Mode power consumption is independent of clock frequency.) Operating a device at a frequency lower than its rated maximum is fully supported provided the clock frequencies are within the specifications given in Table 8, and a device operated below its rated maximum will have lower power consumption. However, inferences should not be made about a device’s power consumption based on the power specifications of another (lower) speed grade. For example, a 1400 MHz device operated at 1267 MHz will not exhibit the same power consumption as a 1267 MHz device operated at 1267 MHz.

**NOTE**

The power consumption information in this table applies when the device operates at the nominal core voltage indicated in Table 4. For power consumption at derated core voltage conditions, see Section 5.3, “Voltage and Frequency Derating.”

**Table 7. Power Consumption for MPC7448 at Maximum Rated Frequency**

	Die Junction (T <sub>j</sub> ) (°C)	Maximum Processor Core Frequency (Speed Grade, MHz)				Unit	Notes
		1000N	1267N <sup>7</sup>	1400N	1700L		
<b>Full-Power Mode</b>							
<b>Typical</b>	65	9.5	8.4	11.0	21.0	W	1, 2
<b>Thermal</b>	105	12.0	10.3	13.7	25.6	W	1, 5
<b>Maximum</b>	105	13.9	12.0	15.9	29.8	W	1, 3
<b>Nap Mode</b>							
<b>Typical</b>	105	6.5	6.5	8.3	13.0	W	1, 6
<b>Sleep Mode</b>							
<b>Typical</b>	105	6.3	6.3	8.0	12.5	W	1, 6
<b>Deep Sleep Mode (PLL Disabled)</b>							
<b>Typical</b>	105	6.0	6.0	7.7	12.0	W	1, 6

**Notes:**

1. These values specify the power consumption for the core power supply (V<sub>DD</sub>) at nominal voltage and apply to all valid processor bus frequencies and configurations. The values do not include I/O supply power (OV<sub>DD</sub>) or PLL supply power (AV<sub>DD</sub>). OV<sub>DD</sub> power is system dependent but is typically < 5% of V<sub>DD</sub> power. Worst case power consumption for AV<sub>DD</sub> < 13 mW.
2. Typical nominal power consumption is an average value measured at the nominal recommended V<sub>DD</sub> (see Table 4) and 65°C while running the Dhrystone 2.1 benchmark and achieving 2.3 Dhrystone MIPs/MHz. This parameter is not 100% tested but periodically sampled.
3. Maximum power consumption is the average measured at nominal V<sub>DD</sub> and maximum operating junction temperature (see Table 4) while running an entirely cache-resident, contrived sequence of instructions to keep all the execution units maximally busy.
4. Doze mode is not a user-definable state; it is an intermediate state between full-power and either nap or sleep mode. As a result, power consumption for this mode is not tested.
5. Typical thermal power consumption is an average value measured at the nominal recommended V<sub>DD</sub> (see Table 4) and 105°C while running the Dhrystone 2.1 benchmark and achieving 2.3 Dhrystone MIPs/MHz. This parameter is not 100% tested but periodically sampled.
6. Typical power consumption for these modes is measured at the nominal recommended V<sub>DD</sub> (see Table 4) and 105°C in the mode described. This parameter is not 100% tested but is periodically sampled.
7. Power consumption for the 1267 MHz device is intentionally constrained via testing and sorting to assure low power consumption for this device.

## 5.2.1 Clock AC Specifications

Table 8 provides the clock AC timing specifications for the MPC7448 part numbers discussed here.

**NOTE**

The core frequency information in this table applies when the device operates at the nominal core voltage indicated in Table 4. For core frequency specifications at derated core voltage conditions, see Section 5.3, “Voltage and Frequency Derating.”

**Table 8. Clock AC Timing Specifications**

At recommended operating conditions. See Table 4.

Characteristic	Symbol	Maximum Processor Core Frequency (MHz)								Unit	Notes
		1000N		1267N		1400N		1700L			
		Min	Max	Min	Max	Min	Max	Min	Max		
Processor frequency DFS mode disabled	$f_{core}$	500	1000	500	1267	500	1400	600	1700	MHz	1, 8, 9
Processor frequency DFS mode enabled	$f_{core-DFS}$	250	500	250	633	250	700	300	850	MHz	10
VCO frequency	$f_{VCO}$	500	1000	500	1267	500	1400	600	1700	MHz	1, 9

**Notes:**

- Caution:** The SYSCLK frequency and PLL\_CFG[0:5] settings must be chosen such that the resulting SYSCLK (bus) frequency, processor core frequency, and PLL (VCO) frequency do not exceed their respective maximum or minimum operating frequencies. Refer to the PLL\_CFG[0:5] signal description in Section 9.1.1, “PLL Configuration,” in the hardware specifications for valid PLL\_CFG[0:5] settings.
- This reflects the maximum and minimum core frequencies when the dynamic frequency switching feature (DFS) is disabled.  $f_{core\_DFS}$  provides the maximum and minimum core frequencies in a DFS mode.
- Caution:** These values specify the maximum processor core and VCO frequencies when the device is operated at the nominal core voltage. If operating the device at the derated core voltage, the processor core and VCO frequencies must be reduced. See Section 5.3, “Voltage and Frequency Derating,” for more information.
- This specification supports the Dynamic Frequency Switching (DFS) feature and is applicable only when one of the DFS modes (divide-by-2 or divide-by-4) is enabled. When DFS is disabled, the core frequency must conform to the maximum and minimum frequencies stated for  $f_{core}$ .

### 5.3 Voltage and Frequency Derating

To reduce power consumption, these devices support voltage and frequency derating in which the core voltage ( $V_{DD}$ ) may be reduced if the reduced maximum processor core frequency requirements are observed. The supported derated core voltage, resulting maximum processor core frequency ( $f_{core}$ ), and power consumption are provided in Table 11. Only those parameters in Table 11 are affected; all other parameter specifications are unaffected.

**Table 11. Supported Voltage, Core Frequency, and Power Consumption Derating**

Maximum Rated Core Frequency (Device Marking)	Supported Derated Core Voltage ( $V_{DD}$ )	Maximum Derated Core Frequency ( $f_{core}$ )	Full-Power Mode Power Consumption		
			Typical	Thermal	Maximum
1000N	N/A				
1267N	1.0 V ± 50 mV	1000 MHz	6.0 W	7.3 W	8.5 W
1400N	1.0 V ± 50 mV	1000 MHz	8.0 W	9.9 W	11.5 W
1700L	N/A				

## 9.2 Power Supply Design and Sequencing

The power supply design and sequencing requirements of the devices described here are identical to those described in the *MPC7448 RISC Microprocessor Hardware Specifications*.

# 11 Part Numbering and Marking

## 11.1 Part Numbers Addressed by This Specification

Table 17 provides the ordering information for the MPC7448 parts described in this document.

**Table 17. Part Marking Nomenclature**


<b>xx</b>	<b>7448</b>	<b>T</b>	<b>xx</b>	<b>nnnn</b>	<b>m</b>	<b>x</b>
<b>Product Code</b>	<b>Part Identifier</b>	<b>Specification Modifier</b>	<b>Package</b>	<b>Processor Frequency</b>	<b>Application Modifier</b>	<b>Revision Level</b>
MC PPC <sup>1</sup>	7448	T = Extended Temperature Device	HX = HCTE BGA	1000	N: 1.0 V ± 50 mV – 40 to 105 °C	C: 2.1: PVR = 0x8004_0201 D: 2.2: PVR = 0x8004_0202
				1267 Revision C only	N: 1.1 V ± 50 mV – 40 to 105 °C	
				1267 Revision D only	N: 1.05 V ± 50 mV – 40 to 105 °C	
				1400	N: 1.15 V ± 50 mV – 40 to 105 °C	
MC				1700	L: 1.3 V +20/-50 mV – 40 to 105 °C	D:2.2: PVR = 0x8004_0202

**Notes:**

1. The P prefix in a Freescale part number designates a “Pilot Production Prototype” as defined by Freescale SOP 3-13. These parts have only preliminary reliability and characterization data. Before pilot production prototypes can be shipped, written authorization from the customer must be on file in the applicable sales office acknowledging the qualification status and the fact that product changes may still occur as pilot production prototypes are shipped.

## 11.3 Part Marking

Parts are marked as the example shown in Figure 23.



BGA

**Notes:**

- AWLYYWW is the test code, where YYWW is the date code (YY = year, WW = work week)
- MMMMMM is the M00 (mask) number.
- YWWLAZ is the assembly traceability code.

**Figure 23. Part Marking for BGA Device**

## Document Revision History

Table B provides a revision history for this part number specification.

**Table B. Document Revision History**

Revision	Date	Substantive Change(s)
2	04/2007	<p>Added 1700LD device information.</p> <p>On first page changed title part number from being N application modifier specific (MC7448TxxnnnnNx) to generic MC7448Txxnnnnmx.</p> <p>On first page under Freescale Part Numbers Affected added MC7448THX1700LD.</p> <p>Table A: Added a 1700L MHz revision D row.</p> <p>Section 4, "General Parameters": Added 1700L MHz revision level D information and added N application modifier information to the 1000, 1267, and 1400 devices.</p> <p>Table 4, Table 7, and Table 8: Added 1700L columns.</p> <p>Table 4, Table 7, Table 8, and Table 11: Added added N application modifier information to the 1000, 1267, and 1400 column headings.</p> <p>Table 11: Added 1700L row.</p> <p>Table 17: Changed 'N' application modifier at top of table to generic 'm'. Added 1700L information for revision level D.</p> <p>Figure 23: Updated part marking replacing 'N' application modifier with 'm'.</p>
1	10/2006	<p>Added revision level D device information.</p> <p>On first page under Freescale Part Numbers Affected added PPC7448THX1000Nx, PPC7448THX1267Nx, and PPC7448THX1400Nx.</p> <p>Table A and list on first page: x stands for C or D revision level.</p> <p>Table A: Added 1267 MHz revision D row and 4 PPC part number rows.</p> <p>Section 4, "General Parameters": Added 1267 MHz revision level D information.</p> <p>Table 4: Added 1267 MHz revision D only column.</p> <p>Table 17: Added PVR and 1267 information for revision level D, added PPC product code, and footnote 1.</p>
0	6/2006	Initial release.

## How to Reach Us:

### Home Page:

[www.freescale.com](http://www.freescale.com)

### email:

[support@freescale.com](mailto:support@freescale.com)

### USA/Europe or Locations Not Listed:

Freescale Semiconductor  
 Technical Information Center, CH370  
 1300 N. Alma School Road  
 Chandler, Arizona 85224  
 1-800-521-6274  
 480-768-2130  
[support@freescale.com](mailto:support@freescale.com)

### Europe, Middle East, and Africa:

Freescale Halbleiter Deutschland GmbH  
 Technical Information Center  
 Schatzbogen 7  
 81829 Muenchen, Germany  
 +44 1296 380 456 (English)  
 +46 8 52200080 (English)  
 +49 89 92103 559 (German)  
 +33 1 69 35 48 48 (French)  
[support@freescale.com](mailto:support@freescale.com)

### Japan:

Freescale Semiconductor Japan Ltd.  
 Headquarters  
 ARCO Tower 15F  
 1-8-1, Shimo-Meguro, Meguro-ku  
 Tokyo 153-0064, Japan  
 0120 191014  
 +81 3 5437 9125  
[support.japan@freescale.com](mailto:support.japan@freescale.com)

### Asia/Pacific:

Freescale Semiconductor Hong Kong Ltd.  
 Technical Information Center  
 2 Dai King Street  
 Tai Po Industrial Estate,  
 Tai Po, N.T., Hong Kong  
 +800 2666 8080  
[support.asia@freescale.com](mailto:support.asia@freescale.com)

### For Literature Requests Only:

Freescale Semiconductor  
 Literature Distribution Center  
 P.O. Box 5405  
 Denver, Colorado 80217  
 1-800-441-2447  
 303-675-2140  
 Fax: 303-675-2150  
[LDCForFreescaleSemiconductor@hibbertgroup.com](mailto:LDCForFreescaleSemiconductor@hibbertgroup.com)

Information in this document is provided solely to enable system and software implementers to use Freescale Semiconductor products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document.

Freescale Semiconductor reserves the right to make changes without further notice to any products herein. Freescale Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Freescale Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Freescale Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Freescale Semiconductor does not convey any license under its patent rights nor the rights of others. Freescale Semiconductor products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Freescale Semiconductor product could create a situation where personal injury or death may occur. Should Buyer purchase or use Freescale Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold Freescale Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Freescale Semiconductor was negligent regarding the design or manufacture of the part.

Freescale™ and the Freescale logo are trademarks of Freescale Semiconductor, Inc. The Power Architecture and Power.org word marks and the Power and Power.org logos and related marks are trademarks and service marks licensed by Power.org. The described product is a PowerPC microprocessor. The PowerPC name is a trademark of IBM Corp. and is used under license. All other product or service names are the property of their respective owners.

© Freescale Semiconductor, Inc., 2007.

Document Number: MPC7448ECS02AD  
 Rev. 2  
 04/2007





## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Microprocessors - MPU category](#):*

*Click to view products by [Freescale manufacturer](#):*

Other Similar products are found below :

[MC68302EH20C](#) [MC7457RX1000LC](#) [MC7457RX1267LC](#) [MC7457VG1267LC](#) [A2C00010998 A](#) [A2C52004004](#) [R5F117BCGNA#20](#)  
[R5F52106BDLA#U0](#) [ADJ3400IAA5DOE](#) [MPC8245TVV266D](#) [MPC8245TZU300D](#) [MPC8260ACVVMHBB](#) [MPC8323ECVRAFDCA](#)  
[MPC8536ECVJAVLA](#) [BOXNUC5PGYH0AJ](#) [20-668-0024](#) [P1010NSN5DFB](#) [P2010NSN2MHC](#) [P2020NXE2HHC](#) [P5020NSE7QMB](#)  
[P5020NSE7TNB](#) [P5020NSE7VNB](#) [LS1020ASN7KQB](#) [LS1020AXN7HNB](#) [LS1020AXN7KQB](#) [A2C00010729 A](#) [A2C00039344](#)  
[T1022NSE7MQB](#) [T1022NXN7PQB](#) [T1023NSE7MQA](#) [T1024NXE7PQA](#) [T1042NSE7MQB](#) [T1042NSN7MQB](#) [T1042NXN7WQB](#)  
[T2080NSE8TTB](#) [T2080NSN8PTB](#) [T2080NXE8TTB](#) [T2081NXN8TTB](#) [R5F101AFASP#V0](#) [MC68302CEH20C](#) [MPC8260ACVVMIBB](#)  
[MPC8280CZUUPEA](#) [MPC8313ECVRAFFC](#) [MPC8313ECVRAGDC](#) [MPC8313EVRADDC](#) [MPC8313EVRAFFC](#) [MPC8313VRADDC](#)  
[MPC8314CVRAGDA](#) [MPC8314VRAGDA](#) [MPC8315VRAGDA](#)