

(1.27 mm) .050"

FTS SERIES

MICRO LOW-PROFILE TERMINAL STRIPS

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?FTS

HI-TEMP

- Insulator Material:** Black Liquid Crystal Polymer
- Terminal Material:** Phosphor Bronze
- Operating Temp Range:** -55 °C to +125 °C
- Plating:** Sn or Au over 50 μ" (1.27 μm) Ni
- Current Rating:** 3.4 A per pin (2 pins powered)
- RoHS Compliant:** Yes
- Lead-Free Solderable:** Yes
- SMT Lead Coplanarity:** .004" (0.10 mm) max

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality




ALSO AVAILABLE (MOQ Required)

- Alignment pin

Board Mates:
CLP, FLE

Cable Mates:
FFSD

OPTIONS



Mates with socket strips or IDC cable

Surface mount or through-hole

Micro pitch .050" x .050" (1.27 mm x 1.27 mm)

Low-profile (1.27 mm) .050"

Shrouded and alignment pin options available

Impedance matched for high-speed applications

FTS	1	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	ROW OPTION	OTHER OPTION									
		02 thru 50 (except -S & -SA option = 05 thru 46)	<p>-01 = .120" (3.05 mm) Post (Mates with FFSD)</p> <p>-02 = .075" (1.91 mm) Post (Mates with FLE)</p> <p>-03 = .065" (1.65 mm) Post (Mates with CLP)</p> <p>-04 = .150" (3.81 mm) Post</p>	<p>-F = Gold flash on post, Matte Tin on tail</p> <p>-L = 10 μ" (0.25 μm) Gold on post, Matte Tin on tail</p>	<p>-D = Double Through-hole</p> <p>-DV = Double Vertical SMT</p> <p>-S = Single Through-hole</p> <p>-SV = Single Vertical SMT</p>	<p>(-D & -DV only)</p> <p>-SA = End Shroud with Alignment Pin (05 thru 46 positions. Style -02 & -03 only)</p> <p>-S = End Shroud (05 thru 46 positions. Style -02 & -03 only)</p> <p>-P = Pick & Place Pad (04 positions minimum)</p> <p>-TR = Tape & Reel (-DV only) (Required callout for positions 2 thru 4)</p>									
			<table border="1"> <thead> <tr> <th>LEAD STYLE</th> <th>A</th> </tr> </thead> <tbody> <tr> <td>-01</td> <td>(3.05) .120</td> </tr> <tr> <td>-02</td> <td>(1.91) .075</td> </tr> <tr> <td>-03</td> <td>(1.65) .065</td> </tr> <tr> <td>-04</td> <td>(3.81) .150</td> </tr> </tbody> </table>	LEAD STYLE	A	-01	(3.05) .120	-02	(1.91) .075	-03	(1.65) .065	-04	(3.81) .150		
LEAD STYLE	A														
-01	(3.05) .120														
-02	(1.91) .075														
-03	(1.65) .065														
-04	(3.81) .150														

Note: Some lengths, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Samtec](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65781-047](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#) [67095-007LF](#)