



Description

<p>Product Summary</p> <ul style="list-style-type: none"> • VDS 20V • ID 3.0A • RDS(ON)(at VGS=4.5V) < 64 mohm • RDS(ON)(at VGS=2.5V) < 86 mohm 	<p>General Description</p> <ul style="list-style-type: none"> • Trench Power LV MOSFET technology • High Power and current handing capability <p>Applications</p> <ul style="list-style-type: none"> • PWM application • Load switch
--	--

Package



SOT-23



Schematic Diagram

Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-source Voltage		VDS	20	V
Gate-source Voltage		VGS	± 12	V
Drain Current	TA=25°C @ Steady State	ID	3.0	A
	TA=70°C @ Steady State		2.0	
Pulsed Drain Current A		IDM	10.8	A
Total Power Dissipation @ TA=25°C		PD	0.69	W
Thermal Resistance Junction-to-Ambient @ Steady State B		R θ J A	172	°C/W
Junction and Storage Temperature Range		TJ ,TSTG	-55~+150	°C

Electrical Characteristics ($T_J=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BVDSS	VGS= 0V, ID=250 μ A	20			V
Zero Gate Voltage Drain Current	IDSS	VDS=20V, VGS=0V			1	μ A
Gate-Body Leakage Current	IGSS	VGS= \pm 12V, VDS=0V			\pm 100	nA
Gate Threshold Voltage	VGS(th)	VDS= VGS, ID=250 μ A	0.45	0.70	1.0	V
Static Drain-Source On-Resistance	RDS(ON)	VGS= 4.5V, ID=2.5A		52	64	m Ω
		VGS= 2.5V, ID=2.0A		70	86	
Diode Forward Voltage	VSD	IS=2.5A, VGS=0V			1.2	V
Maximum Body-Diode Continuous Current	IS				2.5	A
Dynamic Parameters						
Input Capacitance	Ciss	VDS=10V, VGS=0V, f=1MHZ		192		pF
Output Capacitance	Coss			23		
Reverse Transfer Capacitance	Crss			26		
Switching Parameters						
Total Gate Charge	Qg	VGS=4.5V, VDS=10V, ID=2.5A		3.3		nC
Gate Source Charge	Qgs			0.89		
Gate Drain Charge	Qgd			0.75		
Turn-on Delay Time	tD(on)	VGS=4.5V, VDD=10V, RL=1.5 Ω , RGEN=3 Ω		7.9		ns
Turn-on Rise Time	tr			54		
Turn-off Delay Time	tD(off)			17		
Turn-off Fall Time	tf			50		

A. Pulse Test: Pulse Width \leq 300 μ s, Duty cycle \leq 2%.

B. Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch.

Typical Performance Characteristics




Figure1. Output Characteristics




Figure2. Transfer Characteristics




Figure3. Capacitance Characteristics




Figure4. Gate Charge




Figure5. Drain-Source on Resistance




Figure6. Drain-Source on Resistance




Figure7. Safe Operation Area





Figure8. Switching wave

Package Information.

➤ SOT23-3(小)



符号	毫米		英寸	
	最小	最大	最小	最大
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP.		0.037 TYP.	
e1	1.800	2.000	0.071	0.079
L	0.550 REF.		0.022 REF.	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFET](#) category:

Click to view products by [Fuman](#) manufacturer:

Other Similar products are found below :

[IRFD120](#) [JANTX2N5237](#) [2SK2267\(Q\)](#) [BUK455-60A/B](#) [TK100A10N1,S4X\(S](#) [MIC4420CM-TR](#) [VN1206L](#) [NDP4060](#) [SI4482DY](#)
[IRS2092STRPBF-EL](#) [IPS70R2K0CEAKMA1](#) [TK31J60W5,S1VQ\(O](#) [TK31J60W,S1VQ\(O](#) [TK16J60W,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#)
[DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE2384](#) [DMC2700UDMQ-7](#) [DMN2080UCB4-7](#)
[DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)
[STF5N65M6](#) [IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [IPS60R360PFD7SAKMA1](#)
[DMN2990UFB-7B](#) [SSM3K35CT,L3F](#) [IPLK60R1K0PFD7ATMA1](#) [2N7002W-G](#) [MCAC30N06Y-TP](#) [IPWS65R035CFD7AXKSA1](#)
[MCQ7328-TP](#) [SSM3J143TU,LXHF](#) [DMN12M3UCA6-7](#) [PJMF280N65E1_T0_00201](#) [PJMF380N65E1_T0_00201](#)
[PJMF280N60E1_T0_00201](#) [PJMF600N65E1_T0_00201](#) [PJMF900N65E1_T0_00201](#)