


Customer (客戶) : 立創



Part No. (客戶料號) : _____



承認書

SPECIFICATION FOR APPROVAL



Description (說明) : Metal Glaze Film Resistors (金屬釉皮膜電阻器)

Futaba Series (雙羽系列) : RM series (Halogen-Free)

Futaba Part No. (雙羽料號) : see RECOGNITION 2.

Part No. (客戶料號) : _____

台灣雙羽電機股份有限公司
雙羽電子(深圳)有限公司
雙羽電子(蘇州)有限公司

FUTABA ELECTRIC CO., LTD.

SHUANGYU ELECTRONICS (SHEN ZHEN) CO., LTD.

FUTABA ELECTRIC (SUZHOU) CO., LTD.

9, LANE 240, TAMING ROAD. CHUTUNG, HSINCHU. TAIWAN

TEL : (03) 5966636 FAX : (03) 5943635

E-mail : rita@futaba.com.tw

貴公司承認印

Approval Signatures

Customer(客戶)	立創	REV	S1-A(V1194)
Request for your Approval (<input checked="" type="checkbox"/> New <input type="checkbox"/> Engineering Change) (承認事由)		Date (日期)	Aug.28.2023
		(<input checked="" type="checkbox"/> 新料件 <input type="checkbox"/> 工程變更)	

RECOGNITION

序言

We are indebted to you for your examination of our products and are pleased to present our insulated, fixed metal glaze resistors.

(在此很榮幸能向貴公司介紹本公司的產品：固定型金屬釉皮膜電阻器)

The fixed metal glaze resistor is a medium power component specifically designed for applications where a highly reliability is required.

(固定型金屬釉皮膜電阻器是一中功率型的電阻元件，本元件是針對高信賴度電路應用要求所設計的電阻元件)

Specification(說明)：

1.Kind of Resistor： Fixed Metal Glaze Film Resistor **RM series.**

(1. 電阻類型： 固定型金屬釉皮膜電阻器 **RM** 系列)

2.Type, Rated Power, Resistance & Tolerance：

(2. 種類，額定功率，阻值，精密度)

Code No. (客戶料號)	Rated Power (額定功率)	Resistance (阻值)	Tolerance (精密度)	Futaba Part No. (雙羽料號)	PACKIND (包裝)	Remarks (備註)
	1/2W	4MΩ	±5%	RMU12J4004A520NL	A52(Ammo)	RoHS
	1/2W	1MΩ	±1%	RMU12F1004A520NL	A52(Ammo)	RoHS
	1/2W	2MΩ	±1%	RMU12F2004A520NL	A52(Ammo)	RoHS
	1/2W	10KΩ	±1%	RMU12F1002A520NL	A52(Ammo)	RoHS
	S1W	33KΩ	±1%	RMS01F3303A520NL	A52(Ammo)	RoHS
	S1W	10KΩ	±1%	RMS01F1002A520NL	A52(Ammo)	RoHS
	S1W	2MΩ	±1%	RMS01F2004A520NL	A52(Ammo)	RoHS

3. Resistance Value and Voltage： see Table 1.

(3. 阻值與額定電壓：參閱表格1)

4. Wattage of Ambient Temperature： see Fig 1.

(4. 常溫下的額定功率：參閱圖1)

5. Dimensions： see Fig 5, and table 7,

(5. 電阻尺寸：參閱圖5,和表格7,)

6. Coating： paint, insulated, flameproof

(6. 塗裝：不燃性,絕緣塗料)

Additional(加註)

We appreciate your wish to entrust us with further business and we are confident that the excellent quality of the resistor dispatched will prove a strong inducement in this direction.

(非常感激敝司可能有機會對貴公司提供服務，相信敝司堅持的品質一定能滿足貴公司嚴格的要求)

Draftsman (初稿)	Authorized By (審核)	SHUANGYU ELECTRONICS (SHEN ZHEN) CO., LTD. 雙羽電子(深圳)有限公司
江永娣	董青青	

Product Specification (產品型別) : RM series		REV	S1-A(V1194)				
Items (項次)	Contents (內容)						
1. Application (適用範圍)	This specification covers Fixed Metal Glaze Film Resistors ; RM type. (本規範適用於固定型金屬釉皮膜電阻,型別為 RM)						
2. Type Designation (型別代碼)	Types are designated as follows (型別代碼說明如下): Example						
	RM	U	1/2	J	4004	A520	NL
	型名	品名	額定功率	誤差值	電阻值	二次加工	端子線
	Type	Size	Rated Power	Tolerance	Resistance	Forming	Wire
	RM: 金屬釉 皮膜電 阻器	U:Standard S:Small	12:1/2W 01:1W	J:±5% F:±1%	4004=4MΩ	Taping:編帶 A520=A52	(electric plated) NL:電鍍線

Product Specification (產品型別) : **RM series**

REV

S1-A(V1194)

Items(項次)

Contents(內容)

3.Rating


1) Ratings
(額定值)Ratings are shown at table 1. Ratings
(電阻的使用額定值是規定於表-1)

Table 1. Ratings(表-1 額定值)

Items(項次)	Contents(內容)
Type Size(型別品名)	RM
Rated wattage(額定功率)	1/2W、S1W
Maximum operational voltage (最高正常使用電壓)	\sqrt{PR} (上限最高電壓 3500V)
Dielectric withstanding voltage (塗裝絕緣電壓)	700V
Rated ambient temperature (額定環境溫度)	70 °C
Operating temperature range (使用環境的溫度範圍)	(see Fig.1 derating curve)
Resistance tolerance (電阻值的精密度)	J(±5%) F(±F%)

* Rated wattage is the maximum continuous power applicable at ambient temperature from - 55°C~70°C(額定功率的定義為當使用環境溫度範圍在 - 55°C~70°C時，電阻在連續使用的條件下可承受的最高功率)

(see Fig.1 derating curve)



Product Specification (產品型別品名) : RM series	REV	S1-A(V1194)
---	------------	--------------------

Items (項次)	Contents (內容)
------------	---------------

2).Rated voltage (額定電壓)

Rated voltage is the D.C voltage at ambient temperature from -55°C to 70°C.
 Rated voltage shall be determined from the following formula.
 (額定電壓的定義為：當使用環境溫度範圍在-55°C to 70 °C時,電阻可承受的最高直流電壓.其計算公式如下：)
 If Rated voltage is over maximum operational voltage, then rated voltage is equal to maximum operational voltage on table 1. (當根據下列公式計算出的額定電壓高於表 1 的最高正常使用電壓時, 則額定電壓將以 表-1 的最高正常使用電壓為準)

$$V = \sqrt{P(W) \times R(\Omega)}$$

Rated voltage (額定電壓) rated wattage (額定功率) nominal resistance (額定電阻值)

4. Nominal resistance (額定阻值)

Nominal resistance are calculated by the following basic values multiplied by 10⁻¹, 10⁰, 10¹, 10², 10³, 10⁴, 10⁵(額定阻值為將表-2 的基準值乘以右列倍數)

Table 2. (表-2)

		basic value (基準值)											
E - 96	1.00	1.21	1.47	1.78	2.15	2.61	3.16	3.83	4.64	5.62	6.81	8.25	
	1.02	1.24	1.50	1.82	2.21	2.67	3.24	3.92	4.75	5.76	6.98	8.45	
	1.05	1.27	1.54	1.87	2.26	2.74	3.32	4.02	4.87	5.90	7.15	8.66	
	1.07	1.30	1.58	1.91	2.32	2.80	3.40	4.12	4.99	6.04	7.32	8.87	
	1.10	1.33	1.62	1.96	2.37	2.87	3.48	4.22	5.11	6.19	7.50	9.09	
	1.13	1.37	1.65	2.00	2.43	2.94	3.57	4.32	5.23	6.34	7.68	9.31	
	1.15	1.40	1.69	2.05	2.49	3.01	3.65	4.42	5.36	6.49	7.87	9.53	
	1.18	1.43	1.74	2.10	2.55	3.09	3.74	4.53	5.49	6.65	8.06	9.76	

		basic value(基準值)				
E - 24	1.0	1.1	1.2	1.3	1.5	
	1.6	1.8	2.0	2.2	2.4	
	2.7	3.0	3.3	3.6	3.9	
	4.3	4.7	5.1	5.6	6.2	
	6.8	7.5	8.2	9.1		

5.Dimensions and Constructions (尺寸/結構)








Fig.2. (圖-2)

Product Specification (產品型別) : RM series		REV	S1-A(V1194)
tems(項次)	Contents(內容)		
1)Dimensions (尺寸)	Table 3. (表-3) (mm, 公厘)		
	Rated power (額定功率)	Body length (長度)L	Body dia. (直徑)D φ
	1/2W、S1W	9.0 ±0.5	3.3±0.5
2)Construction (結構圖)	<p>Painting method (塗裝規範)</p> <p>Welding point, terminal and lead wire, is permissible to be exposed without the outer coated cover. The extent should be within 1/2 of the arc angle. (塗裝時電阻的焊點, 端面和端子線可允許不被塗料覆蓋(max1.5mm). 端面部份被塗料覆蓋的限度值為 1/2D)</p>  <p style="text-align: center;">Fig. 3.</p> 		
No.	Parts(組成)	Material(材料)	
1	lead wire (端子線)	tin plated copper wire (鍍錫銅線)	
2	contact of cap and lead wire (鐵帽與端線的連接點)	welding (高壓放電點焊接)	
3	ceramic base (陶瓷棒)	aluminum ceramic of the kind (氧化鋁)	
4	Cap (鐵帽)	tin plated iron base (鍍錫鐵片)	
5	helical cutting groove (螺旋切割線)	-- -----	
6	conductive film (導電皮膜)	metal glaze film (金屬釉皮膜)	
7	Marking (捺印)	Color Code(色環)	
8	Insulation coat (絕緣塗料)	$\leq 1/2W$: epoxy paint of the kind 絕緣環氧樹脂塗料 $\geq 1/2W$: silicon paint of the kind flame proof (worth UL94-V0) (矽樹脂塗料) (耐燃材質, 符合 UL94 V0)	

Product Specification(產品型別品名) : RM series	REV	S1-A(V1194)																																																																														
Items(項次)	Contents(內容)																																																																															
3).Marking (b) (捺印(b))	<p data-bbox="323 324 619 360">Color Code(色環表示)</p> <div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;">  <p data-bbox="392 696 488 732">(±5%)</p> </div> <div style="text-align: center;">  <p data-bbox="999 696 1094 732">(±1%)</p> </div> </div> <p data-bbox="276 779 584 815">注：色環斷線可允許≤1/3</p> <table border="1" data-bbox="368 815 1417 1839"> <thead> <tr> <th>BAND COLOR</th> <th>1ST BAND</th> <th>2ND BAND</th> <th>3RD BAND</th> <th>MULTIPLE</th> <th>TOLERANCE</th> </tr> </thead> <tbody> <tr><td>BLACK</td><td>0</td><td>0</td><td>0</td><td>1</td><td></td></tr> <tr><td>BROWN</td><td>1</td><td>1</td><td>1</td><td>10</td><td>±1%</td></tr> <tr><td>RED</td><td>2</td><td>2</td><td>2</td><td>100</td><td>±2%</td></tr> <tr><td>ORANGE</td><td>3</td><td>3</td><td>3</td><td>1000</td><td></td></tr> <tr><td>YELLOW</td><td>4</td><td>4</td><td>4</td><td>10000</td><td></td></tr> <tr><td>GREEN</td><td>5</td><td>5</td><td>5</td><td>100000</td><td>±0.5%</td></tr> <tr><td>BLUE</td><td>6</td><td>6</td><td>6</td><td>1000000</td><td>±0.25%</td></tr> <tr><td>VIOLET</td><td>7</td><td>7</td><td>7</td><td>10000000</td><td>±0.1%</td></tr> <tr><td>GREY</td><td>8</td><td>8</td><td>8</td><td></td><td>±0.05%</td></tr> <tr><td>WHITE</td><td>9</td><td>9</td><td>9</td><td></td><td></td></tr> <tr><td>GOLD</td><td></td><td></td><td></td><td>0.1</td><td>±5%</td></tr> <tr><td>SILVER</td><td></td><td></td><td></td><td>0.01</td><td>±10%</td></tr> </tbody> </table>		BAND COLOR	1ST BAND	2ND BAND	3RD BAND	MULTIPLE	TOLERANCE	BLACK	0	0	0	1		BROWN	1	1	1	10	±1%	RED	2	2	2	100	±2%	ORANGE	3	3	3	1000		YELLOW	4	4	4	10000		GREEN	5	5	5	100000	±0.5%	BLUE	6	6	6	1000000	±0.25%	VIOLET	7	7	7	10000000	±0.1%	GREY	8	8	8		±0.05%	WHITE	9	9	9			GOLD				0.1	±5%	SILVER				0.01	±10%
BAND COLOR	1ST BAND	2ND BAND	3RD BAND	MULTIPLE	TOLERANCE																																																																											
BLACK	0	0	0	1																																																																												
BROWN	1	1	1	10	±1%																																																																											
RED	2	2	2	100	±2%																																																																											
ORANGE	3	3	3	1000																																																																												
YELLOW	4	4	4	10000																																																																												
GREEN	5	5	5	100000	±0.5%																																																																											
BLUE	6	6	6	1000000	±0.25%																																																																											
VIOLET	7	7	7	10000000	±0.1%																																																																											
GREY	8	8	8		±0.05%																																																																											
WHITE	9	9	9																																																																													
GOLD				0.1	±5%																																																																											
SILVER				0.01	±10%																																																																											
4).Outlook (外觀)	There is no unusual evidence affects the characteristics of resistors with the over coat and lead wires. (電阻體和端子線外觀無明顯異狀)																																																																															
5). Safety Marking	EN 62368-1:2018 : File No : DK-121135-A1-UL																																																																															

Product Specification (產品型別品名) : RM series		REV	S1-A(V1194)	
Items (項次)	Contents (內容)			
6.Characteristics and test methods	Characteristics and test methods are shown in table 6. Characteristics. (電氣特性與對應的測試方法如表-6)			
	Table 6. Characteristics (表-6 電氣特性)			
	No.	Items (項次)	Characteristics (電氣特性)	Test methods (測試方法)
	1	Resistance value (電阻值)	class J: ($\pm 5\%$) F ($\pm 1\%$)	JIS C 5201- 1 (4.5 項) classification of applied A
	2	Temperature coefficient of resistance (溫度係數)	<1K Ω : $\pm 500\text{ppm}/^\circ\text{C}$ $\leq 100\text{K}\Omega$: $\pm 300\text{ppm}/^\circ\text{C}$ > 100K Ω : $\pm 200\text{ppm}/^\circ\text{C}$	JIS C 5201- 1 measured at room temperature and room temperature+100 $^\circ\text{C}$
	3	Short-time overload (短時間過負荷)	resistance change within $\pm(1\% + 0.05\Omega)$ (阻值變化範圍)	JIS C 5201 1 (4.13 項) (rated voltage $\times 2.5 \sim 5$ s)
	4	Endurance (under damp and load) (高溫高濕負荷壽命實驗)	resistance change within $\pm(5\% + 0.1\Omega)$ (阻值變化範圍)	JIS C -5201- 1 (4.24 項) 1)test temperature.40 $^\circ\text{C} \pm 2^\circ\text{C}$ 2) relative humidity 90% - 95% 3) duration 1,000 hours
	5	Endurance (rated load) (負荷壽命實驗)	resistance change within $\pm(5\% + 0.1\Omega)$ (阻值變化範圍)	JIS C- 5201- 1 (4.25.1 項) 1) Rated voltage test temperature70 $^\circ\text{C} \pm 3^\circ\text{C}$ 2) duration 1,000 hours
	6	Resistance to soldering heat (銲錫耐熱實驗)	resistance change within $\pm(1\% + 0.05\Omega)$ (阻值變化範圍)	JIS C 5201-1 (4.18 項) 1)temp. of solder 350 $^\circ\text{C} \pm 10^\circ\text{C}$ 2)duration of immersion 3.5 s ± 0.5 s
	7	Solder ability (可銲錫性實驗)	95% (min) coverage (覆蓋率 95%(最少))	JIS C 5201-1 (4.17 項) 1)temp. of solder 245 $^\circ\text{C} \pm 5^\circ\text{C}$ 2)duration of immersion 3 s ± 0.5 s 3)preparation not applicable
	8	Temperature cycling (溫度循環實驗)	resistance change within $\pm(1\% + 0.05\Omega)$ (阻值變化範圍)	JIS C 5201-1(4.19 項) 1) Test temp. -25 $^\circ\text{C} \sim +85^\circ\text{C}$ 2) number of 5 cycles
9	Dielectric withstanding voltage (耐電壓實驗)	Flash over, burning, insulation damage should not be observed (不產生火花, 燃燒現象)	JIS C 5201 1 (4.7 項) 1) V-Block 2) test voltage : see table 1 3) duration time 60 s	
10	Resistance to cold (耐寒實驗)	resistance change within $\pm(1\% + 0.05\Omega)$ (阻值變化範圍)	JIS C 5201-1 (4.23.4 項) 1) test temp. -25 $^\circ\text{C} \pm 3^\circ\text{C}$ 2) duration 24+4/-0 hours	

Product Specification (產品型別品名) : RM series

REV

S1-A(V1194)

Items (項次)

Contents (內容)

Table 6 . Characteristics (continued) (表-6 電氣特性 (續))

No .	Items (項次)	Characteristics (電氣特性)	Test methods (測試方法)
11	Resistance to damp heat (耐高溫高濕)	resistance change within $\pm(1 \% + 0.05 \Omega)$ (阻值變化範圍)	JIS C 5201 1 1) test temp. $40^{\circ}\text{C} \pm 2^{\circ}\text{C}$ 2) relative humidity 90 % to 95 % 3) duration 240 hours
12	Insulation resistance (絕緣電阻)	more than 1,000M Ω (超過)	JIS C 5201-1 (4.6.1 項) 1) test voltage : DC 100V 2) 額定電壓超過上 500V 時，依 500V 施加。
13	Intermittent overload (斷續過負荷)	resistance change within $\pm(5 \% + 0.1 \Omega)$ (阻值變化範圍)	JIS C 5201-1 (4.13 項) 1) applicable more than 100 Ω 2) Rated voltage $\times 3$ 3) 10,000 cycles
14	Tensile strength (拉力強度)	Neither breakage of the lead wire nor loosening of termination resistance change within $\pm(1 \% + 0.05 \Omega)$ (無端線斷裂或端面鬆脫之現象發生. 阻值變化範圍)	JIS C 5201 1 (4.16 項) 10N; 10s \pm 1s(1.02kg)
15	Bending strength (抗折力)	Neither breakage of the lead wire nor loosening of termination resistance change within $\pm(1 \% + 0.05 \Omega)$ (無端線斷裂或端面鬆脫之現象發生. 阻值變化範圍)	JIS C 5201-1 (4.16 項) 1) 360 $^{\circ}$ Round-trip ; 1.5cycle (0.45 ϕ , 0.6 ϕ) 2) 360 $^{\circ}$ Round-trip ; 3cycle (0.8 ϕ)
16	Surge withstanding voltage (脈衝)	Resistance change within $\pm 20 \%$ test circuit 	The following discharge cycle is repeated in the circuit of the left fig. 2.5 sec. ON 2.5 sec. OFF 50 cycles. test voltage (DC source) S1/4W : 3KV ; \geq 1/4W : < 100K Ω : 3KV ; 100K Ω ~ 620K Ω : 5KV ; > 620K Ω : 10KV

Product Specification(產品型別品名) : **RM series**

REV

S1-A(V1194)

Items(項次)

Contents(內容)

7.Forming

7.1Taping

(貼帶)

Dimension and form of taping are shown in Fig.5 and table 7

(貼帶的尺寸和造型分別敘述如：圖-5，表-7)





Fig.5 Taping

Table 7 (表-7)

Unit : mm

Rated Power	W	L	Dφ	P	dφ
1/2W, S1W	52±1	9.0±0.5	3.3±0.5	5 ±0.5	0.60 ±0.1

注：Taping编带为胶带，脱带后引脚会粘胶建议不要脱带加工

Product Specification (產品型別品名) : RM series	REV	S1-A(V1194)																																																				
Items(項次)	Contents (內容)																																																					
8、耐焊錫溫度曲線圖	<p data-bbox="295 280 550 369">耐焊錫溫度曲線圖</p> <div data-bbox="343 504 1300 1041" style="text-align: center;"> <p data-bbox="606 504 1021 560">台灣雙羽電機股份有限公司 耐焊錫溫度曲線圖 (Lead-Free)</p> <p data-bbox="343 560 638 604">1. 沾錫性測試: 245 +5°C / 3.5 sec. 95% 2. 耐焊錫溫度: 260°C / 5 sec</p>  <table border="1" data-bbox="343 616 1300 1041"> <caption>Temperature Profile Data (Estimated)</caption> <thead> <tr> <th>Heating Time (sec)</th> <th>Temperature (°C)</th> </tr> </thead> <tbody> <tr><td>0</td><td>30</td></tr> <tr><td>10</td><td>60</td></tr> <tr><td>20</td><td>90</td></tr> <tr><td>30</td><td>110</td></tr> <tr><td>40</td><td>125</td></tr> <tr><td>50</td><td>135</td></tr> <tr><td>60</td><td>145</td></tr> <tr><td>70</td><td>150</td></tr> <tr><td>80</td><td>155</td></tr> <tr><td>90</td><td>158</td></tr> <tr><td>100</td><td>160</td></tr> <tr><td>110</td><td>162</td></tr> <tr><td>120</td><td>165</td></tr> <tr><td>130</td><td>168</td></tr> <tr><td>140</td><td>170</td></tr> <tr><td>150</td><td>175</td></tr> <tr><td>160</td><td>180</td></tr> <tr><td>170</td><td>195</td></tr> <tr><td>180</td><td>220</td></tr> <tr><td>190</td><td>245</td></tr> <tr><td>200</td><td>260</td></tr> <tr><td>210</td><td>255</td></tr> <tr><td>220</td><td>220</td></tr> <tr><td>230</td><td>100</td></tr> <tr><td>240</td><td>50</td></tr> </tbody> </table> </div>		Heating Time (sec)	Temperature (°C)	0	30	10	60	20	90	30	110	40	125	50	135	60	145	70	150	80	155	90	158	100	160	110	162	120	165	130	168	140	170	150	175	160	180	170	195	180	220	190	245	200	260	210	255	220	220	230	100	240	50
Heating Time (sec)	Temperature (°C)																																																					
0	30																																																					
10	60																																																					
20	90																																																					
30	110																																																					
40	125																																																					
50	135																																																					
60	145																																																					
70	150																																																					
80	155																																																					
90	158																																																					
100	160																																																					
110	162																																																					
120	165																																																					
130	168																																																					
140	170																																																					
150	175																																																					
160	180																																																					
170	195																																																					
180	220																																																					
190	245																																																					
200	260																																																					
210	255																																																					
220	220																																																					
230	100																																																					
240	50																																																					

Product Specification(產品型別品名)： RM series	REV	S1-A(V1194)																									
Items(項次)	Contents (內容)																										
9.Packaging Quantity (包裝數)	<table border="1" data-bbox="352 353 1481 837"> <thead> <tr> <th data-bbox="352 353 620 454">Rated power (額定功率)</th> <th data-bbox="620 353 869 454">BOX (pcs) (盒裝(支))</th> <th data-bbox="869 353 1160 454">Inner box (內盒)</th> <th data-bbox="1160 353 1481 454">Exterior box (外箱)</th> </tr> </thead> <tbody> <tr> <td data-bbox="352 454 620 533">1/2W</td> <td data-bbox="620 454 869 533">--</td> <td data-bbox="869 454 1160 533">--</td> <td data-bbox="1160 454 1481 533">--</td> </tr> <tr> <td data-bbox="352 533 620 611">S1W</td> <td data-bbox="620 533 869 611">--</td> <td data-bbox="869 533 1160 611">--</td> <td data-bbox="1160 533 1481 611">--</td> </tr> <tr> <td data-bbox="352 611 620 689"> </td> <td data-bbox="620 611 869 689"> </td> <td data-bbox="869 611 1160 689"> </td> <td data-bbox="1160 611 1481 689"> </td> </tr> <tr> <td data-bbox="352 689 620 768"> </td> <td data-bbox="620 689 869 768"> </td> <td data-bbox="869 689 1160 768"> </td> <td data-bbox="1160 689 1481 768"> </td> </tr> <tr> <td data-bbox="352 768 620 837"> </td> <td data-bbox="620 768 869 837"> </td> <td data-bbox="869 768 1160 837"> </td> <td data-bbox="1160 768 1481 837"> </td> </tr> </tbody> </table>			Rated power (額定功率)	BOX (pcs) (盒裝(支))	Inner box (內盒)	Exterior box (外箱)	1/2W	--	--	--	S1W	--	--	--												
Rated power (額定功率)	BOX (pcs) (盒裝(支))	Inner box (內盒)	Exterior box (外箱)																								
1/2W	--	--	--																								
S1W	--	--	--																								
10.The Others (其它)	<p>The standards of the specification can be revised by the agreement between the customer and the manufacture. (在經過客戶與雙羽協商同意下，本承認書的標準可予以變更)</p>																										
11.Doubt (疑問)	<p>If any doubt about this specification occurred, it could be clarified by the discussion between the customer and the manufacture. (對本承認書之任何疑問可經由客戶與雙羽之討論解決之)</p>																										
17.Revision (修訂)	<p>This specification will be revised by the discussion and consent between the customer and the manufacture. (本承認書可經由客戶與雙羽之討論同意後予以修訂)</p>																										
18.Notes (備註)	<p>1)Storage condition.(儲存條件) It is desirable that the resistors are stored in the ambient temperature from 0 °C to 30 °C and relative humidity under 65 %. High humidity, dust, harmful gas, for example hydrogen chloride and sulfuric gas should be avoided. Please do not store the resistors for a long time, use the resistors within a year after the delivery. is recommended. (電阻體的恰當儲存條件為 0 °C 至 30 °C 同時相對溼度低於 65 %.高濕,灰塵和有害氣體,好比 鹽酸氣, 硫酸氣都需避免接觸電阻體.電阻請勿儲存過久,建議在收料 1 年內使用)</p> <p>2)Power derating (功率遞減) For the long term stability of the application, power should be derated accordingly by the power derating curve. (為了維持電阻體在使用中的長期穩定性,使用功率遞減方式需確實遵守功率遞減曲線)</p> <p>3)Resistor positioning (電阻體的位置) When the resistors are placed around other electrical parts, the minimum space between them should be kept above 5 mm. (電阻體與其它電子元件最好距離 0.5 公分)</p>																										

Product Specification(產品型別品名) : RM series	REV	S1-A(V1194)
Items(項次)	Contents(內容)	
	<p>4)Soldering (銲錫) During the process of soldering, the effect of heat caused by the soldering should be kept as little as possible. The suggested condition is under 260 °C and within 7 s. (在銲錫過程中, 爲了避免高溫影響電阻體, 所以受熱時間最好越短越好. 建議條件爲 260 °C , 7 秒鐘.)</p> <p>5)Shock to the resistors (對電阻體進行衝撞) When the resistors are subject to mechanical shock, the resistors might be broken. This is quite likely in the automatic insertion machine. Please adjust the machine accordingly. (當電阻體受到衝撞時, 電阻體可能會斷裂. 這在自動插件時可能發生. 如有類似情形發生, 請調整自動插件機的力量.) Also do not drop the resistors from a high ground. (請勿將電阻體從高處墜落)</p> <p>6)Forming (造型) During the forming process, the resistor body and the welding point should not be subjected to too much stress. (在造型時, 電阻體和焊點必須避免過大的受力.)</p> <p>7)2003-01-01 guide Lead-Free products (2003-01-01 導入無鉛產品)</p> <p>8) 2008-08-01 Guide Halogen-Free products. (2008-08-01 導入無鹵產品)</p> <p>9) 产品保质期 3 年。</p>	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Thick Film Resistors - Through Hole](#) category:

Click to view products by [Futaba](#) manufacturer:

Other Similar products are found below :

[M8340104K3300GCD03](#) [M8340105K3300GGD03](#) [M8340105K3922FGD03](#) [M8340107K2401GCD03](#) [M8340109K1002JCD03](#)

[M8340109K1003GCD03](#) [MP850-3.00-1%](#) [ARC3.11 2M J A](#) [M8340105K1003GCD03](#) [M8340105M2201GCD03](#) [M8340107M7501GCD03](#)

[M8340108K2051FCD03](#) [M8340108K7501GCD03](#) [M8340108M5100JGD03](#) [M8340109K1000GCD03](#) [MOX-GRD-001](#)

[M8340102M4701GBD04](#) [M8340102K1002GBD04](#) [M8340109K2002GGD03](#) [M8340108K2002FGD03](#) [OE1305](#) [MS-221-82R5](#) [MOX-](#)

[750231004DE](#) [MOX-4-127505J](#) [SM102034504FE](#) [MOX300002206FE](#) [MOX-400233004F](#) [MOX300001005BE](#) [SM104066008J](#) [MOX-](#)

[400262008PE](#) [MOX-400232506FE](#) [MOX-400234007FE](#) [MOX-400221006G](#) [MOX-750235006ME](#) [SM103032506FE](#) [SM202022005FE](#)

[MOX1125231002FE](#) [MOX-1-122504F](#) [MOX-400225003F](#) [MOX1125731008FE](#) [MOX-5-126002JE](#) [MS176-2.20M-1%](#) [MOX-830212453BE](#)

[TRHE01A270RJ2E](#) [TRHE01A560RJ2E](#) [TRHP01A200RF2E](#) [TRHP01A5001F2E](#) [MG715-2.40M-1%](#) [MS214-20.0K-1%](#) [MF0W4FF4702A50](#)