



Compatible
With:



i.MX



ELI121-CRW

- Industry Standard Product Version
- 12.1" XGA LCD Panel with LED Backlight
- MSRP (Qty Volume): <\$300.00
- MSRP (Qty 1): \$455.00

Features

- 4-wire Resistive Touch Screen with USB Device Interface
- Plug and Play interface to standard SBCs
- HDMI or DVI Input
- +12 Volt DC Input Power ($\pm 5\%$ tolerance)
- 400 nits Brightness (typical)
- 700:1 Contrast Ratio (typical)
- EDID Support for Automatic Screen Sizing
- -20° to $+60^{\circ}$ C operating temperature range
- Franchised Distribution Stocking
- Part Number: ELI121-CRW

Available From:



Specifications

- Screen Size (inches): 12.1 inches
- Touch Screen Type: 4-Wire Resistive
- Display Technology: a-Si TFT LCD
- Touch Screen Interface: USB Device
- Brightness (nits typ): 400
- Resolution: 1024 x 768 (XGA)
- Contrast Ratio (typ): 700 : 1
- Aspect Ratio: Wide 4:3
- Colors: 16.7M (24 bit)
- Horizontal Viewing Angle (L/R): 80/80°
- Vertical Viewing Angle (U/D): 70/70°
- Surface Finish: Anti-glare
- Touch Panel Hardness: $\geq 3H$
- Active Area (in mm) (WxH): 245.76 x 184.32
- Touch Panel Force (gF max): 80
- Response Time (ms typ): 16 tr+tf
- Backlight Life (K hrs min): 30K
- EDID for Auto Screen Sizing: Yes
- Display Interface Input Mode: HDMI / DVI
- Input VDC: 12
- Power Consumption (mA typ/max): 800/950 @ 12 VDC
- Backlight Power Consumption up to 65% of Total
- USB Power Consumption (mA typ/max): 50/100 @ 5.0 VDC
- Operating Temperature: -20° to 60° C
- Storage Temperature: -30° to 70° C
- Plug & Play with Standard SBCs: Yes
- Size: 263.00 (W) x 204.00 (H) x 22.30 (D) mm
- Weight (grams typ): 800
- RoHS Compliant: Yes

See Mechanical and Mounting Info in the User's Manual



www.TeamFDI.com
(256) 883-1240



@TeamFDI
#TeamFDI



[Youtube.com/
FDIProducts](http://Youtube.com/FDIProducts)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Display Modules](#) category:

Click to view products by [Future Designs](#) manufacturer:

Other Similar products are found below :

[P6153-PR](#) [TDP0700T800480PCAP](#) [P6171DPR-DC-RS](#) [P6171DPR-DC-U](#) [MIKROMEDIA 4 FOR STM32F4 CAPACITIVE FPI](#)
[MIKROMEDIA 3 FOR STM32F4 CAPACITIVE FPI](#) [TN0216ANVNANN-GN00](#) [TN0104ANVAANN-GN00](#) [TN0181ANVNANN-GN00](#)
[MIKROMEDIA 5 FOR TIVA CAPACITIVE](#) [MIKROMEDIA 4 FOR TIVA CAPACITIVE](#) [MIKROMEDIA 4 FOR PIC32MZ CAPACITIVE](#)
[RVT43ULFNWC03 V4](#) [SM-RVT101HVBNWCA0](#) [SM-RVT35HHBFWCA0](#) [SM-RVT35HHBNWCA0](#) [SM-RVT43HLBFWCA0](#) [SM-](#)
[RVT43HLBNWCA0](#) [SM-RVT50HQBFWCA0](#) [SM-RVT50HQBNWCA0](#) [SM-RVT70HSBFWCA0](#) [SM-RVT70HSBNWCA0](#) [11769](#)
[MIKROMEDIA FOR DSPIC33](#) [MIKROMEDIA FOR PIC24](#) [MIKROMEDIA FOR PIC32](#) [MIKROMEDIA FOR STELLARIS M3](#)
[MIKROMEDIA HMI 3.5 RES](#) [MIKROMEDIA HMI 5](#) [MIKROMEDIA PLUS FOR FT90X](#) [MIKROMEDIA PLUS FOR PIC32MX7 SHIELD](#)
[MIKROMEDIA PROTO SHIELD](#) [MIKROMEDIA 5 FOR TIVA](#) [MIKROMEDIA 5 FOR TIVA SHIELD](#) [MIKROMEDIA 7 FOR STM32F4](#)
[MIKROMEDIA CONNECT SHIELD](#) [MIKROMEDIA FOR ARM](#) [MIKROMEDIA FOR PSOC5LP](#) [MIKROMEDIA GAMING SHIELD](#)
[MIKROMEDIA HMI 4.3 UXB](#) [MIKROMEDIA HMI 5 RES](#) [MIKROMEDIA HMI 5 UXB](#) [MIKROMEDIA HMI 7](#) [MIKROMEDIA HMI](#)
[BREAKOUT BOARD](#) [RVT50UQTNWC05](#) [RVT70AQFNWC00](#) [18207](#) [PIS-0260](#) [GEN4-ULCD-50D-PI](#) [GEN4-ULCD-70D](#)