



Compatible
With:



i.MX



ELI156-IPHW

- **High Bright Extended Temperature Version**
- **15.6" FHD LCD Panel with LED Backlight**
- **MSRP (Qty Volume): \$595.00**
- **MSRP (Qty 1): \$700.00**

Features

- PCAP Touch Screen with USB Device Interface
- Plug and Play interface to standard SBCs
- HDMI or DVI Input
- +12 VDC Input
- 1300 nits Brightness (typical)
- 750:1 Contrast Ratio (typical)
- EDID Support for Automatic Screen Sizing
- -30° to +85° C operating temperature range
- Franchised Distribution Stocking
- Part Number: ELI156-IPHW
- Scratch Resistant 1.8mm Cover Glass

Specifications

- Screen Size (inches): 15.6
- Touch Screen Type: PCAP
- Display Technology: a-Si TFT Active Matrix
- Touch Screen Interface: USB Device
- Brightness (nits typ): 1300
- Resolution: 1920 x 1080 (FHD)
- Contrast Ratio (typ): 750 : 1
- Aspect Ratio: Wide 16:9
- Colors: 16.7M (24 bit)
- Horizontal Viewing Angle: 88° / 88°
- Vertical Viewing Angle: 88° / 88°
- Surface Finish: Anti-glare
- Touch Panel Hardness: ≥7H
- Active Area (in mm) (W x H): 344.16 x 193.59
- Response Time (ms typ): 10 ton, 15 toff
- Backlight Life (K hrs typ): 50
- EDID for Auto Screen Sizing: Yes
- Display Interface Input Mode: HDMI / DVI
- Input Voltage: 12 VDC (±10% tolerance)
- Power Consumption (mA typ/max): 2600/3100 @12 VDC
- Backlight Power Consumption up to 93% of Total
- USB Power Consumption: (mA typ/max): 50/100 @5.0 VDC
- Operating Temperature: -30° to 85° C¹
- Storage Temperature: -40° to 85° C
- Mounting: 4x M3 Screws
- Plug & Play with Standard SBCs: Yes
- Size: 392.8 (W) x 250.3 (H) x 18.6 (D) mm
- Weight (grams typ): 1800
- RoHS Compliant: Yes

¹As measured at LCD's front/rear surfaces including self heat
See Mechanical and Mounting Info in the User's Manual



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Display Modules](#) category:

Click to view products by [Future Designs](#) manufacturer:

Other Similar products are found below :

[P6153-PR](#) [TDP0700T800480PCAP](#) [P6171DPR-DC-RS](#) [P6171DPR-DC-U](#) [MIKROMEDIA 4 FOR STM32F4 CAPACITIVE FPI](#)
[MIKROMEDIA 3 FOR STM32F4 CAPACITIVE FPI](#) [TN0216ANVNANN-GN00](#) [TN0104ANVAANN-GN00](#) [TN0181ANVNANN-GN00](#)
[MIKROMEDIA 5 FOR TIVA CAPACITIVE](#) [MIKROMEDIA 4 FOR TIVA CAPACITIVE](#) [MIKROMEDIA 4 FOR PIC32MZ CAPACITIVE](#)
[RVT43ULFNWC03 V4](#) [SM-RVT101HVBFWCA0](#) [SM-RVT101HVBNWCA0](#) [SM-RVT35HHBFWCA0](#) [SM-RVT35HHBNWCA0](#) [SM-](#)
[RVT43HLBFWCA0](#) [SM-RVT43HLBNWCA0](#) [SM-RVT50HQBNWCA0](#) [SM-RVT70HSBFWCA0](#) [SM-RVT70HSBNWCA0](#) [PIM579](#)
[1215686](#) [PIM543](#) [DFR0678](#) [P6191PR-DC-U-V3](#) [11769](#) [MIKROMEDIA FOR DSPIC33](#) [MIKROMEDIA FOR PIC24](#) [MIKROMEDIA FOR](#)
[PIC32](#) [MIKROMEDIA FOR STELLARIS M3](#) [MIKROMEDIA HMI 3.5 RES](#) [MIKROMEDIA HMI 5](#) [MIKROMEDIA PLUS FOR FT90X](#)
[MIKROMEDIA PLUS FOR PIC32MX7 SHIELD](#) [MIKROMEDIA PROTO SHIELD](#) [14628](#) [MIKROMEDIA 5 FOR TIVA](#) [MIKROMEDIA 5](#)
[FOR TIVA SHIELD](#) [MIKROMEDIA 7 FOR STM32F4](#) [MIKROMEDIA CONNECT SHIELD](#) [MIKROMEDIA FOR ARM](#) [MIKROMEDIA](#)
[FOR PSOC5LP](#) [MIKROMEDIA GAMING SHIELD](#) [MIKROMEDIA HMI 4.3 UXB](#) [MIKROMEDIA HMI 5 RES](#) [MIKROMEDIA HMI 5](#)
[UXB](#) [MIKROMEDIA HMI 7](#) [MIKROMEDIA HMI BREAKOUT BOARD](#)