4.3" Capacitive Touch Screen LCD GUI





The uEZ GUI[®] unit is everything you need right out of the box to have a touch screen GUI instantly in your project.

Each uEZ GUI unit is available in two convenient forms. To get your project started quickly we offer a full development kit complete with JTAG debugger, power supply, cables, a microSD card and full documentation. The Dev Kit Part Number is uEZGUI-4088-43WQN. Once your design is complete, we also offer a cost-effective production module for prototypes or even for high volume production. The module includes the touchscreen display, all of the necessary hardware, and is supported by the uEZ[®] / FreeRTOS[™] open source software. The uEZ GUI module is available off-the-shelf from any of our franchised distributors under Part Number uEZGUI-4088-43WQN-BA.

Features

- 4.3" TFT WQGA 480 x 272 LCD Panel with Projected Capacitive Touch Screen
- NXP LPC4088 120MHz CPU with 512KB internal Flash
- 16MB SPIFI Serial Flash
- 8MB of SDRAM (optional to 32MB)
- High Speed SD interface supporting 15fps video playback
- 4GB microSD Memory Card
- USB Device Mini-AB for 5.0VDC power and PC communications
- USB Host support through adapter cable
- NV Data Storage via 4KB Internal EEPROM
- Internal Real-Time Clock with Supercap Backup
- Speaker, 3-axis Accelerometer, Temperature Sensor
- PMOD Type 2A connector with SPI and optional I2C
- Mini-JTAG Debug Connector
- External Expansion via two I/O Connectors (70 pins) - UART, I2C, SPI, USB Host/Device, RMII Ethernet









www.teamfdi.com (256) 883-1240



@TeamFDI #TeamFDI



Rowley Associates

Youtube.com/ **FDIProducts**



SEGGER



Module Specifications

- Module P/N: uEZGUI-4088-43WQN-BA
- Contrast Ratio: 500 typical
- Luminance: 340 cd/m2 typical
- Viewing Angle Horizontal: 70° L / 70° R
- Viewing Angle Vertical: 70° U /50° D
- Power consumption typ/max: 350/500mA @ 5.0VDC
- Operating Temperature Range: -20°C to +70°C

- Overall Size: 4.60"W x 2.84"H x 0.56"T
- Viewable area: 3.74"W x 2.12"H
- Weight: 103g
- Touch Resolution: 480x272
- Number Simultaneous Touches:1

µEZ[®] OSAL

- Glass Overlay: 0.7mm
- Glass Hardness: 6H

The **uEZGUI-4088-43WQN-BA** is the stand alone System On Module version and is priced at less than \$175.00 in volume. This unit is designed to be used as an "off-the-shelf" Graphical User Interface (GUI) or Human Machine Interface (HMI) in a variety of end customer applications. The miniature, self-contained design is well suited to embed directly into your product or FDI offers prepackaged versions. FDI also offers low cost customization services for customer specific hardware, software or packaging applications at volumes of 500 units or more.

Software

μEZ[®] (pronounced Muse) is an open source rapid development platform that supplies application developers with an extensive library of open source software, drivers, and processor support all under a common framework. μEZ[®] allows companies to focus on innovation and their value-added applications while minimizing development time and maximizing software reuse.

The diagram to the right shows a typical embedded application stack. The μEZ° components comprise three primary categories to simplify embedded application development:

- Operating System Abstraction Layer (µEZ[®] OSAL)
- Sub-system drivers (ex: μEZ[®] TCP/IP, μEZ[®] USB, μEZ[®] Driver)
- Hardware Abstraction Layer (µEZ® HAL)

Software Included:

- uEZ[®] / FreeRTOS Rapid Development Platform
- uEZ[®] / SafeRTOS option for Medical/Safety Apps
- MicroSD card maps as USB Flash Drive to the PC
- Rowley CrossWorks Compiler and Tool Suite
- Segger J-Link Lite JTAG for programming and debug
- Customized versions available

Ordering Information

Kit Part Number: uEZGUI-4088-43WQN Suggested Resale Price: \$319.00(USD) Order Online at: www.uEZGUI.com or from any of our franchised distributors

Warranty: 30-day money back guarantee Phone 256-883-1240 Fax 256-883-1241 sales@teamfdi.com

FreeRTOS™ µEZ® HAL Hardware Peripheral API Embedded Microprocessor

Applications

OTG



Kit Contents:

- uEZGUI-4088-43WQN-BA Production Module
- USB Device cables for Power and PC communications
- AC Power Supply
- Mini JTAG Debugger with cables
- Micro SD Card

Download Users Manual, documents, schematics, and software examples at: www.teamfdi.com/uEZGUI







Rev 2.2 12/23/2014 All brand names and product names are trademarks or registered trademarks of their respective holder

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Display Development Tools category:

Click to view products by Future Designs manufacturer:

Other Similar products are found below :

 KIT 60121-3
 S5U13U11P00C100
 KIT 60145-3
 S5U13748P00C100
 DFR0413
 KIT95000-3
 LCD-16396
 PIM370
 1109
 MIKROE-2449

 MIKROE-2453
 131
 DEV-13628
 1590
 MIKROE-2269
 1601
 1770
 1947
 1983
 1987
 2050
 2218
 2260
 2345
 2418
 2423
 2454
 2455
 2478

 2674
 SK-220RD-PI
 FIT0477
 333
 334
 TE-M321-SDK
 DFR0428
 cs-epapersk-03
 338
 DEV-14442
 FIT0478
 cs-paperino-01
 OM-E-OLE

 ALTHSMCMIPILCD
 ASD2421-R
 TDP0500T800480PCAP
 LCD-14048
 cs-epapersk-02
 2719
 LCD-01
 PIM113