

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)MAX}$	I_D
60V	2.8Ω@10V	0.34A
	3.6Ω@4.5V	

Feature

- ESD protection
- Advanced trench process technology
- High density cell design for ultra low on-resistance
- Very low leakage current in off condition
- In compliance with EU RoHS 2002/95/EC directives.
- Halogen-free

Application


- Specially designed for battery operated system, solid-state relays drivers, relays, displays, lamps, solenoids, memories, etc.

Package




SOT-23

Circuit diagram



Marking



Absolute maximum ratings (Ta=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V _{DS}	60	V
Gate-Source Voltage	V _{GS}	±20	V
Continuous Drain Current	I _D	0.34	A
Pulsed Drain Current	I _{DM}	1	A
Power Dissipation	P _D	0.35	W
Thermal Resistance from Junction to Ambient	R _{θJA}	357	°C/W
Junction Temperature	T _J	150	°C
Storage Temperature	T _{STG}	-55 ~ +150	°C

Electrical characteristics (T_A=25 °C, unless otherwise noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-source breakdown voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = 10µA	60			V
Zero gate voltage drain current	I _{DSS}	V _{DS} = 60V, V _{GS} = 0V			1	µA
Gate-body leakage current	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V			±10	µA
Gate threshold voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250µA	1.0		2.5	V
Drain-source on-resistance ¹⁾	R _{DS(on)}	V _{GS} = 10V, I _D = 0.5A		1.3	2.8	Ω
		V _{GS} = 4.5V, I _D = 0.2A		1.0	3.6	
Forward transconductance ¹⁾	g _{FS}	V _{DS} = 15V, I _D = 0.25A	100			mS
Dynamic characteristics²⁾						
Input Capacitance	C _{iss}	V _{DS} = 25V, V _{GS} = 0V, f = 1MHz		18		pF
Output Capacitance	C _{oss}			12		
Reverse Transfer Capacitance	C _{rss}			7		
Total Gate Charge	Q _g	V _{DS} = 10V, V _{GS} = 4.5V, ID = 0.2A			2.4	nC
Turn-on delay time	t _{d(on)}	V _{DD} = 30V, V _{GS} = 10V, I _D = 0.2A R _{GEN} = 10Ω			20	nS
Turn-off delay time	t _{d(off)}				40	
Source-Drain Diode characteristics						
Diode Forward voltage	V _{DS}	V _{GS} = 0V, I _S = 0.2A			1.3	V


Notes:

1) Pulse Test: Pulse Width < 300µs, Duty Cycle ≤ 2%.


2) Guaranteed by design, not subject to production testing.

Test Circuit

1) Gate charge test Circuit



2) Switch Time Test Circuit



Typical Characteristics

Figure1: Output Characteristics




Figure 3: On-resistance vs. Drain Current




Figure 5: Gate Charge Characteristics




Figure 2: Typical Transfer Characteristics




Figure 4: Body Diode Characteristics





Figure 6: Capacitance Characteristics



Typical Characteristics

Figure 7: Normalized Breakdown Voltage vs. Junction Temperature




Figure 9: Maximum Safe Operating Area




Figure 11: Maximum Effective Transient Thermal Impedance, Junction-to-Ambient (SOT-23)




Figure 8: Normalized on Resistance vs. Junction Temperature








Figure 10: Maximum Continuous Drain Current vs. Case Temperature



SOT-23 Package Information


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP.		0.037 TYP.	
e1	1.800	2.000	0.071	0.079
L	0.550 REF.		0.022 REF.	
L1	0.300	0.500	0.012	0.020

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for MOSFET category:

Click to view products by FUXINSEMI manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FDPF9N50NZ](#) [FW216A-TL-2W](#) [FW231A-TL-E](#) [APT5010JVR](#) [NTNS3A92PZT5G](#)
[IRF100S201](#) [JANTX2N5237](#) [2SK2464-TL-E](#) [2SK3818-DL-E](#) [FCA20N60_F109](#) [FDZ595PZ](#) [STD6600NT4G](#) [FSS804-TL-E](#) [2SJ277-DL-E](#)
[2SK1691-DL-E](#) [2SK2545\(Q,T\)](#) [D2294UK](#) [405094E](#) [423220D](#) [MCH6646-TL-E](#) [TPCC8103,L1Q\(CM](#) [367-8430-0972-503](#) [VN1206L](#)
[424134F](#) [026935X](#) [051075F](#) [SBVS138LT1G](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [751625C](#) [873612G](#) [IRF7380TRHR](#)
[IPS70R2K0CEAKMA1](#) [RJK60S3DPP-E0#T2](#) [RJK60S5DPK-M0#T0](#) [APT5010JVFR](#) [APT12031JFLL](#) [APT12040JVR](#) [DMN3404LQ-7](#)
[NTE6400](#) [JANTX2N6796U](#) [JANTX2N6784U](#) [JANTXV2N5416U4](#) [SQM110N05-06L-GE3](#) [SIHF35N60E-GE3](#)