


FEATURES:


- ❖ Protects one bi-directional I/O line
- ❖ Low clamping voltage
- ❖ Low operating voltage: 5V
- ❖ ROHS compliant



DFN1006

MAIN APPLICATIONS

- ❖ Cell Phone Handsets and Accessories
- ❖ Personal Digital Assistants (PDA's)
- ❖ Notebooks, Desktops, and Servers
- ❖ Portable Instrumentation
- ❖ Pagers
- ❖ Microprocessor based equipment



PIN Configuration

PROTECTION SOLUTION TO MEET

- ❖ IEC61000-4-2 (ESD) $\pm 20\text{kV}$ (air), $\pm 20\text{kV}$ (contact)
- ❖ IEC61000-4-5 (Lightning) 4.0A (8/20us)

MECHANICAL CHARACTERISTICS

- ❖ Package DFN1006
- ❖ Molding Compound Flammability Rating : UL 94V-O
- ❖ Quantity Per Reel : 10,000pcs
- ❖ Lead Finish : Lead Free
- ❖ Marking code: 5O

ABSOLUTE MAXIMUM RATINGS ($T_A=25^\circ\text{C}$, RH=45%-75%, unless otherwise noted)


Parameter	Symbol	Value	Unit
Storage temperature range	T_{stg}	-55 to +150	$^\circ\text{C}$
Operating junction temperature range	T_j	-55 to +125	$^\circ\text{C}$
Lead Soldering Temperature	T_L	260 (10 sec.)	$^\circ\text{C}$
Peak pulse power dissipation on 8/20 μs waveform	P_{PP}	88	W
ESD per IEC 61000-4-2 (Air)	V_{ESD}	+/- 20	kV
ESD per IEC 61000-4-2 (Contact)		+/- 20	

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Reverse Working Voltage	V_R				5	V
Reverse Breakdown Voltage	V_{BR}	$I_T = 1\text{mA}$	6.0			V
Reverse Leakage Current	I_R	$V_R = 5\text{V}$			1.0	μA
Peak Pulse Current	I_{PP}	$t_p = 8/20\mu\text{s}$			4.0	A
Clamping Voltage	V_C	$I_{PP} = 1.0\text{A}, t_p = 8/20\mu\text{s}$			13	V
		$I_{PP} = 4.0\text{A}, t_p = 8/20\mu\text{s}$			22	V
Junction Capacitance	C_J	$V_R = 0\text{V}, f = 1\text{MHz}$		0.22	0.35	pF

RATINGS AND V-I CHARACTERISTICS CURVES

Symbol	Parameter
V_{RWM}	Reverse Standoff Voltage
I_R	Max Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
V_C	Clamping Voltage @ I_{PP}
I_{PP}	Max Peak Pulse Current
R_{DYN}	Dynamic Resistance
C_J	Junction Capacitance
P_{PP}	Peak Pulse Power



RATINGS AND V-I CHARACTERISTICS CURVES ($T_A=25^\circ\text{C}$, unless otherwise noted)




Fig. 1. 8/20 μs pulse waveform according to
IEC 61000-4-5 and IEC 61643-321




Fig. 2. ESD pulse waveform according to
IEC 61000-4-2




Fig. 3. Power Derating Curve





Fig. 4. Junction Capacitance vs VR

PACKAGE MECHANICAL DATA


Side view

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.350	0.450	0.014	0.018
D	0.550	0.650	0.022	0.026
E	0.950	1.050	0.037	0.041
D1	0.420	0.520	0.017	0.020
E1	0.550	0.650	0.022	0.026
L	0.270	0.370	0.011	0.015
L1	0.000	0.100	0.000	0.004

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for ESD Suppressors / TVS Diodes category:

Click to view products by FUXINSEMI manufacturer:

Other Similar products are found below :

[60KS200C](#) [D18V0L1B2LP-7B](#) [D5V0F4U5P5-7](#) [DESD5V0U1BB-7](#) [NTE4902](#) [P4KE27CA](#) [P6KE11CA](#) [P6KE39CA-TP](#) [P6KE8.2A](#)
[SA110CA](#) [SA60CA](#) [SA64CA](#) [SMBJ12CATR](#) [SMBJ33CATR](#) [SMBJ8.0A](#) [ESD101-B1-02ELS](#) [E6327](#) [ESD105-B1-02EL](#) [E6327](#) [ESD112-B1-02EL](#) [E6327](#) [ESD119B1W01005E6327XTSA1](#) [ESD5V0L1B02VH6327XTSA1](#) [ESD7451N2T5G](#) [19180-510](#) [CPDT-5V0USP-HF](#)
[3.0SMCJ33CA-F](#) [3.0SMCJ36A-F](#) [HSPC16701B02TP](#) [D3V3Q1B2DLP3-7](#) [D55V0M1B2WS-7](#) [DESD5V0U1BL-7B](#) [DRTR5V0U4SL-7](#)
[SCM1293A-04SO](#) [ESD200-B1-CSP0201](#) [E6327](#) [SM12-7](#) [SMF8.0A-TP](#) [SMLJ45CA-TP](#) [SMQA1000T1G](#) [CEN955 W/DATA](#) [82350120560](#)
[VESD12A1A-HD1-GS08](#) [CPDUR5V0R-HF](#) [CPDQC5V0U-HF](#) [CPDQC5V0USP-HF](#) [CPDQC5V0-HF](#) [IP4042CX5/LF,135](#) [D1213A-01LP4-7B](#) [D1213A-02WL-7](#) [1SMB33CAT3G-XYZ](#) [MMAD1108/TR13](#) [5KP100A](#) [5KP15A](#)