

# RB751V40T1G


SMD Small Signal Schottky Diode

#### **FEATURES**

- Low current rectifier schottky diode
- Low voltage, low inductance
- For power supply

#### MAKING: 5





#### Maximum Ratings and Electrical Characteristics, Single Diode @Ta=25°C

Parameter	Symbol	Limit	Unit
Peak reverse voltage	$V_{RM}$	40	V
DC reverse voltage	V <sub>R</sub>	30	V
Mean rectifying current	lo	0.03	А
Non-repetitive Peak Forward Surge Current@t=8.3ms	I <sub>FSM</sub>	0.2	А
Power dissipation	P <sub>D</sub>	200	mW
Thermal Resistance Junction to Ambient	$R_{\theta JA}$	500	°C/W
Operating Junction Temperature Range	Tj	-40 ~ +125	ĉ
Storage Temperature Range	T <sub>stg</sub>	-55 ~ +150	°C


#### Electrical Ratings @Ta=25°C

Parameter	Symbol	Min	Тур	Мах	Unit	Conditions
Forward voltage	VF			0.37	V	I <sub>F</sub> =1mA
Reverse current	I <sub>R</sub>			0.5	μA	V <sub>R</sub> =30V
Capacitance between terminals	Cτ		2		pF	V <sub>R</sub> =1V, f=1MHZ





# RB751V40T1G

SMD Small Signal Schottky Diode



### **Typical Characteristics**





## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Schottky Diodes & Rectifiers category:

Click to view products by FUXINSEMI manufacturer:

Other Similar products are found below :

MA4E2039 MA4E2508M-1112 MBR0530L-TP MBR10100CT-BP MBR1545CT MMBD301M3T5G RB160M-50TR BAS16E6433HTMA1 BAS 3010S-02LRH E6327 BAT 54-02LRH E6327 IDL02G65C5XUMA1 NSR05F40QNXT5G NSVR05F40NXT5G NTE555 JANS1N6640 SB07-03C-TB-H SK310-T SK33A-TP SK34B-TP SS3003CH-TL-E PDS3100Q-7 GA01SHT18 CRS10I30A(TE85L,QM MA4E2501L-1290 MBRB30H30CT-1G JANTX1N5712-1 SB007-03C-TB-E SK33B-TP SK35A-TP SK38B-LTP NTE505 NTSB30U100CT-1G VS-6CWQ10FNHM3 CRG04(T5L,TEMQ) ACDBA1100LR-HF ACDBA1200-HF ACDBA240-HF ACDBA3100-HF CDBQC0530L-HF ACDBA260LR-HF ACDBA1100-HF MA4E2502L-1246 10BQ015-M3/5BT 10BQ060-M3/5BT NRVB130LSFT1G CRS08TE85LQM PMAD1108-LF B120Q-13-F 1N5819T-G B0530WSQ-7-F