

CUSTOMER _____

CUSTOMER'S P/N _____

DESCRIPTION _____ SMD POWER INDUCTOR _____

SGTE PART NO. _____ GPSV1365-100MS01 _____

SAMPLE NO. S21102902 REVISION NO. A1 DATE 29-Oct.-21

SPECIFICATION FOR APPROVAL

FULLY APPROVED	REVISE APPROVED

SGTE 感通科技

深圳感通科技有限公司 (大陸工廠)

GANTONG TECHNOLOGY (SHENZHEN) CO., LTD.

深圳市平湖街道平湖村萬福路 26 號

No.26 Wan fu Road, Ping hu Village. Ping hu town, Shenzhen City.

Tel: 0755-28457600

Fax: 0755-28452952

感通科技有限公司 (台灣辦事處)

臺北縣汐止市新台 5 路一段 77 號 10 樓之 7

10F~7, NO.77, Sec.1, Hsin Tai 5 Road, Shi-chi City, Taipei.

Tel: 886-2-8698-2341

Fax: 886-2-8698-2342

納美科技股份有限公司 (香港辦事處)

LAPEE TECHNOLOGY LIMITED

香港九龍尖沙嘴加連威老道嘉蘭圍 5-11 號利時商業大廈 17 樓 1713 室

Room 1713 17/F, Rise Commercial Bldg5-11 Granville Circuit, Granville Rd, Tsim Sha Tsui., Kln

Tel: 852-25301111

Fax: 852-25371111

<http://www.sgte.cn>

INDEX

COVER PAGE

■ SHAPE & DIMENSION.....	1-8
■ ELECTRICAL CHARACTERISTICS AND EXTERNAL TEST REPORT.....	2-8
■ ELECTRICAL CHARACTERISTICS.....	3-8
■ ELECTRICAL CHARACTERISTICS.....	4-8
■ ELECTRICAL CHARACTERISTICS.....	5-8
■ PACKING FOR SPECIFICATION.....	6-8
■ GENERAL CHARACTERISTICS.....	7-8
■ THE CONDITION OF REFLOW.....	8-8


APPROVED BY	CHECKED BY	DRAWING BY
田一	王康	黄荣英

SPECIFICATION

**RoHS
COMPLIANT**


Customers Part Number	Item Name	Date
	Power Inductor	29-Oct.-21
Gan Tong Part NO.	Sample NO.	Page
GPSV1365-100MS01	S21102902	1-8

External Dimensions Unit (mm)




A	13.45±0.5
B	12.6±0.2
C	6.5 Max
D	≤0.2
E	5.8±0.5
F	2.3±0.5
G	14.5REF
H	8.0 REF
I	5.0REF

Connection



Recommended Land Pattern



Electrical Specification

Measurement Item	Unit Tolerance	Specification	Test Frequency	Test Instrument
L	uH (±20%)	10uH ±20%	100KHz/1V	LCR Meter Agilent/4284A or Chroma /11300
DCR	mΩ	20mΩ(Max)		Chroma /16502
I rms	Amps	10A	100KHz/1V	LCR Meter Agilent/4284A+42841A
I sat	Amps	16A	100KHz/1V	or Chroma /11300+3302+1320+1320S

·I rms: Current that causes a 40°C temperature rise from 25°C ambient.

·I sat: DC current at which the inductance drops 35% from it's value without current.

·All test Data is referenced to 25°C ambient.

·Operating Temperature Range: -25°C to +125°C

TEST REPORT

**RoHS
COMPLIANT**

Customers Part Number	Item Name	Date	
	Power Inductor	29-Oct.-21	
Gan Tong Part NO.	Sample NO.	Revision No.	Page
GPSV1365-100MS01	S21102902	A	2-8

Electrical Characteristic

Item	L0A	DCR	I rms	I sat
Specification	10uH	20mΩ	10Amps	16Amps
Tolerance	±20%	Max	$\Delta T \leq 40^\circ\text{C}$	$L \geq 65\%$
1	9.111	15.76	28.6°C	79.7%
2	9.041	15.66		
3	9.267	15.12		
4	9.420	15.42		
5	9.677	15.63		
6	9.156	14.98		
7	9.291	15.32		
8	9.289	15.05		
9	9.417	15.72		
10	9.316	15.69		
\bar{X}	9.299	15.44		
σ	0.17	0.28		

External Dimensions

Item	A	B	C	D	E	F
Specification	13.45	12.6	6.5		5.8	2.3
Tolerance	±0.5	±0.2	Max	≤0.2	±0.5	±0.5
1	13.38	12.54	6.37	0.12	5.80	2.09
2	13.37	12.53	6.32	0.10	5.81	2.10
3	13.36	12.53	6.35	0.15	5.80	2.10
4	13.39	12.56	6.39	0.13	5.80	2.12
5	13.38	12.54	6.42	0.11	5.81	2.17
6	13.37	12.54	6.33	0.11	5.80	2.20

7	13.41	12.53	6.39	0.13	5.80	2.09
8	13.42	12.54	6.41	0.12	5.80	2.18
9	13.38	12.54	6.32	0.15	5.80	2.27
10	13.47	12.57	6.38	0.14	5.80	2.15
\bar{X}	13.39	12.54	6.37	0.13	5.80	2.15
σ	0.03	0.01	0.03	0.02	0.01	0.06

Inductance measured at 100KHz/1Vrms.

Electrical specifications at 25°C. Humidity 60±10%

ELECTRICAL CHARACTERISTICS


**RoHS
COMPLIANT**

Customers Part Number	Item Name	Date
	Power Inductor	29-Oct.-21
Gan Tong Part NO.	Sample NO.	Page
GPSV1365-100MS01	S21102902	3-8

Inductance VS DC current

IDC	L	%LOA				
0A	9.279	100.0%				
2A	9.307	100.3%				
4A	9.142	98.5%				
6A	8.896	95.8%				
8A	8.610	92.8%				
10A	8.303	89.5%				
12A	8.014	86.4%				
14A	7.703	83.0%				
16A	7.400	79.7%				
18A	7.108	76.6%				

CONDITTON:100KHz/1.0Vrms



ELECTRICAL CHARACTERISTICS


RoHS
COMPLIANT

Customers Part Number	Item Name	Date
	Power Inductor	29-Oct.-21
Gan Tong Part NO.	Sample NO.	Page
GPSV1365-100MS01	S21102902	4-8

DC current VS Temperature

Time	L (μ H)	T ($^{\circ}$ C)	Δ T($^{\circ}$ C)			
08:30	7.978	31.6				
09:00	7.968	58.5	26.9			
09:30	7.966	60.2	28.6			
10:30	7.966	60.2	28.6			
11:30	7.966	60.2	28.6			
12:30	7.966	60.2	28.6			
13:30	7.966	60.2	28.6			

CONDITTON: Load 10A



Inductance VS Temperature


ELECTRICAL CHARACTERISTICS

RoHS
COMPLIANT

Customers Part Number	Item Name	Date
	Power Inductor	29-Oct.-21
Gan Tong Part NO.	Sample NO.	Page
GPSV1365-100MS01	S21102902	5-8

Inductance VS Frequency

FREQ.	L (μ H)					
1KHZ	9.524					
10KHZ	9.561					
100KHZ	9.280					
500KHZ	9.176					
800KHZ	9.201					
1000KHZ	9.232					




PACKING FOR SPECIFICATION


**RoHS
COMPLIANT**

Customers Part Number	Item Name	Date
	Power Inductor	29-Oct.-21
Gan Tong Part NO.	Sample NO.	Page

Packaging Information:




TYPE	A(mm)	B(mm)	C(mm)	D(mm)
13''*24mm	24±0.5	100±2	13.5±0.5	330



TYPE	A	B	C	W	P
GPSR1365	500	24	330	24	20

Tearing Off Force

The force for tearing off cover tape is 15 to 60 grams in the arrow direction under the following conditions.



Room Temp. (°C)	Room Humidity (%)	Room atm (hPa)	Tearing Speed mm/min
5~35	45~85	860~1060	300

Application Notice

• Storage Conditions

To maintain the solderability of terminal electrodes:


1. Temperature and humidity conditions: Less than 30°C and 70% RH.
2. Recommended products should be used within 6 months from the time of delivery.
3. The packaging material should be kept where no chlorine or sulfur exists in the air.

• Transportation

1. Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
2. The use of tweezers or vacuum pick up is strongly recommended for individual components.
3. Bulk handling should ensure that abrasion and mechanical shock are minimized.

GENGRAL CHARACTERISTICS


**RoHS
COMPLIANT**

.STORAGE TEMPERATURE :	25°C~30°C HUMIDITY 45~85% RH
2.OPERATING TEMPERATURE RANGE :	-30°C ~+125°C(CONTAIN HEATING COIL)
3.EXTERNAL APPEARANCE :	NO EXTERNAL DEFECTS CAN BE FOUND IN THE VISUAL INSPECTION.
4. TERMINAL STRENGTH :	NO TERMINAL DETACHMENT SHOULD BE FOUND WHEN THE DEVICE IS PUSHED IN TWO DIRECTIONS OF X AND Y WITH THE FORCE OF 10.0N FOR 10±2 SECONDS AFTER SOLDERING BETWEEN COPPER PLATE AND THE TERMINALS.(REFER TO FIGURE AT RIGHT)
	
5.HEAT ENDURANCE TEST :	REFER TO <u>Recommended Soldering Temperature Graph</u> (AT PAGE 2) .
6.INSULATING RESISTANCE :	THE INSULATION RESISTANCE SHOULD BE OVER 100MΩ WHEN D.C.100V IS APPLIED TO THE WINDING –CORE. MEANWHILE NO STRUCTURE AND ELECTRIC DEFECTS SHOULD BE FOUND FOR 1 MINUTE.
7. TEMPERATURE FEATURE :	INDUCTANCE COEFFICIENT IS (0 ~ 2000)x10 ⁻⁶ (-25 ~ +85°C)
8. HUMIDITY TEST :	INDUCTANCE DEVIATION IS WITHIN ±5.0% AND NO STRUCTURE AND ELECTRIC DEFECTS CAN BE FOUND AFTER 96 HOURS TEST UNDER THE CONDITION OF RELATIVE HUMIDITY OF 90 ~ 95% AND TEMPERATURE OF 40±2°C. AND 1 HOUR STORAGE UNDER ROOM AMBIENT CONDITIONS AFTER THE DEVICE IS WIPED WITH DRY CLOTH.
9. VIBRATION TEST :	INDUCTANCE DEVIATION IS WITHIN ±5.0% AFTER 1 HOUR SWEEPING VIBRATION IN EACH THREE DIRECTIONS. NAMELY, FREQUENCY IS 10 ~ 55 ~ 10Hz AND THE AMPLITUDE OF 1MINUTE CYCLE IS 1.5mm PP.
10.SHOCK TEST :	INDUCTANCE DEVIATION IS WITHIN ±5.0% AFTER THE TEST WITH GOM-BLOCK SHOCK TESTING MACHINE,ONCE IN EACH OF THE THREE PERPENDICULAR AXIS DIRECTIONS. THE SHOCK ACCELERATION IS 981m/s ² .


THE CONDITION OF REFLOW

**RoHS
COMPLIANT**

Wave Soldering



Hand soldering



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Inductors](#) category:

Click to view products by [Gantong](#) manufacturer:

Other Similar products are found below :

[CR32NP-151KC](#) [CR32NP-180KC](#) [CR32NP-181KC](#) [CR32NP-1R5MC](#) [CR32NP-390KC](#) [CR32NP-3R9MC](#) [CR32NP-680KC](#) [CR32NP-820KC](#) [CR32NP-8R2MC](#) [CR43NP-390KC](#) [CR43NP-560KC](#) [CR43NP-680KC](#) [CR54NP-181KC](#) [CR54NP-470LC](#) [CR54NP-820KC](#) [CR54NP-8R5MC](#) [70F224AI](#) [MGDQ4-00004-P](#) [MHL1ECTTP18NJ](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#) [PE-51506NL](#) [PE-53601NL](#) [PE-53602NL](#) [PE-53630NL](#) [PE-53824SNLT](#) [PE-92100NL](#) [PG0434.801NLT](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2LP-R47-R](#) [HC2-R47-R](#) [HC3-2R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-140L](#) [RCH664NP-4R7M](#) [RCH8011NP-221L](#) [RCP1317NP-332L](#) [RCP1317NP-391L](#) [RCR1010NP-470M](#)