

PRODUCT SPECIFICATIONS SHEET

<u>CAT NO.</u>	<u>PRODUCT NAME</u>
-----------------------	----------------------------

10-8109	Silicone (Z9)
10-8108	
10-8106	

DESCRIPTION:

Heat Sink Compound is silicone-based thermal grease made from a silicone fluid thickened with metal oxide fillers.

BENEFITS AND FEATURES:

Grease-like consistency; opaque white in color; zero bleed; very stable at elevated temperatures; excellent thermal resistance and high thermal conductivity; efficient thermal coupler; effective and positive heat sink sealers and heat transfer agent. The product offers high thermal conductivity, virtually no bleed or evaporation over a wide operating temperature range. It will not harden, dry out or melt after 1,000 hours at 200°C. Meets Mil-C-47009 and Mil-C-47113.

MAJOR APPLICATIONS:

Mounting transistors, diodes, rectifiers and resistors. Thermal joint compound for any device where efficient cooling is desired.

METHODS OF APPLICATION:

By hand brushing or wiping. Also, automatic dispensing methods save labor and material.

TYPICAL PROPERTIES:

<u>Property</u>	<u>Value</u>	<u>Test Method</u>
Consistency (Penetration, worked, 60x)	340	ASTM D-217
Specific Gravity, @ 25°C	2.2	ASTM D-70
Bleed, @ 200°C, 24 Hrs., %/Wt	0.50	FTM-321 MODIFIED
Evaporation, @ 200°C, 24 Hrs., %/Wt.	0.50	FTM-321 MODIFIED
Thermal Conductivity, @ 36°C W/m.-K	0.70	ASTM D-5470-06
Electrical Properties		
Dielectric strength, 0.05" gap, V/mil	400	ASTM D-149
Dielectric constant, 25°C @ 1,000 Hz	4.90	ASTM D-150
Dissipation factor, 25°C @ 1,000 Hz	0.0011	ASTM D-150
Volume Resistivity, ohm-cm	1.96 x 10 ¹⁵	ASTM D-257
Operating Temperature Range	-55°C to 205°C	
Flow Rate grams/min. @ 50PSI	5-18	
Appearance	White Paste	

SHELF LIFE, CLOSED CONTAINERS:

Product has a shelf life of up to 5 years from date of manufacture when stored in a sealed container at a temperature of 75°F. Extended shelf life is possible, but material should be checked for consistency before use and any excess oil should be removed.



**RoHS II
CERTIFICATE OF COMPLIANCE**

PART NUMBER:

PRODUCT:

SPECIFICATIONS: "Always EU RoHS II/ELV Compliant"

HARMONIZED TARIFF CODE:

COUNTRY OF ORIGIN:

EU RoHS II status is declared per Directive 2011/65/EU and its subsequent amendments. Therefore, based on the manufacturer's provided data, it is certified that the above part listed is RoHS II Compliant.

DATE:


SIGNED BY: Dan Heinen
Quality Manager

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fan Accessories](#) category:

Click to view products by [GC Electronics](#) manufacturer:

Other Similar products are found below :

[LZ31](#) [63070-2-4013](#) [64442-1-7612](#) [73816-2-3634](#) [854589-1](#) [95778-1-5171](#) [99485901](#) [RF119](#) [2151-4-7320](#) [KM36](#) [27453.32262](#) [95779-1-5171](#) [9614-2-4013](#) [99485906](#) [F92-B](#) [FK40-30](#) [FK80-45](#) [2103-4-7320](#) [2170-4-7320](#) [27453.32298](#) [R88ACPU001M1](#) [R88ACPU001M2](#)
[LZ215](#) [LZ22-2](#) [LZ24-1](#) [LZ30-9](#) [LZ37-2](#) [450-20-0025](#) [525-00-0009](#) [KM38](#) [420-05-0276](#) [450-20-0017](#) [450-20-0020](#) [50824-4-1040](#)
[04.846.1353.0](#) [04.846.1453.0](#) [055032](#) [08121](#) [08188](#) [08196](#) [09494-2-4039](#) [09576-2-4013](#) [109-1102](#) [109-019H](#) [54476-2-4013](#) [71883-2-4053](#)
[63071-2-4013](#) [52544-2-4037](#) [64445-1-7612](#) [73801-2-3634](#)