

HDMI splitter, 2 ports DSP-2PH4-03

PERFECT CONNECTION

- Sends a single HDMI signal to 2 displays
- Signal amplifier Improves signal quality
- Perfect for home theatres, classand conference rooms





Features

- Sends a single HDMI signal to 2 separate monitors, projectors or TV's
- The digital amplifier increases the transmission distance and also improves signal quality
- Supports 3D video

Packaging

Q'ty in crtn, pcs Crtn volume, CUM Crtn weight, kgs Individual package size LxWxH: Carton size LxWxH: Country of origin Barcode Customs code 45 0.02738 3.79 120x25x180 mm 370x370x200 mm CN 8716309091442 8517620000

Specifications

Ports: one input receptacle, 2 output HDMI output receptacles, 19 pin (A)

Interface standard: HDMI + HDCP v.1.4 (compatible with all HDMI versions)

Video formats: HDMI (480p/576i/576p/720p/1080i/1080P) Maximal single-link range: 1920x1080 pixels, 1080p Dual-link range: up to 3840x2160 at 30 Hz; color 30bit, 36bit

Supports Blue-Ray: 24/50/60fs/HD-DVD/xvYCC, audio DTS-HD/ Dolby-trueHD/DTS/Dolby-AC3/DSD/HD(HBR) Signal retiming support Working distance: up to 20 m at AWG26 HDMI cable (at 4K resolution 8 m input max, up to 12 m output)

Certificates



Package contents

Splitter USB power cable User manual

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for HDMI, Displayport & DVI Connectors category:

Click to view products by Gembird manufacturer:

Other Similar products are found below :

1775247-3 2-1932649-5 30-1231 30-528 2069485-1 30-504 30-519 30-542 47648-2000 2002-400 769-103/021-000 1932649-1 233-368NFG6-17NH PJ-210A FDB0901-M0DB300K6KF 3VD51203-3D6A-7H DV11201-H5R6-4F DSP-8PH4-03 AK-AD-38 AK-AD-39 A-DPM-HDMIF-002 A-HDMI90-FML A-MDPM-HDMIF4K-01 CDA0109 A-DPM-VGAF-02 CDA0110 CV0045A CCP-DPM-VGAM-6 CC-MDP-HDMI-6 67881 HAFBF HBLBH HBLBI HAFBG HAFBH HAGBF HAGBF HAGBG HAGBH HAGBI HAGBJ HBLBJ AABIE AABIF AABIG AABIH AABII AABIJ AABIK AABIL AACBE